

Hot water. Perfected.

TR

Residential Series

The water heater evolved.

Introducing trutankless – the most innovative tankless water heating technology. For years, we've worked closely with industry professionals to gather insights into tankless heating systems. The result? Cutting-edge technology that takes the tankless industry to a new level of sophistication. Energy conservation, long-term savings and endless hot water are what your customers want and that's exactly what our forward-thinking system delivers.



Notable Features

- : Self-flushing design eliminates most maintenance requirements
- : Comfort and economy modes
- : Ceramic insulation over robust copper heat exchanger
- : Custom Incoloy 9000 elements from Zoppas Industries superior hard water performance and longevity
- : Threaded for ease of service or replacement
- : Safety redundancy temperature and pressure relief, solid-state relays and software monitoring
- : Freeze protection
- : Each unit is pressure tested at the factory
- : Load balancing multiple units will communicate to manage power consumption across system
- : Load shedding reduce peak power consumption by managing other high demand appliances
- : Smart grid capable compatible with existing grid management infrastructure
- : Leak detection shuts down heating elements
- : Easy to specify with full suite of design files

Optional Equipment

- : Leak Detection with Automatic Water Cutoff Valve
- : Cold Climate Comfort Package
- : Recirculation Pump
- : Showerstart™ Water Saver

State of the Art Features

- : Plug & Play Set-up: Unit detects and supports voltages ranging from 220-240 VAC
- : Wi-Fi compatible
- : Compatible with home automation
- : Remote firmware updates
- : Installer App (Available for iOS and Android phones and tablets)
 - Automates service call notifications
 - Offers live support
 - Remote diagnostics
 - Usage log and fault history
- : User App (Available for iOS and Android phones and tablets)
- Remote temperature setting
- Leak detection with notification
- Error notifications
- Mange user parameters
- Calendar Settings define max. power consumption according to certain days and/or time of day

Warranty

- : Lifetime Limited Warranty on Heat Exchanger
- : 5-Year Parts Warranty

trutankless:

Specifications



Electrical Data

Voltage	220 - 240 VAC
Phase	Single, 50/60 Hz
Wattage	12.5 - 36.0 kW
Max. Amp, Load	40A x 4=160A
Min. Circuit Breaker Siz	e (See Table)
Required Wire Size	(See Table)

Inlet Water Data

Max. Inlet Temperature °F (°C)	131 (55)
Water Flow to Activate Unit = GPM (=LPM)	0.2 (.76)
Max. GPM = GPM (= LPM)	7.5 (28)
Max. Working Pressure PSI (bar)	80 (5.5)
Tested to Pressure PSI (bar)	150 (10.34)

Specifications

М	odel	Height	Width	Depth	Weight	Amperage	Voltage Range	kW Range	Main Panel Size	Breakers (two pole)	Copper Wire [optional]	Plumbing Fittings
Т	R36	17.2"	23.74"	5.5"	35.3 lbs	160	220 - 240	31.8 - 36.0	> 200 Amp	(2) 80A	(4) #4 AWG	Threaded 3/4" NPT
Т	R29	17.2"	23.74"	5.5"	35.3 lbs	120	220 - 240	26.4 - 28.8	200 Amp	(1) 125A [(2) 60A]	(2) #2 AWG [(4) #6 AWG)]	Threaded 3/4" NPT
Т	R24	17.2"	23.74"	5.5"	35.3 lbs	100	220 - 240	22.0 - 24.0	200 Amp	(1) 100 A [(2) 50A]	(2) #2 AWG [(4) #6 AWG]	Threaded 3/4" NPT
Т	R20	17.2"	23.74"	5.5"	35.3 lbs	80	220 - 240	17.6 - 19.2	150A	(1) 80A [(2) 40A]	(2) #4 AWG [(4) #8 AWG]	Threaded 3/4" NPT
Т	R15	17.2"	23.74"	5.5"	35.3 lbs	60	220 - 240	13.2 - 14.4	125A	(1) 60A [(2) 30A]	(2) #6 AWG [(4) #8 AWG]	Threaded 3/4" NPT

Sizing Chart (F°/GPM)

Model	75° Rise	65° Rise	55° Rise	45° Rise	35° Rise
TR36	3.0	3.5	4.4	5.3	7.5
TR29	2.4	2.8	3.3	4.0	5.9
TR24	2.0	2.4	2.7	3.3	4.9
TR20	1.7	2.0	2.2	2.6	3.9
TR15	1.3	1.5	1.6	2.0	2.9



Temp: 52°F to 61°F

Temp: 62°F to 77°F

Certifications

Membership and Associations













Temp: 37°F to 51°F



Call 855-TO-BUY-TRU to learn about the company's complete residential and commercial lineup.

15720 N. Greenway Hayden Loop, Unit 2 : Scottsdale, AZ 85260 : 855-TO-BUY-TRU : trutankless.com