

STAPLERS



1" - 2" x 1/2" (25.4 mm - 50.8 mm x 12.7 mm)
16 Gauge Medium Crown Stapler



1" - 2" x 7/16" (25.4 mm - 50.8 mm x 11.1 mm)
16 Gauge Medium Crown Stapler



1-1/2" (38.1 mm) 18 Gauge
Narrow Crown Stapler Kit

SPECIFICATIONS	D51431	D51430	DWFP12232
Fastener Style	16 Gauge Staple	16 Gauge Staple	18 Gauge Staple
Crown Size	1/2"	7/16"	1/4"
Fastener Length Capacity	1" - 2"	1" - 2"	1/2" - 1-1/2"
Magazine Capacity	160 Staples	160 Staples	100 Staples
Magazine Angle	Straight	Straight	Straight
Magazine Loading	Top Load	Top Load	Bottom Load
Operating Pressure	70 - 120 psi	70 - 120 psi	70 - 120 psi
Speed	20 Fasteners/Second @ 100 psi	20 Fasteners/Second @ 100 psi	—
Depth Setting	Tool-Free Thumb Wheel	Tool-Free Thumb Wheel	Tool-Free depth-of-drive adjustment with detents for proper setting of staples
Includes	(2) allen wrenches and replacement sequential trigger	(2) allen wrenches and replacement sequential trigger	Sample fasteners and 1/4" air fitting

DWFP55130

Two quick couplers
to easily support 2 nailers

3.0 SCFM delivered @ 90 PSI
pump, 2.5 gallon tank and
200 max PSI**
enables many nails to be fired
and provides quick recovery

Low 12 amp draw motor
provides easy start-up and
minimizes breaker tripping



Ball valve drain
allows for quick and
thorough tank draining

*PORTER-CABLE C2002 and DWFP55130
measured per ISO 3744

**Tested per ISO 1217



Low 71.5 dBA*
is 50% quieter than the
PORTER-CABLE pancake
style compressor

Roll cage and control panel
provide protection to key
compressor components

Durable, oil-free pump
provides extended
maintenance-free operation

**Convenient
cord wrap**
for easy storage



**Save space by operating
and storing horizontally
or vertically**



**Lightweight (36 lbs), thin
(12.6") and compact design**
is easy to carry and store

HAND CARRY- OIL-FREE COMPRESSORS



1 Gallon, 135 Max PSI,
Trim Compressor



6 Gallon, 165 Max PSI,
Pancake Compressor



2.5 Gallon, 200 Max PSI,
Quiet Trim Compressor

SPECIFICATIONS	D55140	DWFP55126	DWFP55130
Tank/Max PSI	1 Gallon / 135 PSI Max	6 Gallon / 165 PSI Max	2.5 Gallon / 200 PSI Max
SCFM@90 PSI	.75 scfm	2.6 scfm	3.0 scfm
Pump Type	Belt Drive Oil-Free	Belt Drive Oil-Free	Belt Drive Oil-Free
Amp Draw/Voltage	2.6A, 120V	10A, 120V	12A, 120V
Motor Type	Permanent Magnet	Universal	Universal
HP	0.3 Continuous HP	0.9 Continuous HP	1.1 Continuous HP
Noise Level	71.5 dBA	75.5 dBA	71.5 dBA
Tool Length	19"	16"	20.5" -
Tool Width	14.5"	16"	16.75"
Tool Height	9"	17.5"	12.5"
Tool Weight	24 lbs	30 lbs	36 lbs

Also available in 2" Brad Nailer Combo Kit
DWC1KIT-B