

Project:		
Fixture Type:		
Location:		
Contact:		

# One-Light Outdoor

Wall mounted • Wet location listed PROGRESS LED





## **Description:**

Get inspired with vintage undertones reminiscent of early 20th century train depots. This indoor-outdoor LED Wall lantern is cast aluminum. 3000K, 90+ CRI, 1,211 lumens 71.2 lumens/watt per module (source). Antique Nickel finish.

### **Specifications:**

- Antique Nickel (-81) (plated)
- Solid brass Construction
- Antique Nickel, painted white inside metal shade, White acrylic Diffuser
- LED Module is replaceable (part # 93053641)
- Inspired by vintage light fixtures found in early 20th century train stations.
- Solid brass construction with an Antique Nickle finish.
- Double arm attachment for stability.
- 1,211 lumens 71.2 lumens/watt per module (source)
- · 3000K color temperature, 90+ CRI.
- · Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- · Meets California Title 24 high efficacy requirements for outdoor use only

#### **Performance:**

Number of Modules	1	
Input Power	17w	
Input Voltage	120 V	
Input Frequency	60 Hz	
Lumens/LPW (Source)	1211/71.2 (LM-82)	
Lumens/LPW (Delivered)	751/43.9 (LM-79)	
CCT	3000 K	
CRI	90 CRI	
Life (hours)	60,000 (L70/TM-21)	
FCC	Meets FCC Title 47, Part 15 Class B	
Min. Start Temp	-30 °C	
Max. Operating Temp	30 ℃	
Warranty	5 year warranty	
Labels	cCSAus Wet location listed	
	ENERGY STAR® qualified	
	Meets California Title 24 high efficacy requirements	
	for outdoor use only	

# P5723-8130K9

#### Images:



#### **Dimensions:**

Width: 12" Depth: 13-1/4" Height: 12-1/4" H/CTR: 6-7/8"

Width: 12" Length: 12" Height: 4" Glass 2 Width: 6" Length: 6" Height: 1"

Glass



# One-Light Outdoor



# P5723-8130K9

## **Dimming Notes:**

P5723 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

## **Dimming Controls**

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.