




Schedule 40 Fittings Technical Repair Couplings Dimensions & Information

Repair Coupling - Spigot x Socket

PVC White with EPDM O-ring

Can be used as short-stroke Expansion Joint



Pressure Rating
1/2" - 2" 235 psi @ 73° F
2-1/2" - 4" 200 psi @ 73° F
6" & up 150 psi @ 73° F


Part Number	Size	L	L2	L3	M	T	Approx. Wt. (Lbs.)
S118-05	1/2	11/16	6-1/4	5-9/16	1-7/16	2-7/8	.24
S118-07	3/4	3/4	7-5/8	6-7/8	1-3/4	4	.44
S118-10	1	15/16	8-1/2	7-9/16	2-1/16	4-1/16	.67
S118-12	1-1/4	1	8-13/16	7-13/16	2-7/16	4-1/16	.87
S118-15	1-1/2	1-1/8	9-3/16	8-1/16	2-11/16	3-13/16	1.01
S118-20	2	1-3/16	9-15/16	8-3/4	3-1/4	4-5/16	1.59
S118-25	2-1/2	1-3/4	13-5/8	11-7/8	3-15/16	5-9/16	3.49
S118-30	3	1-7/8	13-11/16	11-13/16	4-5/8	5-9/16	4.29
S118-40	4	2-1/4	14-13/16	12-9/16	5-3/4	6-3/16	6.61
S118-60	6	3	17-3/16	14-3/16	8-7/16	6-5/8	14.72

Unit Must Be Thrust Blocked

Repair Coupling - Socket x Socket

PVC White with EPDM O-ring

Can be used as short-stroke Expansion Joint



Pressure Rating
1/2" - 2" 235 psi @ 73° F
2-1/2" - 4" 200 psi @ 73° F
6" & up 150 psi @ 73° F

Part Number	Size	L	L1	L2	L3	M	T	Approx. Wt. (Lbs.)
S119-05	1/2	11/16	7/8	7-3/8	5-13/16	1-7/16	2-7/8	.27
S119-07	3/4	3/4	1	8-3/4	7	1-3/4	4	.49
S119-10	1	15/16	1-1/8	9-11/16	7-5/8	2-1/16	4-1/16	.76
S119-12	1-1/4	1	1-1/4	10-3/16	7-15/16	2-7/16	4-1/16	1.01
S119-15	1-1/2	1-1/8	1-3/8	10-11/16	8-3/16	2-11/16	3-13/16	1.15
S119-20	2	1-3/16	1-1/2	11-5/8	8-15/16	3-1/4	4-5/16	1.81
S119-25	2-1/2	1-3/4	1-3/4	15-9/16	12-1/16	3-15/16	5-9/16	3.87
S119-30	3	1-7/8	1-7/8	15-3/4	12	4-5/8	5-9/16	4.94
S119-40	4	2-1/4	2-1/4	17-1/4	12-3/4	5-3/4	6-3/16	7.49
S119-60	6	3	3	20-1/2	14-1/2	8-7/16	6-5/8	18.07

Unit Must Be Thrust Blocked

Schedule 40 Fittings Technical
Short Repair Couplings Dimensions & Information



Short Repair Couplings

Space Saving, Compact Version of Standard Repair Coupling Requires 1/3 less Space




- Compact Telescoping Design
- Socket x Socket Configuration for Pipe Repair or Use as a Short-Stroke Expansion Joint
- Spigot x Socket Configuration for Replacing Damaged Fittings
- Both Configurations can be Easily Modified for Opposite Use
- Available in PVC White, Sizes 1/2" - 2"
- EPDM Double O-ring Seal
- Pressure Rated to 235 PSI @ 73°F (23°C)
- NSF® Certified for Potable Water Use

Repair Coupling - Short, Spigot x Socket

PVC White with EPDM O-ring

Pressure Rating
235 psi @ 73° F




Part Number	Size	L	L2	L3	M	T	Approx. Wt. (Lbs.)
SH118-05	1/2	11/16	4-7/8	4-3/16	1-7/16	1-15/16	.20
SH118-07	3/4	3/4	5-3/8	4-11/16	1-3/4	2-3/16	.31
SH118-10	1	15/16	5-3/4	4-13/16	2-1/16	2	.42
SH118-12	1-1/4	1	6-5/8	5-5/8	2-7/16	2-1/2	.60
SH118-15	1-1/2	1-1/8	6-15/16	5-13/16	2-11/16	2-1/2	.74
SH118-20	2	1-3/16	8-5/16	7-1/8	3-1/4	3	1.19

Unit Must Be Thrust Blocked

Repair Coupling - Short, Socket x Socket

PVC White with EPDM O-ring

Pressure Rating
235 psi @ 73° F



Part Number	Size	L	L1	L2	L3	M	T	Approx. Wt. (Lbs.)
SH119-05	1/2	11/16	7/8	5-7/8	4-1/4	1-7/16	1-15/16	.24
SH119-07	3/4	3/4	1	6-9/16	5-13/16	1-3/4	2-3/16	.36
SH119-10	1	15/16	1-1/8	7	4-15/16	2-1/16	2	.51
SH119-12	1-1/4	1	1-1/4	8	5-3/4	2-7/16	2-1/2	.74
SH119-15	1-1/2	1-1/8	1-3/8	8-3/8	5-7/8	2-11/16	2-1/2	.88
SH119-20	2	1-3/16	1-1/2	10	7-5/16	3-1/4	3	1.41

Unit Must Be Thrust Blocked