

FXP1800HD

FIBERGLASS PINNACLE PLATFORM LADDER





- ProTop™ multiple tool slots for increased productivity.
- Larger platform for added comfort.



- **SHOX™**—Advanced impact absorption protects fiberglass rails against damage.
- Raptor Boot™-Heavy duty boot protects fiberglass.

TYPE IAA LOAD CAPACITY

19 % LARGER PLATFORM

vs. other leading ladders.

WAIST-HIGH HANDRAIL at tool belt height for added comfort.

WORK FACING MULTIPLE DIRECTIONS

It is not recommended that worker face ladder steps while on platform.

HEAT TRANSFER TOP

No more OSHA fines due to missing duty rating labels. Scratch and UV resistant.

MODEL	HEIGHT TO PLATFORM	STEP DEPTH	MAX. REACH*	BOTTOM WIDTH	APPROX. SPREAD	APPROX. WEIGHT (LBS)	APPROX. CUBES
FXP1802HD	1' 11"	3"	8' 6"	21 7/8"	36"	20	81
FXP1803HD	2' 10"	3"	9' 5"	23 3/8"	42"	22	10,3'
FXP1804HD	3' 9"	3"	10' 5"	24 7/8"	48"	25	12.8'
FXP1806HD	5' 8"	3"	12' 3"	27 7/8"	61 1/2"	33	18.3'
FXP1808HD	7' 7"	3"	14' 2"	30 7/8"	74"	50	24.7'
FXP1810HD**	9' 6"	3"	16' 1"	33 7/8"	88"	62	31.9'
FXP1812HD**	11' 5"	3"	18'	36 7/8"	101 1/2"	75	40.1'

*Assumes 5' 7" person with 12" vertical reach


SERIES

FXP1700

FIBERGLASS PINNACLE PLATFORM LADDER











3.**sнox™**—Advanced impact absorption protects fiberglass rails against damage.



Raptor Boot™— Heavy duty boot protects fiberglass.



WIDE PLATFORM

Larger than other ladders in its class.

PERFECT TOOL BELT HEIGHT

Puts every tool on your tool belt within reach.

WORK FACING MULTIPLE DIRECTIONS

It is not recommended that worker face ladder steps while on platform.

HEAT TRANSFER TOP

No more OSHA fines due to missing duty rating labels. Scratch and UV resistant.

MODEL	HEIGHT TO PLATFORM	STEP DEPTH	MAX. REACH*	BOTTOM WIDTH	APPROX. SPREAD	APPROX. WEIGHT (LBS)	APPROX. CUBES
FXP1702	1' 11"	3"	8'6"	21 3/4"	33"	18	7.1'
FXP1703	2' 10"	3"	9' 5"	23 1/4"	39"	21	9.3'
FXP1704	3' 9"	3"	10' 5"	24 3/4"	45"	24	11.7'
FXP1706	5' 8"	3"	12' 3"	27 3/4"	57"	31	18.3'
FXP1708	7' 7"	3"	14' 2"	30 3/4"	69"	48	17'
FXP1710	9' 6"	3"	16' 1"	33 3/4"	81"	60	23.3'
FXP1712	11' 5"	3"	18'	36 3/4"	92"	73	38.4'

> *Assumes 5' 7" person with 12" vertical reach



^{**}Special duty: manufacturer tested to 375 lbs.