

# ROUND ACCESS DOOR



## Product Data Sheet



### Description

Elgen's Round Access Door is used to provide easy access into round ductwork.

### Standard Construction

**Door Panel:**

Manufactured from 20 GA ASTM A-653 G60.

**Gasket:**

Closed-cell neoprene gasket is UL94HF1 listed with service temperature range of 20° F to 200° F The gasket is bonded to the inside of the frame.

**Springs:**

Manufactured from zinc-plated steel

**Knobs:**

UL94HB listed polypropylene molded knobs with threaded metal inserts.

**Bolts:**

Manufactured from zinc-plated steel

Door Size	Made to Fit Ductwork
8" x 4"	Flat or Round 6" - 76"
12" x 8"	Flat or Round 12" - 76"
16" x 12"	Flat or Round 16" - 76"

### Features

Meets 2005 SMACNA Standards for pressure class & gauges(Refer tp page 7-2, figure 7-2)  
Provides More Effective Access Area  
No Frame To Install  
Tested up to 20 W.G. and negative 10W.G.

### Optional Construction

Stainless Steel 304  
Stainless Steel 316  
Aluminum

### Packaging

Door Size	Packaging
All Sizes	Each

### Guarantee

All Elgen products are guaranteed by Elgen Manufacturing against defective material.

#### Elgen Manufacturing

10 Railroad Ave, Closter NJ 07624

Tel: 800.503.9805 :: Fax: 201.964.9030

info@elgenmfg.com :: www.elgenmfg.com