

Big Boss Lanyard

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.13-2013, and ANSI A10.32-2012 regulations.

Big Boss Lanyards are suitable for the following applications:



Personal Fall Arrest: Big Boss Lanyards may be used in Personal Fall Arrest applications to support a MAXIMUM 1 Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 pounds. Maximum free fall is up to 12' for workers from 130-310 pounds, and up to 6' for workers from 311-420 pounds. Applicable D-ring: Dorsal.



Restraint: Big Boss Lanyards may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully extended length of lanyard. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



Work Positioning: Big Boss Lanyards may be used in Work Positioning applications. Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 pounds. Maximum allowable free fall is 2'. Applicable D-rings: Side, Shoulder.



For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs. for free fall up to 12', and 311-420 lbs. for free fall up to 6'.



Not all Big Boss Lanyards may be used in every application type. ALWAYS consider lanyard length, design, and any other structural components. ALWAYS read and adhere to product instructions and labels. Competent Person MUST determine Big Boss Lanyard compatibility.

Materials: polyester, nylon, and galvanized steel or aluminum.

Extended free fall for workers between 130-310 lbs. significantly increases amount of safe working zones, as it allows workers to tie off to anchorages below their harness D-ring. However, always avoid working with D-ring above anchorage connector if possible.

Increased shock absorption and deceleration distance allows workers between 311-420 lbs. to work in Fall Arrest applications with free fall of up to 6', which is not permissible with standard shock absorbing lanyards.

Part #	Size	Description
21300	6'	Big Boss Extended Free Fall Lanyard - Single Leg w/High Strength Stainless Steel Snap Hooks (2) & 12' Free Fall Shock Pack
21301	6'	Big Boss Extended Free Fall Lanyard - Single Leg w/High Strength Stainless Steel Snap Hook (1) & Rebar Hooks (2), & 12' Free Fall Shock Pack
21302	6'	Big Boss Extended Free Fall Lanyard - Double Leg w/High Strength Aluminum Snap Hooks (2) & 12' Free Fall Shock Pack
21303	6'	Big Boss Extended Free Fall Lanyard - Double Leg w/High Strength Aluminum Snap Hook (1) & Rebar Hooks (2), & 12' Free Fall Shock Pack
21310	6'	Big Boss Extended Free Fall Lanyard - Double Leg w/High Strength Snap Hook (1) & Rebar Hooks (2), 18" Extension, & 12' Free Fall Shock Pack