

24" C-SERIES BEVERAGE CENTER

HC24BB-3 | 24" INDOOR MODEL



QUALITY & INNOVATION
THAT **INSPIRES**



Solid Door Model



Glass Door Model



GENERAL C-SERIES FEATURES

- Zero-clearance hinging allows for abutment with surrounding cabinetry
- 525 Btu commercial-grade compressor
- Front-vented, RAPIDcool forced-air refrigeration system
- Commercial-grade stainless steel interior
- **Industry Exclusive** convertible door design allows all doors the ability to be converted to wood overlay from stainless steel
- **Industry Exclusive** adjustable, full-extension pull-out shelves (drawer models excluded)
- Stainless-steel ball-bearing glides provide smooth movement of shelves
- Low E, UV-coated glass provides industry leading insulation and protection.
- Digital temperature control
- Interior light
- Optional door locks and Industry-Exclusive drawer locks (factory installed)
- Stacking kit available
- Indoor and outdoor models available
- Also available - 24" Indoor Refrigerator and Wine Reserve, 24" Outdoor Refrigerator
- 5.2 cubic feet of capacity
- Industry Best Three Year Warranty plus additional three years on sealed system

HC24BB FEATURES

- Available with solid stainless steel door, solid wood overlay door, stainless steel glass door or wood overlay glass door
- Black vinyl-clad exterior
- Includes two (2) full-extension wine shelves and one (1) pull-out shelf
- Beverage Center temperature 33°- 48°F

Form No.HC24B-3
Rev. 06.15.2015

Overall Width	23-7/8" (60.64 cm.)
Overall Height	34-1/4" (86.96 cm.)
Overall Depth	24" (60.96 cm.)
Opening Width	24" (60.96 cm.)
Opening Height	34-3/8" (87.31 cm.)
Opening Depth	24" (60.96 cm.)
Refrigerated Volume	5.2 cu. ft.
Door Swing Clearance	25" (63.5 cm.) minimum
Electrical	115V, 60Hz., 1 Phase, 2.3 amps
Plumbing	None Required
Shipping Weight	195 lbs (88.45 kg.)
Annual Energy Consumption	274 kWh (<i>solid door</i>) 305 kWh (<i>glass door</i>)

HC24BB-3-1L*	Solid stainless steel door, hinge left
HC24BB-3-2L*	Solid wood overlay door, hinge left
HC24BB-3-3L*	Stainless steel glass door, hinge left
HC24BB-3-4L*	Wood overlay glass door, hinge left

50" [1270] Area in which electrical outlet must be located.

7 9/16" [192]

Power cord 6-5/8" [168] off floor.*

6 1/4" [159]

20" [508]

11 7/8" [302]

18 3/16" [461]

1 1/2" [36] Min. clearance from a corner to achieve 90° door swing.

90° Swing required for pull-out shelf clearance.

24 15/16" [634] Min. clearance for door swing.

* - Leg leveler can add 3/4" [19] to these dimensions when fully extended.

