

RADIANT HEATING SYSTEMS

MOTORIZED VALVE ACTUATOR

TECHNICAL BULLETIN



Application

The Motorized Valve Actuator (MVA) is a power-open and spring-closed unit. Its 24VAC, quick-opening motorized valve head provides individual flow control (per loop) on a multi-zoned manifold (manifold serving more than one zone).


Part Number

A3020522

FRONT VIEW



INTERNAL VIEW



Installation

The MVA mounts directly on the 1¼" Brass Valved Manifold and TruFLOW™ Classic Manifold. Prior to installation, balance the valves on the manifold. Refer to the Radiant Floor Heating Installation Handbook for valve balancing. The face plate on the MVA features instructions for alignment. When installing, turn brass nut until pointer is centered over dot.

Note: Mount MVAs in a vertical or horizontal position, but do not mount them upside down.

Voltage

24VAC

Current Draw (24 volts)

0.29A/6.96VA

Operating Range


24V +/- 10% VAC

Maximum Close Off Pressure

17 psi/39.2 feet of head

Maximum Number of MVAs

6 MVAs-50VA transformer 9 MVAs-75VA transformer 12 MVAs-100VA transformer (computed with a 10% line loss)



Uponor, Inc. 5925 148th Street West Apple Valley, MN 55124

Tel: (800) 321-4739 Fax: (952) 891-1409

Web: www.uponor-usa.com E-mail: learnmore@uponor-usa.com

Uponor Ltd.

655 Park Street Regina, SK S4N 5N1 Tel: (888) 994-7726 Fax: (800) 638-9517

Web: www.uponor.ca E-mail: info@uponor.ca

