

Basic end caps

Submittal information

Date submitted:

Project Information	
Job name :	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative :	Approved by :

Technical Data

Material Brass
End type 1 ISO 228-G 1-1/4"

Temp./pressure ratings 73°F (23°C) at 160 psi (11 bar)

180°F (82°C) at 100 psi (6.9 bar) 200°F (93°C) at 80 psi (5.5 bar)

Product information and application use

The Basic End Cap terminates the end of the TruFLOW™ Jr. modular manifolds. Includes required gaskets and O-rings.

The Brass Manifold Loop End Cap closes off unused QS20 loop connections.



Part name	Part no.	A [inch]	B [inch]	C [inch]	E [inch]	Weight per UOM [lbs/UOM]
Basic End Cap, R32	A2080032	2.13	-	2.13	0.625	0.25
Basic End Cap Gasket, spare part, R32	A2400032	1.58	1.58	0.125	0.125	0.01
TruFLOW Manifold Basic End Cap	A2611250	1.496	1.496	0.768	1.024	-

Installation Related applications

The Basic End Cap threads onto one end of a brass manifold. A gasket aids the seal. Do not overtighten. The Brass Manifold Loop End Cap threads onto a brass manifold outlet. A gasket aids the seal. Do not over-tighten. For more information, refer to the Uponor Radiant Installation Handbook. Available accessories: Basic End Cap Gasket, spare part (A2400032); Loop End Gasket, spare part (A2400020)

Radiant Heating and Cooling Systems

Codes	Standards	Listings
-	ASTM F877	

Trademark Information	Contact information		
	Uponor Inc.	Uponor Ltd.	
	5925 148th Street West	6510 Kennedy Road	
ProPEX® is a registered trademark of Uponor Inc. ProPEX™ is a trademark of Uponor Ltd.	Apple Valley, MN 55124	Mississauga, ON L5T 2X4	
	T 800.321.4739	T 888.594.7726	
	F 952.891.2008	F 800.636.9517	