

Elbows - 1/4 Bend

A.Y. McDonald Service Fittings are made in the United States of America and are manufactured to meet or exceed the AWWA C800 (latest revision) standard. Our service fittings are rated to withstand the same pressures as the tubing they are designed to fit. They are designed and tested for cold potable water only. EPDM rubber gaskets are used in our compression fittings.



74761

		74761		74761-22		74761-22-33		74761-22-44		74761-22-55		74761G	
Size	Nut	Nut	Flare x Flare	-22 CTS Compression x -22 CTS Compression	-22 CTS Compression x -33 PEP Compression	-22 CTS Compression x -44 PVC Compression	-22 CTS Compression x -44 PVC Compression	-22 CTS Compression x -55 IP Compression	-22 CTS Compression x -55 IP Compression	G CTS Compression x G CTS Compression			
3/4"	3/4"	3/4"	●		●		●		●		●		
3/4" x 1"	3/4"	1"			●						●		
1"	1"	1"	●		●						●		
1 1/4"	1 1/4"	1 1/4"			●						●		
1 1/2"	1 1/2"	1 1/2"	●		●						●		
2"	2"	2"	●		●						●		

		74761G-3G		74761Q		74761Q-3Q		74761T		74761T-33	
Size	Nut	Nut	G CTS Compression x -3G PEP Compression	Q CTS Compression x Q CTS Compression	Q CTS Compression x -Q CTS Compression	Q CTS Compression x -3Q PEP Compression	T CTS Compression x T Compression	T CTS Compression x -33 PEP Compression			
3/4"	3/4"	3/4"	●		●		●		●		●
3/4" x 1"	3/4"	1"			●				●		●
1"	1"	1"			●				●		●
1 1/4"	1 1/4"	1 1/4"			●				●		●
1 1/2"	1 1/2"	1 1/2"			●				●		●
2"	2"	2"			●				●		

		74761T-44		74761T-55		74761-33		74761-3G		74761-3Q	
Size	Nut	Nut	T CTS Compression x -44 PVC Compression	T CTS Compression x -55 IP Compression	-33 PEP Compression x -33 PEP Compression	-33 PEP Compression x -33 PEP Compression	-3G PEP Compression x -3G PEP Compression	-3G PEP Compression x -3G PEP Compression	-3Q PEP Compression x -3Q PEP Compression		
3/4"	3/4"	3/4"	●		●		●		●		●
1"	1"	1"			●		●		●		●
1 1/2"	1 1/2"	1 1/2"			●		●		●		●
2"	2"	2"			●		●		●		

		74761-44		74761-44-55		74761-55	
Size	Nut	Nut	-44 PVC Compression x -44 PVC Compression	-44 PVC Compression x -55 IP Compression	-55 IP Compression x -55 IP Compression		
3/4"	3/4"	3/4"	●		●		●
1"	1"	1"	●		●		●
1 1/4"	1 1/4"	1 1/4"	●				
1 1/2"	1 1/2"	1 1/2"	●		●		
2"	2"	2"	●				

Elbows - 1/8 Bend

		74747		74747-22		74747G		74747Q		74747T	
Size	Nut	FNPT	Flare x FNPT	-22 CTS Compression x FNPT	G CTS Compression x FNPT	Q CTS Compression x FNPT	T CTS Compression x FNPT				
3/4"	3/4"	3/4"	●		●		●				
3/4" x 1"	3/4"	1"	●		●		●				
1"	1"	1"	●		●		●				
1" x 1 1/4"	1"	1 1/4"	●								

OPTIONS

- For Handyloc - Replace "Q" or "-3Q" with "H" or "-3H" in 3/4" & 1" only.
- For C903 tube - Replace "Q" with "K". On "Q" Series options only 3/4" x 1" only.
- For valve or fitting less flare nut add "L" to end of model number.
- CTS Anode (QA) & Flare Anode (A) - Replace "Q" with QA or add "A" to flare.
- Insert stiffeners are required on all flexible plastic connections. See page 23.
- See page 15 for Flare conversion adapters.