

Sloan® Manual Specialty Flushometer

SLOAN 995-0.125-RB

Product description

0.125 gpf, Rough Brass Finish, Fixture Connection Rear Spud, Single Flush, 2”-10.75” L Dimension, Sloan® Concealed Manual Specialty Urinal Hydraulic Flushometer.

Compliances & Certifications

(ADA Compliant, BAA Compliant, BREEAM Water Credit, cUPC Certified, Green Globes Water, IAPMO, LEED Water, Satisfies LEED Credits, EPA WaterSense Listed)

Code 3785511

Finish

Rough Brass (RB)

Downloads

- Royal_Regal Series 900 Hydraulic Installation Instructions.pdf
- Control Stop Repair and Maintenance Guide.pdf
- Flush Connections Flanges Repair and Maintenance Guide.pdf
- Additional Downloads

Videos

- Sloan – Company Overview

Details

- Flush Volume: 0.125 gpf (0.5 lpf)
- Finish: Rough Brass (RB)
- Valve: Diaphragm
- Valve Body Material: Semi-red Brass
- Fixture Type: Urinal
- Fixture Connection: Rear Spud
- Rough-in Dimension: 13.5” (343mm)
- Spud Coupling: 0.75” (19mm)
- Supply Pipe: 0.75” (19mm)
- L Dimension: 2”-10.75” (51-273mm)

Features

- High chloramine resistant PERMEX®synthetic rubber diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

Recommended specifications

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

Valve Operating Pressure (Flowing)

15-80 psi (103 - 552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

Warranty

View Warranty Information

Notes

All information contained within this document subject to change without notice.

Looking for other variations of the SLOAN 995 product? View the general spec sheet with all options.

Find a compatible urinal for this flushometer.
Find a compatible water closet for this flushometer.

WaterSense compliant when used with a 0.125 gpf (0.5 lpf) WaterSense fixture.


"L" DIM.
2 3/4" (70 mm)
+ WALL THICKNESS
(121 mm)
4 3/4"
3/4" I.P.S
SUPPLY
(DN 20 mm)
PUSH
BUTTON
(TYPE & LOCATION
OPTIONAL)
CENTERLINE
OF FIXTURE
13 1/2"
(343 mm)
1" (25 mm)
OPENING
IN WALL
CENTERLINE
OF WASTE
FIN.
WALL
FIN.
FLOOR