

# ADS POLYFLEX WATER SERVICE LINE (CTS)

## SDR 9 (250 PSI) PE4710 (BLUE)

| SIZE        | PRODUCT CODE | COIL LENGTH   | MAX. ALLOWABLE PRESSURE AT 73° F |
|-------------|--------------|---------------|----------------------------------|
| ¾" (19 mm)  | X4-75250100  | 100' (30 m)   | 250 psi (1724 kPa)               |
| ¾" (19 mm)  | X4-75250300  | 300' (90 m)   | 250 psi (1724 kPa)               |
| ¾" (19 mm)  | X4-752501000 | 1000' (300 m) | 250 psi (1724 kPa)               |
| 1" (25 mm)  | X4-1250100   | 100' (30 m)   | 250 psi (1724 kPa)               |
| 1" (25 mm)  | X4-1250300   | 300' (90 m)   | 250 psi (1724 kPa)               |
| 1" (25 mm)  | X4-1250500   | 500' (150 m)  | 250 psi (1724 kPa)               |
| 1" (25 mm)  | X4-12501000  | 1000' (300 m) | 250 psi (1724 kPa)               |
| 1¼" (32 mm) | X4-125250100 | 100' (30 m)   | 250 psi (1724 kPa)               |
| 1¼" (32 mm) | X4-125250300 | 300' (90 m)   | 250 psi (1724 kPa)               |
| 1¼" (32 mm) | X4-125250500 | 500' (150 m)  | 250 psi (1724 kPa)               |
| 1½" (38 mm) | X4-150250100 | 100' (30 m)   | 250 psi (1724 kPa)               |
| 1½" (38 mm) | X4-150250500 | 500' (150 m)  | 250 psi (1724 kPa)               |
| 2" (50 mm)  | X4-2250100   | 100' (30 m)   | 250 psi (1724 kPa)               |
| 2" (50 mm)  | X4-2250300   | 300' (90 m)   | 250 psi (1724 kPa)               |
| 2" (50 mm)  | X4-2250500   | 500' (150 m)  | 250 psi (1724 kPa)               |



## SDR 9 (250 PSI) PE4710 (BLACK)

| SIZE        | PRODUCT CODE  | COIL LENGTH   | MAX. ALLOWABLE PRESSURE AT 73° F |
|-------------|---------------|---------------|----------------------------------|
| ¾" (19 mm)  | X4-75250100B  | 100' (30 m)   | 250 psi (1724 kPa)               |
| ¾" (19 mm)  | X4-75250300B  | 300' (90 m)   | 250 psi (1724 kPa)               |
| ¾" (19 mm)  | X4-75250500B  | 500' (150 m)  | 250 psi (1724 kPa)               |
| ¾" (19 mm)  | X4-752501000B | 1000' (300 m) | 250 psi (1724 kPa)               |
| 1" (25 mm)  | X4-1250100B   | 100' (30 m)   | 250 psi (1724 kPa)               |
| 1" (25 mm)  | X4-1250300B   | 300' (90 m)   | 250 psi (1724 kPa)               |
| 1" (25 mm)  | X4-1250500B   | 500' (150 m)  | 250 psi (1724 kPa)               |
| 1" (25 mm)  | X4-12501000B  | 1000' (300 m) | 250 psi (1724 kPa)               |
| 1¼" (32 mm) | X4-125250100B | 100' (30 m)   | 250 psi (1724 kPa)               |
| 1¼" (32 mm) | X4-125250300B | 300' (90 m)   | 250 psi (1724 kPa)               |
| 1¼" (32 mm) | X4-125250500B | 500' (150 m)  | 250 psi (1724 kPa)               |
| 1½" (38 mm) | X4-150250100B | 100' (30 m)   | 250 psi (1724 kPa)               |
| 1½" (38 mm) | X4-150250300B | 300' (90 m)   | 250 psi (1724 kPa)               |
| 1½" (38 mm) | X4-150250500B | 500' (150 m)  | 250 psi (1724 kPa)               |
| 2" (50 mm)  | X4-2250100B   | 100' (30 m)   | 250 psi (1724 kPa)               |
| 2" (50 mm)  | X4-2250300B   | 300' (90 m)   | 250 psi (1724 kPa)               |
| 2" (50 mm)  | X4-2250500B   | 500' (150 m)  | 250 psi (1724 kPa)               |



ADS CTS pipe may be used on residential and commercial water service, well/pump water systems, municipal service lines and farm and ranch water systems.

OTHER COIL LENGTHS AND PRESSURE RATINGS MAY BE AVAILABLE. PLEASE CONTACT YOUR LOCAL ADS REP FOR MORE DETAILS.