


SUBMITTAL INFORMATION

Iron Service Saddles - (F202-xxx-TAP-SSB-I style)



F202 DOUBLE STAINLESS STEEL STRAP IRON SERVICE SADDLES



Threads - CC or IP per AWWA C800

Finish: Epoxy Coating

Nylatron Washers (both sides)

Closed Lug

Stainless Steel Straps



Coated Stainless Steel Nuts

Stainless Steel Washers (open lug side)



| NOM. PIPE SIZE | O.D. RANGE | APPROX. WT. LBS. | CATALOG NUMBER | ✓ SUBMITTED ITEM(S) |
|----------------|---------------|------------------|---------------------|---------------------|
| 4" | **4.26 - 4.80 | 5.4 | F202-480-TAP-SSB-I | |
| | *4.74 - 5.26 | 5.4 | F202-526-TAP-SSB-I | |
| 6" | 5.94 - 6.69 | 6.5 | F202-669-TAP-SSB-I | |
| | 6.63 - 6.90 | 6.5 | F202-690-TAP-SSB-I | |
| | 6.84 - 7.60 | 6.8 | F202-760-TAP-SSB-I | |
| 8" | 7.93 - 8.71 | 7.4 | F202-871-TAP-SSB-I | |
| | 8.63 - 9.05 | 7.4 | F202-905-TAP-SSB-I | |
| | 8.99 - 9.79 | 8.2 | F202-979-TAP-SSB-I | |
| 10" | 10.00 - 10.75 | 10.4 | F202-1075-TAP-SSB-I | |
| | 10.75 - 11.10 | 11.5 | F202-1110-TAP-SSB-I | |
| | 11.10 - 12.12 | 11.5 | F202-1212-TAP-SSB-I | |
| 12" | 12.00 - 12.75 | 12.5 | F202-1275-TAP-SSB-I | |
| | 12.75 - 13.20 | 12.5 | F202-1320-TAP-SSB-I | |
| | 13.20 - 14.38 | 12.5 | F202-1438-TAP-SSB-I | |

I = Imported casting

* Saddles for this pipe range are not available with 2" CC (CC7) or 2-1/2" IP (IP8) threads.

** These saddles with 2" CC (CC7) or 2-1/2" IP (IP8) taps only fit 4.80" O.D. pipe. Example: F202-480-CC7-SSB-I fits 4.80" pipe O.D. only.

OUTLET TAP CODE

| CC (AWWA) THREAD | | |
|------------------|-------------|---------------------|
| THREAD | CODE NUMBER | ✓ SUBMITTED ITEM(S) |
| 3/4" CC | CC3 | |
| 1" CC | CC4 | |
| 1-1/4" CC | Δ CC5 | |
| 1-1/2" CC | CC6 | |
| 2" CC | CC7 | |
| IP THREAD | | |
| THREAD | CODE NUMBER | ✓ SUBMITTED ITEM(S) |
| 3/4" IP | IP3 | |
| 1" IP | IP4 | |
| 1-1/4" IP | Δ IP5 | |
| 1-1/2" IP | IP6 | |
| 2" IP | IP7 | |
| 2-1/2" IP | IP8 | |

Δ Contact factory for availability

FEATURES

- Body made of high strength ductile iron per ASTM A536
- Straps are 5/8" stainless steel per ASTM A493, Grade 305 (UNS 530500)
Each strap has a 5/8" flat bearing surface
- Gasket is EPDM rubber, ASTM D2000
- Finish on saddle body is fusion-bonded epoxy coating
- UL Classified to ANSI/NSF Standard 61

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

12/19/17

Submitted By: