AMERICAN Amarillo Fast-Grip Gaskets

It's More Than Just A Color – It's Confidence





AMERICAN Amarillo Fast-Grip gaskets are the latest innovation in an already proven, field-adaptable method of restraining 4" – 30" ductile iron pipe. AMERICAN has been in the business of bright ideas for over 110 years. The bright yellow Amarillo Fast-Grip gasket is just the latest example of a water works innovation that benefits our customers and the public. Designed to the same specifications as the previous generation of Fast-Grips, the Amarillo model gives you added confidence that you've selected the proper gasket for the Fastite bell, that the gasket seated properly during installation and that it's an AMERICAN product – made in America, The Right Way.

EOE/Minority/Female/Veteran/Disability



A M E R I C A N - U S A . C O M 1 - 8 0 0 - 4 4 2 - 2 3 4 7

SPIRALWELD PIPE



A Specification for **Amarillo Fast-Grip Gaskets** On Ductile Iron Pipe

Four-inch through 30-inch restrained joints shall be AMERICAN Amarillo Fast-Grip gasket and joint restraining system.

Pressure ratings shall be 350 psi for 4-inch through 18-inch; 250 psi for 20inch through 24-inch; and 150 psi for 30-inch, but in no case shall the joint be considered rated at a higher pressure than the pipe of which it is a part.

Joint deflection shall be 5 degrees for 4-inch through 12-inch; 4 degrees for 14-inch; 3 degrees for 16-inch through 24-inch; and 2.5 degrees for 30-inch.

Gaskets shall meet applicable requirements of AWWA/ANSI C111/A21.11, shall be styrene butadiene rubber (SBR), and shall be ANSI/NSF Standard 61 certified for contact with potable water.

Gaskets shall be yellow in color, and the yellow color shall be consistent throughout the entire cross section of the gasket. The yellow color shall not be attained by surface coating; it shall be inherent within the rubber.

Restraining gaskets shall be manufactured in the United States.



