

# NEW 2014 FPPI PRODUCTS



## TrimFit® Butterfly Valve (BFGCI)



TrimFit® Model BFGCI (Grooved Butterfly Valve, Cast Iron) are designed to be installed in any orientation and monitored to signal if the valve is opened or closed. TrimFit® Model BFGCI is UL/ULC listed and FM approved for use in a fire sprinkler system.

### Threaded

| Part No.  | Description                  | Box Qty. |
|-----------|------------------------------|----------|
| 06-558-00 | Butterfly Valve 2½ UL/ULC/FM | 1        |
| 06-560-00 | Butterfly Valve 3" UL/ULC/FM | 1        |
| 06-562-00 | Butterfly Valve 4" UL/ULC/FM | 1        |
| 06-564-00 | Butterfly Valve 6" UL/ULC/FM | 1        |
| 06-566-00 | Butterfly Valve 8" UL/ULC/FM | 1        |



AUTO SPKR



STANDPIPE

## Double Clapper Siamese FDC



The Double Clapper Siamese, Straight Pattern Fire Department Connection and the Double Clapper Siamese – 90° pattern are Underwriters' Laboratories listed and Factory Mutual Approved. Manufactured from solid brass\* components to increase service life. The double clapper design features 2 brass clappers and brass seats within a cast brass\* body. The 2½" swivels are pin lug design for ease of use and compatibility with local fire service districts. Swivel gaskets are included. Breakable caps or plugs should be installed to protect swivels and prevent debris from being accidentally introduced into the water way. AVAILABLE IN ROUGH BRASS AND CHROME.

### Threaded

| Part No.  | Description                    | Box Qty. |
|-----------|--------------------------------|----------|
| 09-120-00 | 90° DBL Clapper Siamese RB NST | 1        |
| 09-120-01 | 90° DBL Clapper Siamese PC NST | 1        |
| 09-121-00 | STR DBL Clapper Siamese RB NST | 1        |
| 09-121-01 | STR DBL Clapper Siamese PC NST | 1        |