













K	SMITH JAY R. SMITH MFG. CO.® DIVISION OF SMITH INDUSTRIES, INC. POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com MEMBER OF:				LOCATION 																																																														
	FLOOR OR SHOWER DRAINS WITH ADJUSTABLE STRAINER HEADS																																																																		
	FUNCTION: General service floor drain for use in showers, toilets, kitchens, and other finished areas where foot traffic is expected. The round top strainer head is used for all types of poured finished floors. The square top is particularly adaptable to floors that are finished in material of square or straight line pattern. Reversible flashing collar permits adjustment to meet finished floor level.																																																																		
	A (Pipe Size) = 02(50), 03(80) or 04(100)																																																																		
CAULK OUTLET Fig. 2010C (A) ROUND TOP Fig. 2010C (B) SQUARE TOP THREADED OUTLET Fig. 2015T (A) ROUND TOP Fig. 2015T (B) SQUARE TOP																																																																			
<table border="1" style="width:100%; border-collapse: collapse; font-size: 0.8em;"> <tr> <th rowspan="2">Strainer Size</th> <th colspan="2">*Collar In High Position X</th> <th colspan="2">*Collar In Low Position XX</th> <th colspan="2">Free Area SQ IN (SQ CM)</th> </tr> <tr> <th>MIN</th> <th>MAX</th> <th>MIN</th> <th>MAX</th> <th>ROUND</th> <th>SQUARE</th> </tr> <tr> <td>B DIA or SQ</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>05 (125)</td> <td>1 1/4 (32)</td> <td>2 1/4 (57)</td> <td>3/4 (19)</td> <td>1 5/8 (41)</td> <td>7 (45)</td> <td>6.5 (42)</td> </tr> <tr> <td>06 (150)</td> <td>1 1/4 (32)</td> <td>2 1/4 (57)</td> <td>3/4 (19)</td> <td>1 5/8 (41)</td> <td>9 (58)</td> <td>12.5 (81)</td> </tr> <tr> <td>07 (180)</td> <td>1 1/4 (32)</td> <td>2 1/4 (57)</td> <td>7/8 (22)</td> <td>1 7/8 (48)</td> <td>14 (90)</td> <td>11 (71)</td> </tr> <tr> <td>08 (205)</td> <td>1 1/2 (38)</td> <td>2 1/2 (64)</td> <td>1 (25)</td> <td>1 7/8 (48)</td> <td>17 (110)</td> <td>14 (90)</td> </tr> <tr> <td>•09 (230)</td> <td>1 1/2 (38)</td> <td>2 3/8 (60)</td> <td>1 (25)</td> <td>1 7/8 (48)</td> <td>18 (116)</td> <td>16 (103)</td> </tr> <tr> <td>•10 (255)</td> <td>1 1/2 (38)</td> <td>2 3/8 (60)</td> <td>1 (25)</td> <td>1 7/8 (48)</td> <td>23 (148)</td> <td>16 (103)</td> </tr> </table>						Strainer Size	*Collar In High Position X		*Collar In Low Position XX		Free Area SQ IN (SQ CM)		MIN	MAX	MIN	MAX	ROUND	SQUARE	B DIA or SQ							05 (125)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	7 (45)	6.5 (42)	06 (150)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	9 (58)	12.5 (81)	07 (180)	1 1/4 (32)	2 1/4 (57)	7/8 (22)	1 7/8 (48)	14 (90)	11 (71)	08 (205)	1 1/2 (38)	2 1/2 (64)	1 (25)	1 7/8 (48)	17 (110)	14 (90)	•09 (230)	1 1/2 (38)	2 3/8 (60)	1 (25)	1 7/8 (48)	18 (116)	16 (103)	•10 (255)	1 1/2 (38)	2 3/8 (60)	1 (25)	1 7/8 (48)	23 (148)	16 (103)
Strainer Size	*Collar In High Position X		*Collar In Low Position XX		Free Area SQ IN (SQ CM)																																																														
	MIN	MAX	MIN	MAX	ROUND	SQUARE																																																													
B DIA or SQ																																																																			
05 (125)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	7 (45)	6.5 (42)																																																													
06 (150)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	9 (58)	12.5 (81)																																																													
07 (180)	1 1/4 (32)	2 1/4 (57)	7/8 (22)	1 7/8 (48)	14 (90)	11 (71)																																																													
08 (205)	1 1/2 (38)	2 1/2 (64)	1 (25)	1 7/8 (48)	17 (110)	14 (90)																																																													
•09 (230)	1 1/2 (38)	2 3/8 (60)	1 (25)	1 7/8 (48)	18 (116)	16 (103)																																																													
•10 (255)	1 1/2 (38)	2 3/8 (60)	1 (25)	1 7/8 (48)	23 (148)	16 (103)																																																													
<table border="1" style="width:100%; border-collapse: collapse; font-size: 0.8em;"> <tr> <th>A SIZE</th> <th>B</th> <th>D</th> <th>E</th> <th>F</th> <th>G</th> <th>MIN-X-MAX</th> <th>MIN-XX-MA</th> </tr> <tr> <td>02 (50)</td> <td>05 (125)</td> <td>2 3/4 (70)</td> <td>1 1/4 (32)</td> <td>4 3/4 (120)</td> <td>5 (125)</td> <td>1 1/4 (32) 2 1/4 (57)</td> <td>3/4 (19) 1 5/8 (41)</td> </tr> <tr> <td>03 (80)</td> <td>06 (150)</td> <td>2 3/4 (70)</td> <td>2 1/4 (57)</td> <td>4 3/4 (120)</td> <td>5 (125)</td> <td>1 1/4 (32) 2 1/4 (57)</td> <td>3/4 (19) 1 5/8 (41)</td> </tr> <tr> <td>04 (100)</td> <td>08 (200)</td> <td>3 1/4 (83)</td> <td>3 1/4 (83)</td> <td>6 (150)</td> <td>4 (100)</td> <td>1 1/2 (38) 2 1/2 (64)</td> <td>- -</td> </tr> </table>						A SIZE	B	D	E	F	G	MIN-X-MAX	MIN-XX-MA	02 (50)	05 (125)	2 3/4 (70)	1 1/4 (32)	4 3/4 (120)	5 (125)	1 1/4 (32) 2 1/4 (57)	3/4 (19) 1 5/8 (41)	03 (80)	06 (150)	2 3/4 (70)	2 1/4 (57)	4 3/4 (120)	5 (125)	1 1/4 (32) 2 1/4 (57)	3/4 (19) 1 5/8 (41)	04 (100)	08 (200)	3 1/4 (83)	3 1/4 (83)	6 (150)	4 (100)	1 1/2 (38) 2 1/2 (64)	- -																														
A SIZE	B	D	E	F	G	MIN-X-MAX	MIN-XX-MA																																																												
02 (50)	05 (125)	2 3/4 (70)	1 1/4 (32)	4 3/4 (120)	5 (125)	1 1/4 (32) 2 1/4 (57)	3/4 (19) 1 5/8 (41)																																																												
03 (80)	06 (150)	2 3/4 (70)	2 1/4 (57)	4 3/4 (120)	5 (125)	1 1/4 (32) 2 1/4 (57)	3/4 (19) 1 5/8 (41)																																																												
04 (100)	08 (200)	3 1/4 (83)	3 1/4 (83)	6 (150)	4 (100)	1 1/2 (38) 2 1/2 (64)	- -																																																												
•Add 3/8" (10) to all min./max. dimensions for round strainer. •Not available for 05" (125) size strainer. *Collar is reversible to obtain extreme high and low strainer positions. NOTE: Dimensions shown in parentheses are in millimeters.																																																																			
REGULARLY FURNISHED: Duco Cast Iron Body with Flashing Collar and Adjustable Strainer Head as Indicated by Suffix Letter Selected. Meets ASME Standard A112.6.3-2001 02(50), 03(75) or 04"(100) sizes only. SEE PM0457 FOR OPTIONAL STRAINER HEADS. VARIATIONS: ☐ Ball Float Backwater Valve -BFV (Fig. 2015 only) ☐ Flapper Type Backwater Valve -V ☒ Hinged Grate -H ☐ Sediment Bucket -B ☐ Trap Primer Connection -P050 1/2" (13) & -P075 3/4" (19) ☐ Vandal Proof Screws -U ☐ Wide Flanged Strainer (Specify Fig. DX 2010) ☐ T Threaded Outlet ☐ Bronze Body -BB (Fig. 2010 only) ☐ Chrome Plated Strainer -CP ☐ Galvanized Cast Iron Body -G ☐ Nickel Bronze Strainer -NB ☐ Polished Bronze Strainer -PB ☐ Stainless Steel (Specify Fig. 9700-A) (Fig. 2010 only)																																																																			
<table border="1" style="width:100%; border-collapse: collapse; font-size: 0.8em;"> <tr> <td style="width:10%;">K</td> <td style="width:10%;">9-22-06</td> <td style="width:30%;">Revised ANSI note</td> <td style="width:10%;">RN</td> <td style="width:10%;">CL</td> <td style="width:10%;">WEIGHT POUNDS</td> <td style="width:10%;">VOLUME CUBIC FEET</td> <td style="width:20%;">FIGURE NUMBER</td> </tr> <tr> <td>J</td> <td>5-11-05</td> <td>Revised ANSI note</td> <td>JJ</td> <td>AM</td> <td></td> <td></td> <td rowspan="3" style="text-align: center; font-size: 2em; vertical-align: middle;">2010,2015</td> </tr> <tr> <td>H</td> <td>6-15-95</td> <td>Added Millimeters</td> <td>EMB</td> <td>BS</td> <td></td> <td></td> </tr> <tr> <td>G</td> <td>7-1-94</td> <td>Revised</td> <td>CMB</td> <td>BS</td> <td></td> <td></td> </tr> <tr> <td>REV.</td> <td>DATE</td> <td>DESCRIPTION</td> <td>BY</td> <td>CKD. BY</td> <td></td> <td></td> <td></td> </tr> </table>						K	9-22-06	Revised ANSI note	RN	CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER	J	5-11-05	Revised ANSI note	JJ	AM			2010,2015	H	6-15-95	Added Millimeters	EMB	BS			G	7-1-94	Revised	CMB	BS			REV.	DATE	DESCRIPTION	BY	CKD. BY																											
K	9-22-06	Revised ANSI note	RN	CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER																																																												
J	5-11-05	Revised ANSI note	JJ	AM			2010,2015																																																												
H	6-15-95	Added Millimeters	EMB	BS																																																															
G	7-1-94	Revised	CMB	BS																																																															
REV.	DATE	DESCRIPTION	BY	CKD. BY																																																															

G	SMITH JAY R. SMITH MFG. CO. DIVISION OF SMITH INDUSTRIES, INC. POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com MEMBER OF:					LOCATION				
	OPTIONAL STRAINER HEADS									
	DRAWING NUMBER PM0457 SH 1 of 2	SIZE A	ASSUME NO RESPONSIBILITY OR USE OF SUPERSEDED OR VOID DATA							
	SCALE NONE	DATE: 5-17-85								
APPROVED BY: TD	CHECKED BY: TD	DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE								
DRAWN BY: PJ	FIGURE NUMBER									
2010 SERIES OPTIONAL STRAINER HEADS										
NOTE: Dimensions shown in parenthesis are in millimeters.										

ROUND STRAINER MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: *Hinged Grate (Specify Suffix -AH) Sediment Bucket -B Vandal Proof Screws -U <table border="1" style="width: 100%; font-size: 0.8em; margin-top: 10px;"> <tr> <th>B DIA</th> <th>05 (125)</th> <th>06 (150)</th> <th>07 (180)</th> <th>08 (205)</th> <th>09 (230)</th> <th>10 (255)</th> </tr> <tr> <td>H</td> <td>2 (51)</td> <td>2 (51)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> <td>2 1/2 (64)</td> <td>2 3/4 (70)</td> </tr> <tr> <td>X MIN</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/2 (38)</td> <td>1 1/2 (38)</td> <td>1 1/2 (38)</td> </tr> <tr> <td>X MAX</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> <td>2 1/2 (64)</td> <td>2 3/4 (70)</td> </tr> </table> Specify Type, Size & Finish eg: A05NB *Not available for 05" (125) size SUFFIX -A	B DIA	05 (125)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)	X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)	X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)	FLAPPER TYPE BACKWATER VALVE MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: *Hinged Grate (Specify Suffix -AH) Sediment Bucket -B Vandal Proof Screws -U <table border="1" style="width: 100%; font-size: 0.8em; margin-top: 10px;"> <tr> <th>B DIA</th> <th>05 (125)</th> <th>06 (150)</th> <th>07 (180)</th> <th>08 (205)</th> </tr> <tr> <td>H</td> <td>2 (51)</td> <td>2 (51)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> </tr> <tr> <td>X MIN</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/2 (38)</td> </tr> <tr> <td>X MAX</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> </tr> </table> Specify Type, Size & Finish eg: AV05NB *Not available for 05" (125) size SUFFIX -AV	B DIA	05 (125)	06 (150)	07 (180)	08 (205)	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)
B DIA	05 (125)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)																																											
H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)																																											
X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)																																											
X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)																																											
B DIA	05 (125)	06 (150)	07 (180)	08 (205)																																													
H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)																																													
X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)																																													
X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)																																													
SQUARE STRAINER MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -BV) 05 (125), 06 (150), 07 (180) or 08" (205) sizes only *Hinged Grate (Specify Suffix -BH) Sediment Bucket -B Vandal Proof Screws -U <table border="1" style="width: 100%; font-size: 0.8em; margin-top: 10px;"> <tr> <th>B DIA</th> <th>05 (125)</th> <th>06 (150)</th> <th>07 (180)</th> <th>08 (205)</th> <th>09 (230)</th> <th>10 (255)</th> </tr> <tr> <td>H</td> <td>2 (51)</td> <td>2 (51)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> </tr> <tr> <td>X MIN</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/2 (38)</td> <td>1 1/2 (38)</td> <td>1 1/2 (38)</td> </tr> <tr> <td>X MAX</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> <td>2 1/4 (57)</td> <td>2 3/8 (60)</td> </tr> </table> Specify Type, Size & Finish eg: B05NB *Not available for 05" (125) size SUFFIX -B	B DIA	05 (125)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	2 1/4 (57)	X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)	X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	2 3/8 (60)	STRAINER HEAD w/SQUARE HINGED COVER MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Gasketed Water Tight Cover -GC Secured Cover -SC Secondary Strainer Grate-SG Specify Type, Size & Finish eg: BSNB SUFFIX -BS																				
B DIA	05 (125)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)																																											
H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	2 1/4 (57)																																											
X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)																																											
X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	2 3/8 (60)																																											
REINFORCED ROUND STRAINER FUNCTION: Used in finished floors where light wheeled loads are anticipated. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -CV) Sediment Bucket -B Vandal Proof Screws -U <table border="1" style="width: 100%; font-size: 0.8em; margin-top: 10px;"> <tr> <th>B DIA</th> <th>05 (125)</th> <th>06 (150)</th> <th>08 (205)</th> <th>10 (255)</th> </tr> <tr> <td>H</td> <td>2 (51)</td> <td>2 (51)</td> <td>2 1/2 (64)</td> <td>2 3/4 (70)</td> </tr> <tr> <td>MIN</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/2 (38)</td> <td>1 7/8 (48)</td> </tr> <tr> <td>MAX</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> <td>2 3/4 (70)</td> </tr> </table> Specify Type, Size & Finish eg: C06NB SUFFIX -C	B DIA	05 (125)	06 (150)	08 (205)	10 (255)	H	2 (51)	2 (51)	2 1/2 (64)	2 3/4 (70)	MIN	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 7/8 (48)	MAX	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 3/4 (70)	REINFORCED TRACTOR STRAINER FUNCTION: Used in finished floors where medium weight wheeled loads are anticipated and loose set non-tilt tractor grate is desired. MATERIALS: Cast Iron -CI Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -DV or -EV) Sediment Bucket -B Vandal Proof Screws -U <table border="1" style="width: 100%; font-size: 0.8em; margin-top: 10px;"> <tr> <th>SUFFIX</th> <th>B DIA</th> <th>H</th> <th colspan="2">X</th> </tr> <tr> <td></td> <td></td> <td></td> <td>MIN</td> <td>MAX</td> </tr> <tr> <td>-D</td> <td>07 (180)</td> <td>3 1/4 (83)</td> <td>2 5/8 (67)</td> <td>3 1/2 (89)</td> </tr> <tr> <td>-E</td> <td>09 (230)</td> <td>3 1/2 (89)</td> <td>2 3/4 (70)</td> <td>3 1/2 (89)</td> </tr> </table> Specify Type, Size & Finish eg: D09PB E09PB SUFFIX -D-E	SUFFIX	B DIA	H	X					MIN	MAX	-D	07 (180)	3 1/4 (83)	2 5/8 (67)	3 1/2 (89)	-E	09 (230)	3 1/2 (89)	2 3/4 (70)	3 1/2 (89)								
B DIA	05 (125)	06 (150)	08 (205)	10 (255)																																													
H	2 (51)	2 (51)	2 1/2 (64)	2 3/4 (70)																																													
MIN	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 7/8 (48)																																													
MAX	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 3/4 (70)																																													
SUFFIX	B DIA	H	X																																														
			MIN	MAX																																													
-D	07 (180)	3 1/4 (83)	2 5/8 (67)	3 1/2 (89)																																													
-E	09 (230)	3 1/2 (89)	2 3/4 (70)	3 1/2 (89)																																													
TILE FLANGE FUNCTION: Provides integral flange set 5/32" (4) below rim to receive floor covering. Flange may have option of tapped holes for securing pan and gasket. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -FV) Holes in Flange -SH Sediment Bucket -B Vandal Proof Screws -U <table border="1" style="width: 100%; font-size: 0.8em; margin-top: 10px;"> <tr> <th colspan="2">X</th> </tr> <tr> <th>MIN</th> <th>MAX</th> </tr> <tr> <td>1 1/4 (32)</td> <td>2 1/8 (54)</td> </tr> </table> Specify Type, Size & Finish eg: F06NB SUFFIX -F	X		MIN	MAX	1 1/4 (32)	2 1/8 (54)	ADJUSTABLE STRAINER HEAD FUNCTION: Used in a non-traffic area when a funnel type strainer head is required and space does not allow use of the 3500 series funnel. The extended rim allows use as an anti-flood and anti-splash drip pan. VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -F37V or F38V) MATERIALS: Cast Iron -CI Chrome Plated -CP Galvanized Cast Iron -G Polished Bronze -PB Nickel Bronze -NB <table border="1" style="width: 100%; font-size: 0.8em; margin-top: 10px;"> <tr> <th>SUFFIX</th> <th>-F37</th> <th>-F38</th> </tr> <tr> <td>B DIA</td> <td>07 (180)</td> <td>09 (230)</td> </tr> <tr> <td>H</td> <td>3 1/4 (83)</td> <td>3 1/2 (89)</td> </tr> <tr> <td>X MIN</td> <td>2 5/8 (67)</td> <td>2 3/4 (70)</td> </tr> <tr> <td>X MAX</td> <td>3 1/2 (89)</td> <td>3 1/2 (89)</td> </tr> </table> Specify Type, Size & Finish eg: F37NB F38CP SUFFIX -F37-F38	SUFFIX	-F37	-F38	B DIA	07 (180)	09 (230)	H	3 1/4 (83)	3 1/2 (89)	X MIN	2 5/8 (67)	2 3/4 (70)	X MAX	3 1/2 (89)	3 1/2 (89)																											
X																																																	
MIN	MAX																																																
1 1/4 (32)	2 1/8 (54)																																																
SUFFIX	-F37	-F38																																															
B DIA	07 (180)	09 (230)																																															
H	3 1/4 (83)	3 1/2 (89)																																															
X MIN	2 5/8 (67)	2 3/4 (70)																																															
X MAX	3 1/2 (89)	3 1/2 (89)																																															
<table border="1" style="width: 100%; font-size: 0.8em;"> <tr> <td style="width: 15%;">REV.</td> <td style="width: 15%;">DATE</td> <td style="width: 30%;">DESCRIPTION</td> <td style="width: 10%;">BY</td> <td style="width: 10%;">CKD. BY</td> <td style="width: 20%;"></td> <td style="width: 10%;"></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>										REV.	DATE	DESCRIPTION	BY	CKD. BY																																			
REV.	DATE	DESCRIPTION	BY	CKD. BY																																													
FIGURE NUMBER 2010 SERIES OPTIONAL STRAINER HEADS 1 of 2																																																	

H	 SMITH JAY R. SMITH MFG. CO. DIVISION OF SMITH INDUSTRIES, INC. POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com  MEMBER OF:  MEMBER OF:				LOCATION																																																																												
	OPTIONAL STRAINER HEADS																																																																																
DRAWING NUMBER PM0457 SH 2 of 2 SIZE A SCALE NONE DATE: 5-17-85 APPROVED BY: TD CHECKED BY: TD DRAWN BY: PJ	ASSUME NO RESPONSIBILITY OR USE OF SUPERSEDED OR VOID DATA DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE																																																																																
	LOW DOME STRAINER FUNCTION: Used in gutters and recessed areas where excessive debris build-up is expected. Dome insures drainage even when partly covered. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -GV) Sediment Bucket -B Vandal Proof Screws -U  <table border="1" style="width:100%; font-size: x-small;"> <tr> <th>B DIA</th> <th>05 (125)</th> <th>06 (150)</th> <th>08 (205)</th> </tr> <tr> <td>H</td> <td>2 (51)</td> <td>2 (51)</td> <td>2 1/2 (64)</td> </tr> <tr> <td>MIN</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/2 (38)</td> </tr> <tr> <td>MAX</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> </tr> </table> SUFFIX -G Specify Type, Size & Finish eg: G08PB	B DIA	05 (125)	06 (150)	08 (205)	H	2 (51)	2 (51)	2 1/2 (64)	MIN	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	MAX	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	SOLID HINGED COVER FUNCTION: Used in areas where intermittent drain use is required. Solid cover prevents intrusion of chips, saw-dust, etc., which are swept up before cover is opened for washdown. The secondary strainer prevents debris from entering the waste line. MATERIALS: Cast Iron -CI Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -GV) Vandal Proof Screws -U  <table border="1" style="width:100%; font-size: x-small;"> <tr> <th>B DIA</th> <th>05 (125)</th> <th>06 (150)</th> <th>07 (180)</th> <th>08 (205)</th> </tr> <tr> <td>H</td> <td>2 (51)</td> <td>2 (51)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> </tr> <tr> <td>MIN</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/2 (38)</td> </tr> <tr> <td>MAX</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> </tr> </table> SUFFIX -H Specify Type, Size & Finish eg: H05CP	B DIA	05 (125)	06 (150)	07 (180)	08 (205)	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	SPANNER WRENCH COVER FUNCTION: Solid gas tight, vandal proof, threaded cover for areas where intermittent drain use is required. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -JV) Holes in Flange -SH Sediment Bucket -B Vandal Proof Screws -U  <table border="1" style="width:100%; font-size: x-small;"> <tr> <th colspan="2">X</th> </tr> <tr> <td>MIN</td> <td>MAX</td> </tr> <tr> <td>2 (51)</td> <td>3 (76)</td> </tr> </table> SUFFIX -J Specify Type, Size & Finish eg: J06NB	X		MIN	MAX	2 (51)	3 (76)																																				
	B DIA	05 (125)	06 (150)	08 (205)																																																																													
	H	2 (51)	2 (51)	2 1/2 (64)																																																																													
	MIN	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)																																																																													
	MAX	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)																																																																													
	B DIA	05 (125)	06 (150)	07 (180)	08 (205)																																																																												
	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)																																																																												
	MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)																																																																												
	MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)																																																																												
X																																																																																	
MIN	MAX																																																																																
2 (51)	3 (76)																																																																																
REINFORCED SQUARE STRAINER FUNCTION: Used in finished floors where some light wheeled traffic is anticipated. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -KV) Sediment Bucket -B Vandal Proof Screws -U  <table border="1" style="width:100%; font-size: x-small;"> <tr> <th>B SQ</th> <th>05 (125)</th> <th>06 (150)</th> <th>07 (180)</th> <th>08 (205)</th> </tr> <tr> <td>H</td> <td>2 (51)</td> <td>2 (51)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> </tr> <tr> <td>MIN</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/2 (38)</td> </tr> <tr> <td>MAX</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> </tr> </table> SUFFIX -K Specify Type, Size & Finish eg: K07CP	B SQ	05 (125)	06 (150)	07 (180)	08 (205)	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	RECTANGULAR STRAINER FUNCTION: Used in finished floors where light wheeled loads and or heavy foot traffic are anticipated. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Sediment Bucket -B Vandal Proof Screws -U  <table border="1" style="width:100%; font-size: x-small;"> <tr> <th>SUFFIX</th> <th>L</th> <th>M</th> <th>N</th> <th>P</th> <th>R</th> <th>T</th> </tr> <tr> <td>B x B'</td> <td>1/2(115)x3(205)</td> <td>1/2(100)x12(305)</td> <td>5(125)x9(230)</td> <td>5(125)x13(330)</td> <td>6(150)x10(255)</td> <td>5(125)x17(430)</td> </tr> <tr> <td>H</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> <td>2 1/4 (57)</td> <td>3 (76)</td> <td>2 1/4 (57)</td> <td>3 (76)</td> </tr> <tr> <td>MIN</td> <td>1 3/8 (35)</td> <td>1 7/8 (49)</td> <td>1 3/8 (35)</td> <td>2 1/8 (54)</td> <td>1 3/8 (35)</td> <td>2 1/4 (57)</td> </tr> <tr> <td>MAX</td> <td>2 3/8 (60)</td> <td>2 3/4 (70)</td> <td>2 3/8 (60)</td> <td>3 (76)</td> <td>2 3/8 (60)</td> <td>3 1/8 (79)</td> </tr> </table> SUFFIX -L-M-N-P-R-T Specify Type, Size & Finish eg: LNB	SUFFIX	L	M	N	P	R	T	B x B'	1/2(115)x3(205)	1/2(100)x12(305)	5(125)x9(230)	5(125)x13(330)	6(150)x10(255)	5(125)x17(430)	H	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	3 (76)	2 1/4 (57)	3 (76)	MIN	1 3/8 (35)	1 7/8 (49)	1 3/8 (35)	2 1/8 (54)	1 3/8 (35)	2 1/4 (57)	MAX	2 3/8 (60)	2 3/4 (70)	2 3/8 (60)	3 (76)	2 3/8 (60)	3 1/8 (79)	ANGLE STRAINER FUNCTION: Shower room drain set at wall and floor junction. Vertical grate openings prevent drain stoppage should flat surface become covered. MATERIALS: Cast Iron -CI Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Vandal Proof Screws -U  <table border="1" style="width:100%; font-size: x-small;"> <tr> <th>SUFFIX</th> <th>B</th> <th>C</th> <th>D</th> <th colspan="2">X</th> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>MIN</td> <td>MAX</td> </tr> <tr> <td>-V</td> <td>3 1/2 (89)</td> <td>3 1/2 (89)</td> <td>4 1/2 (115)</td> <td>1 5/8 (41)</td> <td>2 5/8 (67)</td> </tr> <tr> <td>-W</td> <td>6 3/4 (170)</td> <td>6 3/4 (170)</td> <td>6 1/2 (165)</td> <td>1 5/8 (41)</td> <td>2 5/8 (67)</td> </tr> </table> SUFFIX -V-W Specify Type, Size & Finish eg: VPB, WNB	SUFFIX	B	C	D	X						MIN	MAX	-V	3 1/2 (89)	3 1/2 (89)	4 1/2 (115)	1 5/8 (41)	2 5/8 (67)	-W	6 3/4 (170)	6 3/4 (170)	6 1/2 (165)	1 5/8 (41)	2 5/8 (67)
B SQ	05 (125)	06 (150)	07 (180)	08 (205)																																																																													
H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)																																																																													
MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)																																																																													
MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)																																																																													
SUFFIX	L	M	N	P	R	T																																																																											
B x B'	1/2(115)x3(205)	1/2(100)x12(305)	5(125)x9(230)	5(125)x13(330)	6(150)x10(255)	5(125)x17(430)																																																																											
H	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	3 (76)	2 1/4 (57)	3 (76)																																																																											
MIN	1 3/8 (35)	1 7/8 (49)	1 3/8 (35)	2 1/8 (54)	1 3/8 (35)	2 1/4 (57)																																																																											
MAX	2 3/8 (60)	2 3/4 (70)	2 3/8 (60)	3 (76)	2 3/8 (60)	3 1/8 (79)																																																																											
SUFFIX	B	C	D	X																																																																													
				MIN	MAX																																																																												
-V	3 1/2 (89)	3 1/2 (89)	4 1/2 (115)	1 5/8 (41)	2 5/8 (67)																																																																												
-W	6 3/4 (170)	6 3/4 (170)	6 1/2 (165)	1 5/8 (41)	2 5/8 (67)																																																																												
EXTENSION ADAPTOR FUNCTION: Used when a strainer head must be raised to accommodate deeper floor fill. REGULARLY FURNISHED: Ducto Cast Iron -CI MATERIALS: Cast Bronze -CB Galvanized Cast Iron -G  NOTE: Extension can be stacked for increased maximum adjustment. SUFFIX -X	OVERFLOW WITH STANDPIPE FUNCTION: Used as overflow drain in decorative pools, fish ponds or similar areas. Dome prevents floating objects from entering drain line. MATERIALS: Chrome Plated -CP Nickel Bronze -NB Polished Bronze -PB VARIATIONS: Less Dome -LD Standpipe Height other than 6" (150) (Specify Height)  <table border="1" style="width:100%; font-size: x-small;"> <tr> <th>SUFFIX</th> <th>A</th> <th colspan="2">X</th> </tr> <tr> <td></td> <td>SIZE</td> <td>MIN</td> <td>MAX</td> </tr> <tr> <td>-Y</td> <td>2 (51)</td> <td>3/4 (19)</td> <td>2 1/8 (54)</td> </tr> <tr> <td>-Z</td> <td>3 (76)</td> <td>3/4 (19)</td> <td>2 1/8 (54)</td> </tr> </table> SUFFIX -Y-Z Specify Type, Size & Finish eg: YCP, ZCP	SUFFIX	A	X			SIZE	MIN	MAX	-Y	2 (51)	3/4 (19)	2 1/8 (54)	-Z	3 (76)	3/4 (19)	2 1/8 (54)	HEAVY DUTY ADJUSTABLE FUNCTION: Used in finished floors where light wheeled loads and or heavy foot traffic are anticipated. MATERIALS: Polished Bronze -PB Rough Bronze -RB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -69V) Sediment Bucket -B Vandal Proof Screws -U  SUFFIX -69 eg: A06NB-69																																																															
SUFFIX	A	X																																																																															
	SIZE	MIN	MAX																																																																														
-Y	2 (51)	3/4 (19)	2 1/8 (54)																																																																														
-Z	3 (76)	3/4 (19)	2 1/8 (54)																																																																														
 Fig. 3580	 Fig. 3581	 Fig. 3590	 Fig. 3591																																																																														
FIGURE NUMBER	FIGURE NUMBER 2010 SERIES OPTIONAL STRAINER HEADS 2 of 2																																																																																
REV.	DATE	DESCRIPTION	BY	CKD. BY																																																																													
1	8-24-99	Revised	TBW	BS																																																																													
2	6-11-99	Revised Tables	CMD	BS																																																																													
3	1-22-99	T Strainer was S Strainer	TBW	BS																																																																													
4	11-4-97	Added Nickel Bronze	EMB	BS																																																																													
5	10-28-96	Chg'd Func of Suffix -V -W																																																																															

NOTE: Dimensions shown in parenthesis are in millimeters.