

Elkay Lustertone Classic Stainless Steel 22" x 19-1/2" x 5-1/2" Single Bowl Drop-in ADA Sink Model(s) LRAD221955

PRODUCT SPECIFICATIONS

Elkay Lustertone[™] Classic Stainless Steel 22" x 19-1/2" x 5-1/2", Single Bowl Drop-in ADA Sink. Sink is manufactured from 18 gauge 304 Stainless Steel with a Lustrous Satin finish, Rear Center drain placement, and Bottom only pads.

Installation Type:	Drop-in	
Material:	304 Stainless Steel	
Finish:	Lustrous Satin	
Gauge:	18	
Sound Deadening:	Bottom only pads	
Number of Bowls:	1	
Sink Dimensions:	22" x 19-1/2" x 5-1/2"	
Bowl 1 Dimensions:	18" x 14" x 5-3/8"	
Drain Size:	3-1/2" (89mm)	
Drain Location:	Rear Center	
Minimum Cabinet Size:	27"	
Mounting Hardware:	Part # 64090012 included for countertops	
	up to 3/4" (19mm) thick	
Cutout Template #:	1000001255	

Template is available for download at elkay.com. CAD software will be required to open the template.

Cutout Dimensions for Drop-in Installation:

21-3/8" x 18-7/8" (543mm x 479mm) with 1-1/2" (38mm) corner radius

Custom Options	
Type 316 Stainless Steel	
Drain Location	
Right Rear	Left Rear
Center	Center Rear
Overflow Location	
Front	Rear
Alternate Punching	
Faucet Model:	Punch Required:
Sink Size	
Bowl Depth:	Drainboard Width:

PART:	_QTY:
PROJECT:	
CONTACT:	
DATE:	
NOTES:	
APPROVAL:	



AMERICAN PRIDE. A LIFETIME TRADITION. Like your family, the Elkay family has values and traditions that endure. For almost a century, Elkay has been a family-owned and operated company, providing thousands of jobs that support our families and communities.



Product Compliance:

ADA & ICC A117.1 ASME A112.19.3/CSA B45.4 BUY AMERICAN ACT




Sinks are listed by IAPMO[®] as meeting the applicable requirements of the Uniform Plumbing Code[®], International Plumbing Code[®], and National Plumbing Code of Canada.



Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards.

Clean and Care Manual (PDF) Installation Instructions (PDF) Warranty (PDF)

Similar models are available with: 4", 4-1/2", 5", 6", and 6-1/2" depths, CuVerro antimicrobial copper, Quick-Clip Mounting System




In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.



Hole Drilling Configurations:

1-1/2" (38mm) Diameter Faucet Holes on 4" (102mm) Centers



OPTIONAL ACCESSORIES

Screw

CBS1418	
LK99, LKAD35	
LKGT1041CR, LKGT1041NK,	
LKGT1041RB	
LK364, LK463	
LKWRB1418SS	
LKGT1054	

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.