



TANKTEX™

WATER FINDING FLOWABLE PASTE

DESCRIPTION

TANKTEX™ flowable paste detects and locates water in fuel oil and gasoline tanks. TANKTEX™ warns against the possibility of corrosion, product degradation and contamination due to water. It turns violet in color on contact with water.

CHARACTERISTICS

- * Squeeze bottle makes it easy to use.
- * Easy to see
- * Supersensitive

APPLICATIONS

TANKTEX™ may be used with petroleum and petroleum based products.

PACKAGING

<u>Code</u>	<u>Size</u>	<u>Qty./Case</u>	<u>Lbs./Case</u>	<u>Cu. Ft./Case</u>
68462	2 Oz.	24	7	0.144

TANKTEX™ WATER FINDING FLOWABLE PASTE

INSTRUCTIONS

READ ALL DIRECTIONS, MSDS AND WARNINGS ON LABEL BEFORE USING

DIRECTIONS:

Shake well.

- 1) Lift spout. Invert bottle while moving it in a downward motion to apply a bead on measuring device.
- 2) Be sure to touch bottom of tank or vessel. If paste turns violet in color, water is present.

For additional technical information, call Toll Free 1-800-231-3345

PRECAUTIONS

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

CAUTION: EYE IRRITANT.
KEEP OUT OF REACH OF CHILDREN.
CONTAINS ALKALINE MATERIAL.

FIRST AID: EYES: Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately. **SKIN:** Wash off with soap and water. Seek medical attention if irritation persists. **INGESTION:** If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

For additional information, refer to Material Safety Data Sheet.

SPECIFICATIONS

Wt/Gal @ 77°F	8.26
Flash Point SETA CC	>350° F (176°C)
Color	Green Paste
Shelf Life	2 years minimum

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

LIMITED WARRANTY

Rectorseal® makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. **THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL®.** The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Rectorseal® shall not be liable for incidental or consequential damages.

MANUFACTURED IN U.S.A. BY
Rectorseal® • 2601 Spenwick Drive • Houston, Texas 77055-1035
Telephone: 713-263-8001 or 1-800-231-3345 Fax: 713-263-7577 or 1-800-441-0051
www.rectorseal.com