



GRIME-SOLV™

FOAMING HEAVY DUTY CLEANER AND DEGREASER

DESCRIPTION

GRIME-SOLV™ is a foaming, heavy duty, cleaner and degreaser, for use on marine and automotive engines, heating, air conditioning and refrigeration equipment, and all types of machinery that can be rinsed with water or wiped with a rag. The foam holds the cleaning agents where sprayed, concentrating the powerful emulsifiable chemicals to lift off dirt and grease.

CHARACTERISTICS

- * Non-flammable
- * Safe for metals
- * Non-corrosive
- * Excellent cleaner/degreaser
- * Wipes clean or rinses with water

APPLICATIONS

GRIME-SOLV™ lifts encrusted grime, grease or carbon from oil burning , air conditioning and refrigeration equipment, marine and automotive engines and other machinery that can be rinsed with water or wiped with a rag. Can be used to remove stains from concrete driveways and brick walls, to clean white wall tires, and for cleaning surfaces before painting.

PACKAGING

<u>Code</u>	<u>Size</u>	<u>Qty./Case</u>	<u>Lbs./Case</u>	<u>Cu. Ft./Case</u>
88436	14 ounce aerosol	12	14	0.52

INSTRUCTIONS

READ ALL DIRECTIONS, MSDS AND WARNINGS ON LABEL BEFORE USING

- SHAKE WELL BEFORE USING.
- Spray from 6 to 10 inches away and thoroughly saturate areas to be cleaned. Faster action is obtained by gently brushing GRIME-SOLV™ into the grease and grime being removed. Brushing is essential on unusually heavy deposits.
- Allow GRIME-SOLV™ to penetrate for a short time.
- Flush off with water – the stronger the stream the better. When hosing down engines, be certain to start the engine as soon as possible and idle until the engine becomes warm enough to evaporate the water.
- If used on painted surfaces, wash GRIME-SOLV™ off immediately to avoid removing the wax finish or streaking the paint.
- Test on plastic surfaces prior to use. Product will damage certain plastics.

For additional technical information, call Toll Free 1-800-231-3345

PRECAUTIONS

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

WARNING!
CONTENTS UNDER PRESSURE.
VAPOR HARMFUL – KEEP OUT OF REACH OF CHILDREN
READ BACK PANEL CAREFULLY.

CONTAINS; CHLORINATED SOLVENTS. Use only as directed with adequate ventilation. Avoid contact with eyes and skin. Do not spray into fire or on hot surfaces. Store at room temperature. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120° F.

FIRST AID: Skin: Wash off with soap and water. **Eyes:** Flush with water for 15 minutes. Seek medical attention if irritation persists. **Inhalation:** Move to fresh air. Give artificial respiration if breathing has stopped, and oxygen if available. Call physician immediately.

For additional information, refer to Material Safety Data Sheet.

SPECIFICATIONS

Wt/Gal @ 77°F	11.04 lbs/ gal.
Flash Point SETA CC	None
Color	White foam
Shelf Life	2 years minimum

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

LIMITED WARRANTY

RectorSeal makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. **THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL.** The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal shall not be liable for incidental or consequential damages.

MANUFACTURED IN U.S.A. BY
RectorSeal • 2601 Spenwick Drive • Houston, Texas 77055-1035
Telephone: 713-263-8001 or 1-800-231-3345 Fax: 713-263-7577 or 1-800-441-0051
www.rectorseal.com