

Tube Nuts & Sleeves



Nut

0486	OD mm	OD	£
4BMTXS	6	1/4"	0.60
5BMTXS	8	5/16"	0.80
6BMTXS	10	3/8"	0.95
8BMTXS	12	1/2"	0.85
10BMTXS	14,15,16	5/8"	1.65
12BMTXS	18, 20	3/4"	3.00
16BMTXS	25	1"	4.90
20BMTXS	28,30,32	1.1/4"	13.15
24BMTXS	35,38	1.1/2"	16.30



Metric Sleeve

0486	OD mm	£
TXS6	6	0.55
TXS8	8	0.60
TXS10	10	0.55
TXS12	12	0.55
TXS14	14	3.35
TXS15	15	1.10
TXS16	16	0.85
TXS18	18	3.40
TXS20	20	1.10
TXS25	25	2.90
TXS30	30	5.90
TXS32	32	7.45
TXS38	38	9.95

Imperial Sleeve

0486	OD	£
4TXS	1/4"	1.05
5TXS	5/16"	1.25
6TXS	3/8"	1.65
8TXS	1/2"	1.65
10TXS	5/8"	1.90
12TXS	3/4"	2.40
16TXS	1"	2.85
20TXS	1.1/4"	12.55
24TXS	1.1/2"	25.45

Straight Union



Tube x Tube

0486	OD mm	OD	£
4HTXS	6	1/4"	6.95
5HMTXS	8	5/16"	6.50
6HMTXS	10	3/8"	9.70
8HMTXS	12	1/2"	6.95
10HMTXS	14,15,16	5/8"	7.05
12HMTXS	18, 20	3/4"	10.65
16HMTXS	25	1"	16.75
20HMTXS	28,30,32	1.1/4"	34.10
24HMTXS	35,38	1.1/2"	45.40

Reducer, Tube x Tube

0486	OD mm	OD	OD mm	OD	£
8-6HTXS	12	1/2"	10	3/8"	9.90
10-8HMTXS	14,15,16	5/8"	12	1/2"	11.00
12-10HMTXS	18, 20	3/4"	14,15,16	5/8"	12.80
16-12HMTXS	25	1"	18, 20	3/4"	20.10
20-16HMTXS	28,30,32	1.1/4"	25	1"	40.95

Tee Union



Tube x Tube

0486	OD mm	OD	£
4JMTXS	6	1/4"	18.80
5JMTXS	8	5/16"	19.00
6JMTXS	10	3/8"	15.90
8JMTXS	12	1/2"	22.15
10JMTXS	14,15,16	5/8"	24.60
12JMTXS	18, 20	3/4"	29.25
16JMTXS	25	1"	44.45
20JTXS	28,30,32	1.1/4"	93.45
24JTXS	35,38	1.1/2"	115.25

90° Elbow Union



Tube x Tube

0486	OD mm	OD	£
4ETXS	6	1/4"	12.35
5EMTXS	8	5/16"	14.05
6ETXS	10	3/8"	14.70
8EMTXS	12	1/2"	12.30
10EMTXS	14,15,16	5/8"	17.80
12EMTXS	18, 20	3/4"	21.25
16EMTXS	25	1"	34.60
20EMTXS	28,30,32	1.1/4"	62.75
24EMTXS	35,38	1.1/2"	95.20

Bulkhead Union



Straight, Tube x Tube

0486	OD mm	OD	£
4WMTXWLNMS	6	1/4"	10.45
5WMTXWLNMS	8	5/16"	14.00
6WMTXWLNMS	10	3/8"	10.60
8WMTXWLNMS	12	1/2"	13.10
10WMTXWLNMS	14,15,16	5/8"	15.50
12WTXWLNMS	18, 20	3/4"	20.65
16WMTXWLNMS	25	1"	33.45
20WMTXWLNMS	28,30,32	1.1/4"	51.30
24WTXWLNMS	35,38	1.1/2"	102.35



90° Elbow, Tube x Tube

0486	OD mm	OD	£
4WETXWLNMS	6	1/4"	10.45
5WEMTXWLNMS	8	5/16"	14.00
6WEMTXWLNMS	10	3/8"	10.60
8WEMTXWLNMS	12	1/2"	13.10
10WEMTXWLNMS	14,15,16	5/8"	15.50
12WEMTXWLNMS	18, 20	3/4"	20.65
16WETXWLNMS	25	1"	33.45
20WETXWLNMS	28,30,32	1.1/4"	51.30



Lock Nut

0486		£
4WLNMS	7/16"	10.45
5WLNMS	1/2"	14.00
6WLNMS	9/16"	10.60
8WLNMS	3/4"	13.10
10WLNMS	7/8"	15.50
12WLNMS	1.1/16"	20.65
16WLNMS	1.5/16"	33.45
20WLNMS	1.5/8"	51.30

Male Stud Coupling



NPT

0486	OD mm	OD	W	£
4-4FMTXS	6	1/4"	1/4"	8.40
5FMTXS	8	5/16"	1/8"	11.10
6-2FTXS	10	3/8"	1/8"	11.30
6FMTXS	10	3/8"	1/4"	9.00
6-6FTXS	10	3/8"	3/8"	12.10
8FMTXS	12	1/2"	3/8"	11.80
8-8FTXS	12	1/2"	1/2"	9.85
10-6FMTXS	14,15,16	5/8"	3/8"	14.40
10FMTXS	14,15,16	5/8"	1/2"	13.90
12-8FTXS	18,20	3/4"	1/2"	16.05
12FMTXS	18,20	3/4"	3/4"	14.80
12-16FTXS	18,20	3/4"	1"	22.65
16FMTXS	25	1"	1"	22.15
16-20FTXS	25	1"	1.1/4"	54.50
20FTXS	28,30,32	1.1/4"	1.1/4"	41.95
24FMTXS	35,38	1.1/2"	1.1/2"	46.75



BSPT

0486	OD mm	OD	W	£
4-4F3MXS	6	1/4"	1/4"	7.55
5F3MXS	8	5/16"	1/8"	11.05
6F3MXS	10	3/8"	1/4"	11.40
6-6F3MXS	10	3/8"	3/8"	12.00
8F3MXS	12	1/2"	3/8"	15.15
8-8F3MXS	12	1/2"	1/2"	12.55
10-6F3MXS	14,15,16	5/8"	3/8"	12.50
10F3MXS	14,15,16	5/8"	1/2"	13.75
12-8F3MXS	18,20	3/4"	1/2"	16.90
12F3MXS	18,20	3/4"	3/4"	15.85
12-16F3MXS	18,20	3/4"	1"	22.70
16-12F3MXS	25	1"	3/4"	34.35
16F3MXS	25	1"	1"	30.85
20-16F3MXS	28,30,32	1.1/4"	1"	43.85
20F3MXS	28,30,32	1.1/4"	1.1/4"	42.05
24F3MXS	35,38	1.1/2"	1.1/2"	51.05

O-Ring + Retaining Ring (ISO 1179), BSPP

0486	OD mm	OD	W	£
4F4OMXS	6	1/4"	1/8"	7.05
4-4F4OMXS	6	1/4"	1/4"	6.30
4-6F4OMXS	6	1/4"	3/8"	9.75
5-4F4OMXS	8	5/16"	1/4"	7.15
6F4OMXS	10	3/8"	1/4"	6.05
6-6F4OMXS	10	3/8"	3/8"	6.35
6-8F4OMXS	10	3/8"	1/2"	10.10
8-4F4OMXS	12	1/2"	1/4"	8.85
8F4OMXS	12	1/2"	3/8"	7.10
8-8F4OMXS	12	1/2"	1/2"	8.10
8-12F4OMXS	12	1/2"	3/4"	16.05
10-6F4OMXS	14,15,16	5/8"	3/8"	8.60
10F4OMXS	14,15,16	5/8"	1/2"	8.25
12-8F4OMXS	18,20	3/4"	1/2"	12.40
12F4OMXS	18,20	3/4"	3/4"	12.70
12-16F4OMXS	18,20	3/4"	1"	24.95
16-12F4OMXS	25	1"	3/4"	16.80
16F4OMXS	25	1"	1"	16.40
20-16F4OMXS	28,30,32	1.1/4"	1"	34.60
20F4OMXS	28,30,32	1.1/4"	1.1/4"	42.10
24F4OMXS	35,38	1.1/2"	1.1/2"	74.90

ED Seal, BSPP

0486	OD mm	OD	W	£
4F42EDMXS	6	1/4"	1/8"	6.45
4-4F42EDMXS	6	1/4"	1/4"	5.75
4-6F42EDMXS	6	1/4"	3/8"	9.00
4-8F42EDMXS	6	1/4"	1/2"	14.10
5-4F42EDMXS	8	5/16"	1/4"	6.05
6-2F42EDMXS	10	3/8"	1/8"	7.95
6F42EDMXS	10	3/8"	1/4"	5.50
6-6F42EDMXS	10	3/8"	3/8"	6.35
6-8F42EDMXS	10	3/8"	1/2"	8.55
8-4F42EDMXS	12	1/2"	1/4"	8.10
8F42EDMXS	12	1/2"	3/8"	6.45
8-8F42EDMXS	12	1/2"	1/2"	8.10
8-12F42EDMXS	12	1/2"	3/4"	14.70
10-6F42EDMXS	14,15,16	5/8"	3/8"	7.85
10F42EDMXS	14,15,16	5/8"	1/2"	8.25
12-8F42EDMXS	18,20	3/4"	1/2"	15.25
12F42EDMXS	18,20	3/4"	3/4"	12.70
12-16F42EDMXS	18,20	3/4"	1"	19.65
16-12F42EDMXS	25	1"	3/4"	14.00
16F42EDMXS	25	1"	1"	16.40
20-16F42EDMXS	28,30,32	1.1/4"	1"	31.70
20F42EDMXS	28,30,32	1.1/4"	1.1/4"	35.10
24F42EDMXS	35,38	1.1/2"	1.1/2"	68.10

O-Ring Seal, UNF

0486	OD mm	OD	W	£
4F5OMXS	6	1/4"	7/16"	7.05
4-6F5OMXS	6	1/4"	9/16"	9.75
5-4F5OMXS	8	5/16"	7/16"	7.15
6F5OMXS	10	3/8"	9/16"	6.05
6-4F5OMXS	10	3/8"	7/16"	6.35
6-5F5OMXS	10	3/8"	1/2"	10.10
8F5OMXS	12	1/2"	3/4"	7.10
8-10F5OMXS	12	1/2"	7/8"	8.10
10F5OMXS	14,15,16	5/8"	7/8"	8.25
12-8F5OMXS	18,20	3/4"	3/4"	12.40
12F5OMXS	18,20	3/4"	1.1/16"	12.70
12-16F5OMXS	18,20	3/4"	1.5/16"	24.95
16F5OMXS	25	1"	1.5/16"	16.40
20-16F5OMXS	28,30,32	1.1/4"	1.5/16"	34.60
20F5OMXS	28,30,32	1.1/4"	1.5/8"	42.10
24F5OMXS	35,38	1.1/2"	1.7/8"	74.90



O-Ring Seal (ISO6149), Metric

0486	OD mm	OD	W	£
4M10F870MXS	6	1/4"	M10x1.0	7.05
6M16F870MXS	10	3/8"	M16x1.5	6.35
6M18F870MXS	10	3/8"	M18x1.5	10.10
8M18F870MXS	12	1/2"	M18x1.5	7.10
16M27F870MXS	25	1"	M27x2.0	16.40
16M33F870MXS	25	1"	M33x2.0	34.60
20M42F870MXS	28,30,32	1.1/4"	M42x2.0	42.10

Dash Size	Tube Size		Thread Size UN / UNF
	(Inch)	(mm)	
2	1/8"	—	5/16-24
3	3/16"	—	3/8-24
4	1/4"	6	7/16-20
5	5/16"	8	1/2-20
6	3/8"	10	9/16-18
8	1/2"	12	3/4-16
10	5/8"	14,15,16	7/8-14
12	3/4"	18,20	1.1/6-12
14	7/8"	22	1.3/6-12
16	1"	25	1.5/6-12
20	1.1/4"	28,30,32	1.5/8-12
24	1.1/2"	35,38	1.7/8-12
28	—	42	2.1/4-12
32	2"	50	2.1/2-12

Male Stud 90° Elbow



BSPT

0486	OD mm	OD		£
4-4C3MXS	6	1/4"	1/4"	15.85
5-4C3MXS	8	5/16"	1/4"	15.60
6C3MXS	10	3/8"	1/4"	15.80
6-6C3MXS	10	3/8"	3/8"	18.90
8C3MXS	12	1/2"	3/8"	19.50
8-8C3MXS	12	1/2"	1/2"	22.90
10-6C3MXS	14,15,16	5/8"	3/8"	23.45
10C3MXS	14,15,16	5/8"	1/2"	24.45
12-8C3MXS	18,20	3/4"	1/2"	43.60
12C3MXS	18,20	3/4"	3/4"	40.40
16-12C3MXS	25	1"	3/4"	56.50
16C3MXS	25	1"	1"	56.40
20-16C3MXS	28,30,32	1.1/4"	1"	86.25
20C3MXS	28,30,32	1.1/4"	1.1/4"	89.15
24C3MXS	35,38	1.1/2"	1.1/2"	108.35



NPT

0486	OD mm	OD		£
4-4CTXS	6	1/4"	1/4"	16.10
5-4CTXS	8	5/16"	1/4"	16.75
6-2CTXS	10	3/8"	1/8"	22.35
6CMTXS	10	3/8"	1/4"	14.55
6-6CMTXS	10	3/8"	3/8"	19.50
8CTXS	12	1/2"	3/8"	18.85
8-8CTXS	12	1/2"	1/2"	22.75
10-6CTXS	14,15,16	5/8"	3/8"	21.20
10CTXS	14,15,16	5/8"	1/2"	28.30
12-8CTXS	18,20	3/4"	1/2"	37.85
12CTXS	18,20	3/4"	3/4"	32.00
12-16CTXS	18,20	3/4"	1"	51.35
16CTXS	25	1"	1"	39.55
20CTXS	28,30,32	1.1/4"	1.1/4"	41.95
24CTXS	35,38	1.1/2"	1.1/2"	46.75

O-Ring Seal
(ISO6149), Metric



0486	OD mm	OD		£
4M10C870MXS	6	1/4"	M10x1.0	14.60
5M12C870MXS	8	5/16"	M12x1.5	18.90
6M14C870MXS	10	3/8"	M14x1.5	13.30
6M16C870MXS	10	3/8"	M16x1.5	21.25
8M16C870MXS	12	1/2"	M16x1.5	22.00
8M18C870MXS	12	1/2"	M18x1.5	16.40
12M22C870MXS	18,20	3/4"	M22x1.5	25.95
12M27C870MXS	18,20	3/4"	M27x2.0	37.50
16M33C870MXS	25	1"	M33x2.0	60.25

O-Ring + Retaining Ring
(ISO 1179), BSPP

0486	OD mm	OD		£
4C4OMXS	6	1/4"	1/8"	13.10
4-4C4OMXS	6	1/4"	1/4"	12.25
5-4C4OMXS	8	5/16"	1/4"	12.35
6C4OMXS	10	3/8"	1/4"	11.65
6-6C4OMXS	10	3/8"	3/8"	13.60
6-8C4OMXS	10	3/8"	1/2"	20.35
8-4C4OMXS	12	1/2"	1/4"	15.85
8C4OMXS	12	1/2"	3/8"	13.45
8-8C4OMXS	12	1/2"	1/2"	17.75
8-12C4OMXS	12	1/2"	3/4"	32.00
10-6C4OMXS	14,15,16	5/8"	3/8"	18.05
10C4OMXS	14,15,16	5/8"	1/2"	17.40
12-8C4OMXS	18,20	3/4"	1/2"	23.00
12C4OMXS	18,20	3/4"	3/4"	25.40
12-16C4OMXS	18,20	3/4"	1"	37.60
16-12C4OMXS	25	1"	3/4"	38.05
16C4OMXS	25	1"	1"	37.20
20-16C4OMXS	28,30,32	1.1/4"	1"	67.65
20C4OMXS	28,30,32	1.1/4"	1.1/4"	68.85
24C4OMXS	35,38	1.1/2"	1.1/2"	89.80



O-Ring Seal, UNF

0486	OD mm	OD		£
4C5OMXS	6	1/4"	7/16"	16.60
4-6C5OXS	6	1/4"	9/16"	12.75
6C5OMXS	10	3/8"	9/16"	14.00
6-4C5OXS	10	3/8"	7/16"	16.80
6-8C5OXS	10	3/8"	3/4"	24.80
8C5OMXS	12	1/2"	3/4"	18.60
8-10C5OMXS	12	1/2"	7/8"	27.75
10C5OMXS	14,15,16	5/8"	7/8"	26.00
12-10C5OMXS	18,20	3/4"	7/8"	31.55
12C5OMXS	18,20	3/4"	1.1/16"	31.25
12-16C5OXS	18,20	3/4"	1.5/16"	54.45
16C5OMXS	25	1"	1.5/16"	40.35
20C5OXS	28,30,32	1.1/4"	1.5/8"	87.55
24C5OXS	35,38	1.1/2"	1.7/8"	120.65

Male Stud 45° Elbow



BSPT

0486	OD mm	OD		£
4V3MXS	6	1/4"	1/8"	35.90
6V3MXS	10	3/8"	1/4"	27.30
8V3MXS	12	1/2"	3/8"	29.30
12V3MXS	18,20	3/4"	3/4"	35.90
16V3MXS	25	1"	1"	50.50



NPT

0486	OD mm	OD		£
4VTXS	6	1/4"	1/8"	24.10
5VTXS	8	5/16"	1/8"	23.05
6VTXS	10	3/8"	1/4"	28.40
8VTXS	12	1/2"	3/8"	30.40
10VTXS	14,15,16	5/8"	1/2"	33.90
12VTXS	18,20	3/4"	3/4"	38.90
16VTXS	25	1"	1"	57.30



O-Ring + Retaining Ring
(ISO 1179), BSPP

0486	OD mm	OD		£
4V4OMXS	6	1/4"	1/8"	23.45
4-4V4OMXS	6	1/4"	1/4"	21.35
6V4OMXS	10	3/8"	1/4"	16.15
6-6V4OMXS	10	3/8"	3/8"	21.95
6-8V4OMXS	10	3/8"	1/2"	27.30
8V4OMXS	12	1/2"	3/8"	20.40
8-8V4OMXS	12	1/2"	1/2"	23.25
10V4OMXS	14,15,16	5/8"	1/2"	18.85
12V4OMXS	18,20	3/4"	3/4"	26.05
16V4OMXS	25	1"	1"	57.35



O-Ring Seal, UNF

0486	OD mm	OD		£
4V5OXS	6	1/4"	7/16"	24.90
6V5OXS	10	3/8"	9/16"	19.05
8V5OXS	12	1/2"	3/4"	20.25
10V5OXS	14,15,16	5/8"	7/8"	26.30
12V5OXS	18,20	3/4"	1.1/16"	46.85
16V5OXS	25	1"	1.5/16"	68.70

Tee Union



Male Run Tee, O-Ring Seal, UNF

0486	OD mm	OD		£
4R5OXS	6	1/4"	7/16"	40.05
6R5OXS	10	3/8"	9/16"	38.55
8R5OXS	12	1/2"	3/4"	44.20
10R5OXS	14,15,16	5/8"	7/8"	50.90
12R5OXS	18,20	3/4"	1.1/16"	68.55
16R5OXS	25	1"	1.5/16"	91.85



Male Branch Tee, O-Ring Seal, UNF

0486	OD mm	OD		£
4S5OXS	6	1/4"	7/16"	31.90
6S5OXS	10	3/8"	9/16"	35.95
8S5OXS	12	1/2"	3/4"	39.45
10S5OXS	14,15,16	5/8"	7/8"	57.20
12S5OXS	18,20	3/4"	1.1/16"	59.30
16S5OXS	25	1"	1.5/16"	58.60



Male Run Tee, NPT

0486	OD mm	OD		£
4RTXS	6	1/4"	1/8"	17.80
6RTXS	10	3/8"	1/4"	28.60
8RTXS	12	1/2"	3/8"	31.80
10RTXS	14,15,16	5/8"	1/2"	42.65
12RTXS	18,20	3/4"	3/4"	51.65
16RTXS	25	1"	1"	104.10



Male Branch Tee, NPT

0486	OD mm	OD		£
4STXS	6	1/4"	1/8"	17.80
6STXS	10	3/8"	1/4"	28.60
8STXS	12	1/2"	3/8"	31.80
10STXS	14,15,16	5/8"	1/2"	42.65
12STXS	18,20	3/4"	3/4"	51.65
16STXS	25	1"	1"	104.10



Male Run Tee, O-Ring + Retaining Ring (ISO 1179), BSPP

0486	OD mm	OD		£
4R4OMXS	6	1/4"	1/8"	42.05
6R4OMXS	10	3/8"	1/4"	19.00
8R4OMXS	12	1/2"	3/8"	27.75
10R4OMXS	14,15,16	5/8"	1/2"	29.95
12R4OMXS	18,20	3/4"	3/4"	46.30
16R4OMXS	25	1"	1"	59.75



Male Branch Tee, O-Ring + Retaining Ring (ISO 1179), BSPP

0486	OD mm	OD		£
4S4OMXS	6	1/4"	1/8"	33.25
6S4OMXS	10	3/8"	1/4"	21.30
8S4OMXS	12	1/2"	3/8"	25.45
10S4OMXS	14,15,16	5/8"	1/2"	39.40
12S4OMXS	18,20	3/4"	3/4"	47.70
16S4OMXS	25	1"	1"	68.15

Fixed Female Connectors



Straight, Tube x NPT

0486	OD mm	OD		£
4GTXS	6	1/4"	1/8"	13.95
6GTXS	10	3/8"	1/4"	9.00
8GTXS	12	1/2"	3/8"	11.80
10GTXS	14,15,16	5/8"	1/2"	13.90
12GTXS	18,20	3/4"	3/4"	14.80
16GTXS	25	1"	1"	22.15



90° Elbow, Tube x NPT

0486	OD mm	OD		£
4DTXS	6	1/4"	1/8"	19.35
6DTXS	10	3/8"	1/4"	28.10
8DTXS	12	1/2"	3/8"	35.15
10DTXS	14,15,16	5/8"	1/2"	61.95
12DTXS	18,20	3/4"	3/4"	78.10
16DTXS	25	1"	1"	92.55

Dash Size	Tube Size		Thread Size UN / UNF
	(Inch)	(mm)	
2	1/8"	—	5/16-24
3	3/16"	—	3/8-24
4	1/4"	6	7/16-20
5	5/16"	8	1/2-20
6	3/8"	10	9/16-18
8	1/2"	12	3/4-16
10	5/8"	14,15,16	7/8-14
12	3/4"	18,20	1.1/8-12
14	7/8"	22	1.3/8-12
16	1"	25	1.5/8-12
20	1.1/4"	28,30,32	1.5/8-12
24	1.1/2"	35,38	1.7/8-12
28	—	42	2.1/4-12
32	2"	50	2.1/2-12

Swivel Male x Female Stud Coupling



NPT

0486	OD mm	OD		£
4F6XS	6	1/4"	1/8"	17.35
4-4F6XS	6	1/4"	1/4"	16.95
5F6XS	8	5/16"	1/8"	17.50
6F6XS	10	3/8"	1/4"	17.00
6-6F6XS	10	3/8"	3/8"	19.10
8F6XS	12	1/2"	3/8"	24.10
10F6XS	14,15,16	5/8"	1/2"	26.30
12F6XS	18,20	3/4"	3/4"	26.55
16F6XS	25	1"	1"	37.75



BSPT

0486	OD mm	OD		£
4F63MXS	6	1/4"	1/8"	18.30
4-4F63MXS	6	1/4"	1/4"	18.30
6F63MXS	10	3/8"	1/4"	19.70
8F63MXS	12	1/2"	3/8"	22.95
10F63MXS	14,15,16	5/8"	1/2"	25.50
12F63MXS	18,20	3/4"	3/4"	30.05
16F63MXS	25	1"	1"	39.00



O-Ring + Retaining Ring (ISO 1179),
BSPP

0486	OD mm	OD		£
4F64OMXS	6	1/4"	1/8"	16.30
5-4F64OMXS	8	5/16"	1/4"	12.05
6F64OMXS	10	3/8"	1/4"	11.65
6-6F64OMXS	10	3/8"	3/8"	13.80
8F64OMXS	12	1/2"	3/8"	12.95
10F64OMXS	14,15,16	5/8"	1/2"	15.00
12F64OMXS	18,20	3/4"	3/4"	19.25
16F64OMXS	25	1"	1"	30.70
20F64OMXS	28,30,32	1.1/4"	1.1/4"	62.60
24F64OMXS	35,38	1.1/2"	1.1/2"	102.65

ED Seal, BSPP

0486	OD mm	OD		£
4F642EDMXS	6	1/4"	1/8"	15.05
4-4F642EDMXS	6	1/4"	1/4"	11.65
5-4F642EDMXS	8	5/16"	1/4"	12.05
6F642EDMXS	10	3/8"	1/4"	8.95
6-6F642EDMXS	10	3/8"	3/8"	11.70
8-4F642EDMXS	12	1/2"	1/4"	15.00
8F642EDMXS	12	1/2"	3/8"	10.80
8-8F642EDMXS	12	1/2"	1/2"	13.90
10-6F642EDMXS	14,15,16	5/8"	3/8"	14.40
10F642EDMXS	14,15,16	5/8"	1/2"	12.50
12-8F642EDMXS	18,20	3/4"	1/2"	17.00
12F642EDMXS	18,20	3/4"	3/4"	17.50
16-12F642EDMXS	25	1"	3/4"	29.05
16F642EDMXS	25	1"	1"	25.55



O-Ring Seal, UNF

0486	OD mm	OD		£
4F65OMXS	6	1/4"	7/16"	17.35
6F65OMXS	10	3/8"	9/16"	18.20
8F65OMXS	12	1/2"	3/4"	23.55
10F65OMXS	14,15,16	5/8"	7/8"	27.15
12F65OMXS	18,20	3/4"	1.1/16"	32.40
16F65OMXS	25	1"	1.5/16"	42.40



O-Ring Seal (ISO6149), Metric

0486	OD mm	OD		£
4M10F6870MXS	6	1/4"	M10x1.0	19.65
5M12F6870MXS	8	5/16"	M12x1.5	22.35
6M14F6870MXS	10	3/8"	M14x1.5	22.70
8M16F6870MXS	12	1/2"	M16x1.5	26.90
10M18F6870MXS	14,15,16	5/8"	M18x1.5	24.45
12M27F6870MXS	18,20	3/4"	M27x2.0	33.90

Tube End Reducing Adaptors



Tube x Tube

0486	OD mm	OD	OD mm	OD	£
6-4TRTXS	10	3/8"	6	1/4"	6.15
6-5TRTXS	10	3/8"	8	5/16"	8.35
8-4TRTXS	12	1/2"	6	1/4"	6.25
8-5TRTXS	12	1/2"	8	5/16"	6.75
8-6TRTXS	12	1/2"	10	3/8"	5.70
10-4TRTXS	14,15,16	5/8"	6	1/4"	8.25
10-6TRTXS	14,15,16	5/8"	10	3/8"	7.45
10-8TRTXS	14,15,16	5/8"	6	1/4"	8.95
12-4TRTXS	18,20	3/4"	6	1/4"	11.60
12-6TRTXS	18,20	3/4"	10	3/8"	12.35
12-8TRTXS	18,20	3/4"	12	1/2"	9.55
12-10TRTXS	18,20	3/4"	14,15,16	5/8"	11.45
16-8TRTXS	25	1"	12	1/2"	14.55
16-10TRTXS	25	1"	14,15,16	5/8"	19.00
16-12TRTXS	25	1"	18,20	3/4"	14.55
20-10TRTXS	28,30,32	1.1/4"	14,15,16	5/8"	66.70
20-12TRTXS	28,30,32	1.1/4"	18,20	3/4"	66.70
20-16TRTXS	28,30,32	1.1/4"	25	1"	40.30
24-20TRTXS	35,38	1.1/2"	28,30,32	1.1/4"	50.05

Gauge Connector



(ISO 1179-1), BSPP

0486	OD mm	OD		£
4G4MXS	6	1/4"	1/8"	10.70
4-4G4MXS	6	1/4"	1/4"	13.20
5G4MXS	8	5/16"	1/8"	27.30
6G4MXS	10	3/8"	1/4"	12.50
6-6G4MXS	10	3/8"	3/8"	13.10
8G4MXS	12	1/2"	3/8"	20.80
8-8G4MXS	12	1/2"	1/2"	15.65
10G4MXS	14,15,16	5/8"	1/2"	11.65
12G4MXS	18,20	3/4"	3/4"	31.95
16G4MXS	25	1"	1"	29.15

Tube x Female Swivel Nut



90° Elbow

0486	OD mm	OD	£
4C6MXS	6	1/4"	13.60
5C6MXS	8	5/16"	14.20
6C6MXS	10	3/8"	14.45
8C6MXS	12	1/2"	14.95
10C6MXS	14,15,16	5/8"	16.10
12C6MXS	18, 20	3/4"	23.00
16C6MXS	25	1"	33.75
20C6XS	28,30,32	1.1/4"	63.50
24C6XS	35,38	1.1/2"	85.60



45° Elbow

0486	OD mm	OD	£
4V6XS	6	1/4"	16.60
5V6XS	8	5/16"	20.00
6V6MXS	10	3/8"	15.10
8V6XS	12	1/2"	16.20
10V6MXS	14,15,16	5/8"	20.40
12V6XS	18, 20	3/4"	25.65
16V6XS	25	1"	43.70
20V6XS	28,30,32	1.1/4"	75.10
24V6XS	35,38	1.1/2"	95.55

Run Tee

0486	OD mm	OD	£
4R6MXS	6	1/4"	22.75
5R6MXS	8	5/16"	24.05
6R6MXS	10	3/8"	20.10
8R6MXS	12	1/2"	20.40
10R6MXS	14,15,16	5/8"	24.65
12R6MXS	18, 20	3/4"	32.00
16R6MXS	25	1"	45.15
20R6XS	28,30,32	1.1/4"	101.20
24R6XS	35,38	1.1/2"	117.70



Branch Tee

0486	OD mm	OD	£
4S6XS	6	1/4"	23.75
5S6MXS	8	5/16"	27.10
6S6MXS	10	3/8"	20.50
8S6MXS	12	1/2"	21.55
10S6MXS	14,15,16	5/8"	28.75
12S6MXS	18, 20	3/4"	33.45
16S6MXS	25	1"	49.65
20S6XS	28,30,32	1.1/4"	107.45
24S6XS	35,38	1.1/2"	140.35

Blanking Ends



Male, Plug

0486	OD mm	OD	£
4PNTXS	6	1/4"	7.00
5PNTXS	8	5/16"	7.60
6PNTXS	10	3/8"	5.65
8PNTXS	12	1/2"	5.95
10PNMTXS	14,15,16	5/8"	6.90
12PNMTXS	18, 20	3/4"	9.15
16PNTXS	25	1"	15.35
20PNTXS	28,30,32	1.1/4"	23.35
24PNTXS	35,38	1.1/2"	30.65



Female, Cap

0486	OD mm	OD	£
4FNMTXS	6	1/4"	2.25
5FNMTXS	8	5/16"	3.15
6FNMTXS	10	3/8"	2.60
8FNMTXS	12	1/2"	2.80
10FNMTXS	14,15,16	5/8"	3.95
12FNMTXS	18, 20	3/4"	5.20
16FNMTXS	25	1"	7.65
20FNMTXS	28,30,32	1.1/4"	31.75
24FNMTXS	35,38	1.1/2"	36.20



Triple-Lok® is the original 37° flare fitting designed by Parker. Continued improvements and refinements give a higher working pressure than the minimum levels specified in the ISO 8434-2 and SAE J514 international standards.

Maybe this and the reputation for reliability is the reason that **Triple-Lok®** has been chosen by more OEM equipment manufacturers than any other brand of "JIC fitting".