



PIPE SLEEVING

Specifications:

Furnish and install Water-Tite pipe sleeving to protect plastic and copper piping in concrete. Water-Tite pipe sleeving is most commonly used in concrete slab construction for pipes that are set into the concrete. Product shall be Water-Tite product code checked below as manufactured by IPS Corporation.

FEATURES:

Material: Polyethylene

Accommodates Pipe sizes: 1/2", 3/4" and 1"

Color-Coded: Red = Hot and Blue = Cold

Packaging: Self-dispensing box



DIRECTIONS:

1. Cut desired length of pipe sleeving
2. Insert piping into sleeve prior to pouring concrete slab
3. Red = Hot and Blue = Cold

PRECAUTIONS:

Limit sun exposure, as prolonged exposure will eventually deteriorate polyethylene.

Read all directions and cautions prior to using this product

√	Product Code #	Product Description	Thickness	Width	Model #	Units/Case
	83405	Red for 1/2" - 1" Tubing (200' Roll)	0.004"	2.25"	WTSR4	20
	83407	Blue for 1/2" - 1" Tubing (200' Roll)	0.004"	2.25"	WTSB4	20
	83400	Red for 1/2" - 1" Tubing (200' Roll)	0.006"	2.25"	WTSR	20
	83404	Blue for 1/2" - 1" Tubing (200' Roll)	0.006"	2.25"	WTSB	20
	83409	Red for 1/2" - 1" Tubing (200' Roll)	0.010"	2.25"	WTSR10	20
	83410	Blue for 1/2" - 1" Tubing (200' Roll)	0.010"	2.25"	WTSB10	20
Ultra-Flex Heavy 25 mil. Pipe Sleeving is ideal for both CPVC and Copper Piping Systems. Not intended for PEX						
	83416	Red Ultra-Flex Heavy for 1/2" - 1" Tubing (100' Roll)	0.025"	2.18"	83416	1
	83417	Blue Ultra-Flex Heavy for 1/2" - 1" Tubing (100' Roll)	0.025"	2.18"	83417	1
	83418	Red Ultra-Flex Heavy for 1/2" - 1" Tubing (50' Roll)	0.025"	2.18"	83418	1
	83419	Blue Ultra-Flex Heavy for 1/2" - 1" Tubing (50' Roll)	0.025"	2.18"	83419	1

