


Class 300 (XS/XH)

FIG. 3166

Coupling



For Listings/Approval Details and Limitations, visit our website at www.anvilintl.com or contact an Anvil® Sales Representative.

FIGURE 3166 - COUPLING

Nominal Size	Dimension A	Approx. Wt. Each
<i>In. (mm)</i>	<i>In. (mm)</i>	<i>Lbs. (kg)</i>
1/4	1.38	0.17
8	35.05	0.08
3/8	1.63	0.26
10	41.40	0.12
1/2	1.88	0.42
15	47.75	0.19
3/4	2.13	0.65
20	54.10	0.29
1	2.38	0.99
25	60.45	0.45
1 1/4	2.88	1.60
32	73.15	0.73
1 1/2	2.88	2.00
40	73.15	0.91
2	3.63	3.20
50	92.20	1.45
2 1/2	4.13	5.50
65	104.90	2.49
3	4.13	7.30
80	104.90	3.31

MATERIAL SPECIFICATIONS

Dimensions: Fittings: ASME B16.3
 Unions: ASME B16.39
 Bushings/Plugs: ASME B16.14

Material: ASTM A-197

Finish: Black or Hot Dip Galvanized per ASTM A153 Class A

Threads: NPT per ASME B1.20.1

Pressure Ratings: Fittings: ASME B16.3
 Unions: ASME B16.39
 Bushings/Plugs: ASME B16.14

Pressure Testing: All malleable iron fittings are tested for through wall porosity using an air under water process.

Agency Approvals: All malleable iron fittings and unions are UL/ULC Listed and FM Approved.

PROJECT INFORMATION

APPROVAL STAMP

Project:	<input type="checkbox"/> Approved
Address:	<input type="checkbox"/> Approved as noted
Contractor:	<input type="checkbox"/> Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	