



SPECIFICATION SHEET

280-EV6141

EVOLUTION™ DELUXE 6141 FULL BRIM HARD HAT

- Meets ANSI Z89.1-2014 Type I Class E requirements (Class C for Vented)
- High-Density Polyethylene (HDPE) shell with a full brim providing additional protection against sun, glare, rain and falling debris
- Extended back brim helps protect neck and ears from the sun's UV rays, as well as a run-off for rain and snow...short front brim shades the face while allowing excellent visibility
- Brim includes finger grips on front and rear, as well as a textured underside to reduce reflection/glare
- 6-Point suspension system with polyester textile straps offers unrivaled comfort without compromising performance
- Unique "3D Adjustment" provides a precise fit using harness depth settings...unlike any other hard hat on the US market today
- EasyJust™ Slip Ratchet is simple to adjust and an improved alternative to the traditional pin-lock system
- Chamlon™ sweatband for maximum sweat absorption
- Universal slots to fit various accessories
- Packed ready-to-wear with no installation of the suspension required

APPLICATIONS

- Construction
- Oil & gas
- Mining
- Demolition
- High pressure jetting
- Energy companies
- Certain emergency services (FEMA & USAR)
- High-risk environments where high impact situations are of concern

CARE INSTRUCTIONS

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature.

TECHNICAL DATA

MATERIAL	Shell: High Density Polyethylene, Recyclable Suspension: HDPE strap & clips, polyester straps Sweatband: Egyptian cotton core with PU coating
COLOR	<input type="checkbox"/> White (-10) <input type="checkbox"/> Blue (-50) <input type="checkbox"/> Lime Yellow (-LY) <input type="checkbox"/> Yellow (-20) <input type="checkbox"/> Red (-60) <input type="checkbox"/> Bright Orange (-OR) <input type="checkbox"/> Green (-30)
HAT SIZE	6 5/8 - 8 (20 7/8" - 25")
EACH WEIGHT	14.5 oz / 411.1 g
PACKAGING	10 per case
CASE	12.6" x 21.7" x 17.9" / 32cm x 55.1cm x 45.5cm
CASE WEIGHT	16 lbs / 7.3 kg
COO	USA

BARCODES

ITEM	EACH	DOZEN	CASE
<input type="checkbox"/> 280-EV6141-10	5038428010863	---	5038428812450
<input type="checkbox"/> 280-EV6141-20	5038428010870	---	5038428812467
<input type="checkbox"/> 280-EV6141-30	5038428010887	---	5038428812474




BARCODES CONT.

<input type="checkbox"/> 280-EV6141-50	5038428010894	---	5038428812481
<input type="checkbox"/> 280-EV6141-60	5038428010900	---	5038428812498
<input type="checkbox"/> 280-EV6141-LY	5038428010931	---	5038428812528
<input type="checkbox"/> 280-EV6141-OR	5038428010924	---	5038428812511
ITEM	EACH	DOZEN	CASE
VENTED HARD HATS (CLASS C)			
<input type="checkbox"/> 280-EV6141V-10	5038428011112	---	5038428812610
<input type="checkbox"/> 280-EV6141V-20	5038428011129	---	5038428812627

DIMENSIONS (in/cm)

	OSFA						
A	11.5 / 29.2						
B	6.375 / 16.2						



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

968 Albany Shaker Road | Latham, NY 12110 | 800-262-5755 | 518-861-0133 | Fax: 518-861-0144 | sales@pipusa.com | www.pipusa.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.