


**Two-way (2/2) general service solenoid valves have one inlet port and one outlet port.**

- Control of air, water, light oil, and non-corrosive media
- Normally closed (opens when energized) and normally open (closes when energized) operation
- Size range of 1/8" to 3"



**General Service - 2/2 Normally Closed 1/8"**

Pipe Size (in)	Orifice (in)	Cv Flow	Operating Pressure Differential (psi)				Max. Fluid Temp. °F	Valve Catalog Number	Body Material	Sealing Material	Voltage	Valve Order Code	Wattage	Approvals		Rebuild Kit Order Code	Replacement Coil Order Code	Approx. Shipping Weight (lbs.)
			Min.	Air	Water	Light Oil								UL	FM			
<b>2/2 Normally Closed</b>																		
1/8	3/64	0.06	0	750	750	725	180	8262H001	BR	NBR	120/60,110/50	<b>21959</b>	6.1	○	○	323581	238210-032-D*	2.3
		0.06	0	750	750	725	180	8262H001	BR	NBR	240/60,220/50	<b>22056</b>	6.1	○	○	323581	238210-058-D*	2.3
	1/16	0.08	0	220	220	220	180	SC8256A002V	BR	FKM	24/DC	<b>21833</b>	6.9	□	-	-	400125-142-*	0.5
		0.08	0	220	220	220	180	U8256A002V	BR	FKM	24/DC	<b>21834</b>	6.9	□	-	-	400125-142-D*	0.5
	3/32	0.21	0	370	330	190	180	8262H014	BR	NBR	120/60,110/50	<b>21972</b>	6.1	○	○	323581	238210-032-D*	2.3
		0.21	0	370	330	190	180	EF8262H014	BR	NBR	120/60,110/50	<b>21973</b>	6.1	○	○	323581	238214-032-D*	2.3
		0.21	0	235	160	160	180	8262H014	BR	NBR	24/DC	<b>21975</b>	10.6	○	○	323557	238310-006-D*	2.3
		0.21	0	235	160	160	180	8262H014	BR	NBR	12/DC	<b>21974</b>	10.6	○	○	323557	238310-004-D*	2.3
	7/64	0.19	0	135	126	80	180	SC8256B045V	BR	FKM	120/60, 110/50	<b>21836</b>	6.3	□	-	-	400125-225-*	0.6
		0.19	0	63	63	63	180	U8256B045V	BR	FKM	24/DC	<b>21844</b>	6.9	□	-	-	400125-142-D*	0.6
		0.19	0	135	126	80	180	U8256B045V	BR	FKM	120/60	<b>21843</b>	6.3	□	-	-	400125-225-D*	0.6
		0.19	0	135	126	80	180	U8256B046V	SS	FKM	120/60, 110/50	<b>21838</b>	6.3	□	-	-	400125-225-*	0.6
	1/8	0.35	0	185	180	120	180	OPSF8262H002	BR	NBR	120/60,110/50	<b>22064</b>	6.1	○	○	325145	238212-032-*	2.3
			0	185	180	120	180	8262H002	BR	NBR	120/60,110/50	<b>21960</b>	6.1	○	○	3235145	238210-032-D*	2.3
			0	185	180	120	180	8262H002	BR	NBR	24/60	<b>21965</b>	6.1	○	○	3235145	238210-005-D*	2.3
			0	185	180	120	180	8262H002	BR	NBR	240/60,220/50	<b>21963</b>	6.1	○	○	3235145	238210-058-D*	2.3
			0	185	180	120	180	8262H002	BR	NBR	480/60,440/50	<b>21964</b>	6.1	○	○	3235145	238210-088-D*	2.3
			0	185	180	120	180	EF8262H002	BR	NBR	120/60,110/50	<b>21962</b>	6.1	○	○	3235145	238214-032-D*	2.3
			0	185	180	120	180	8262H002V	BR	FKM	120/60,110/50	<b>21961</b>	6.1	○	○	323581-V	238210-032-D*	2.3
			0	130	110	95	180	8262H002	BR	NBR	12/DC	<b>21966</b>	10.6	○	○	323587	238310-006-D*	2.3
0			130	110	95	180	8262H002	BR	NBR	24/DC	<b>21967</b>	10.6	○	○	323587	238310-004-D*	2.3	
0			155	180	140	180	8262H006	SS	NBR	120/60,110/50	<b>21968</b>	6.1	○	○	323583	238210-032-D*	2.3	

## General Service - 2/2 Normally Closed 1/2"

Pipe Size (in)	Orifice (in)	Cv Flow	Operating Pressure Differential (psi)				Max. Fluid Temp. °F	Valve Catalog Number	Body Material	Sealing Material	Voltage	Valve Order Code	Wattage	Approvals		Rebuild Kit Order Code	Replacement Coil Order Code	Approx. Shipping Weight (lbs.)	
			Min.	Max.										UL	FM				
				Air	Water	Light Oil													
<b>2/2 Normally Closed</b>																			
7/16		2.2	5	40	40	-	150	8210G015	BR	NBR	24/DC	<b>21851</b>	11.6	●	-	302374	238710-006-D*	2.0	
		2.2	5	150	125	-	180	8210G015	BR	NBR	120/60,110/50	<b>20126</b>	6.1	●	-	302275	238210-032-D*	2.0	
		2.2	5	150	125	-	180	8210G015	BR	NBR	24/60	<b>20130</b>	6.1	●	-	302275	238210-005-D*	2.0	
		2.2	5	150	125	-	180	8210G015	BR	NBR	240/60,220/50	<b>20128</b>	6.1	●	-	302275	238210-058-D*	2.0	
		2.2	5	150	125	-	180	EF8215G015	BR	NBR	120/60,110/50	<b>20127</b>	6.1	●	-	302275	238214-032-D*	2.0	
		2.2	5	150	125	-	180	8210G037	SS	NBR	120/60,110/50	<b>20179</b>	6.1	●	-	302327	238210-032-D*	2.0	
		2.2	5	150	125	-	180	EF8210G037	SS	NBR	120/60,110/50	<b>20181</b>	6.1	●	-	302327	238214-032-D*	2.0	
		2.8	0	4	6	-	180	8030G016	BR	NBR	120/60,110/50	<b>20010</b>	6.1	○	●	302789	238210-032-D*	2.7	
		2.8	0	15	15	-	200	8030G017	BR	NBR	120/60	<b>21443</b>	16.1	○	-	302790	272610-032-D*	2.7	
	2.8	0	15	-	-	180	8030G017VH	BR	NBR	120/60	<b>21444</b>	16.1	-	-	302790-VH	272610-032-D*	2.7		
3/8		3.2	25	1500	1500	1500	200	8223G003	BR	NYLON	120/60,110/50	<b>20359</b>	17.1	-	-	302315	238610-132-D*	3.4	
		3.2	25	1500	1500	1500	200	8223G010	SS	PTFE	120/60,110/50	<b>20364</b>	17.1	-	-	302322	238610-132-D*	3.4	
17/32		4.5	5	230	230	230	195	SC8238T405	BR	BR	120/60	<b>21900</b>	4.0	□	-	323457	43005573	2.0	
		4.5	5	230	230	230	195	SC8238T405	BR	BR	24/60	<b>21901</b>	4.0	□	-	323457	43005582	2.0	
1/2		4	0	150	150	-	180	8210G094	BR	NBR	120/60,110/50	<b>20229</b>	10.1	○	-	302272	238610-032-D*	3.2	
		4	0	150	150	-	180	8210G094	BR	NBR	24/60	<b>20246</b>	10.1	○	-	302272	238610-005-D*	3.2	
		4	0	150	150	-	180	8210G094	BR	NBR	240/60,220/50	<b>20243</b>	10.1	○	-	302272	238610-058-D*	3.2	
		4	0	150	150	-	180	EF8210G094	BR	NBR	120/60,110/50	<b>20236</b>	10.1	○	-	302272	238214-032-D*	3.2	
		4	0	150	150	-	180	JKF8210G094	BR	NBR	120/60,110/50	<b>20242</b>	10.1	○	-	302272	238612-032-*	3.2	
		4	0	150	150	-	180	JSF8210G094	BR	NBR	120/60,110/50	<b>21778</b>	10.1	○	-	302272	238612-032-*	3.2	
		4	0	150	150	-	180	SC8210G094	BR	NBR	120/60,110/50	<b>21031</b>	10.1	○	-	302272	238612-032-*	3.2	
		4	0	150	150	-	180	8210G094M0	BR	NBR	120/60,110/50	<b>20231</b>	10.1	○	-	302272-M0	238610-032-D*	3.2	
		4	0	150	150	-	180	8210G094V	BR	FKM	120/60,110/50	<b>20233</b>	10.1	○	-	302272-V	238610-032-D*	3.2	
		4	0	150	-	-	180	8210G094N	BR	NBR	120/60,110/50	<b>20232</b>	10.1	○	-	302272-N	238610-032-D*	3.2	
		4	0	40	40	-	150	8210G094	BR	NBR	24/DC	<b>20248</b>	11.6	○	-	302372	238710-006-D*	3.2	
		4	0	40	40	-	150	8210G094	BR	NBR	12/DC	<b>20247</b>	11.6	○	-	302372	238710-004-D*	3.2	
		4	0	40	40	-	150	SC8210G094	BR	NBR	24/DC	<b>21621</b>	11.6	○	-	302372	238712-006-*	3.2	
		4	0	150	150	125	175	8210G087	SS	NBR	120/60,110/50	<b>20201</b>	17.1	●	-	302328	238610-132-D*	3.3	
		4	0	150	150	125	175	EF8210G087	SS	NBR	120/60,110/50	<b>20204</b>	17.1	●	-	302328	238614-132-D*	3.3	
		4	0	150	150	125	175	EF8210G087V	SS	FKM	120/60,110/50	<b>20206</b>	17.1	●	-	302328-V	238614-132-D*	3.3	
		4	0	150	150	-	175	8210G087E	SS	EPDM	120/60,110/50	<b>20202</b>	17.1	-	-	302328-E	238610-132-D*	3.3	
	5/8		4	0	40	40	-	150	8210G087	SS	NBR	24/DC	<b>21722</b>	11.6	●	-	302423	238710-006-D*	3.3
			4	0	40	40	-	150	EF8210G087	SS	NBR	24/DC	<b>20209</b>	11.6	●	-	302423	238714-006-D*	3.2
			4	5	200	150	135	180	8210G002	BR	NBR	120/60,110/50	<b>20043</b>	6.1	○	-	302273	238210-032-D*	3.2
			4	5	200	150	135	180	8210G002	BR	NBR	24/60	<b>20058</b>	6.1	○	-	302273	238210-005-D*	3.2
			4	5	200	150	135	180	8210G002	BR	NBR	240/60,220/50	<b>20053</b>	6.1	○	-	302273	238210-058-D*	3.2
			4	5	200	150	135	180	8210G002	BR	NBR	480/60,440/50	<b>20056</b>	6.1	○	-	302273	238210-088-D*	3.2
			4	5	200	150	135	180	EF8210G002	BR	NBR	120/60,110/50	<b>20049</b>	6.1	○	-	302273	238214-032-D*	3.2
		4	5	200	150	135	180	EF8210G002M0	BR	NBR	120/60,110/50	<b>20050</b>	6.1	○	-	302273-M0	238214-032-D*	3.2	
		4	5	200	150	135	180	JKF8210G002	BR	NBR	120/60,110/50	<b>20051</b>	6.1	○	-	302273	238212-032-*	3.2	
		4	5	200	150	135	180	SC8210G002	BR	NBR	120/60,110/50	<b>20995</b>	6.1	○	-	302273	238212-032-*	3.2	
		4	5	200	150	135	180	JSF8210G002	BR	NBR	120/60,110/50	<b>20989</b>	6.1	●	-	302273	238212-032-*	3.2	
		4	5	200	150	135	180	8210G002M0	BR	NBR	120/60,110/50	<b>20046</b>	6.1	●	-	302273-M0	238210-032-D*	3.2	
		4	5	200	150	135	180	8210G002V	BR	FKM	120/60,110/50	<b>20048</b>	6.1	-	-	302273-V	238210-032-D*	3.2	
		4	5	125	-	-	140	8210G002Q	BR	NBR	120/60	<b>21311</b>	15.1	□	-	304006	270110-032-D*	3.2	
		4	5	125	100	100	150	8210G002	BR	NBR	24/DC	<b>20062</b>	11.6	○	-	302373	238710-006-D*	3.2	
		4	5	125	100	100	150	8210G002	BR	NBR	12/DC	<b>20061</b>	11.6	○	-	302373	238710-004-D*	3.2	
		4	5	125	100	100	150	EF8210G002	BR	NBR	24/DC	<b>20063</b>	11.6	○	-	302373	238714-006-D*	3.2	
		4	5	125	100	100	150	SC8210G002	BR	NBR	24/DC	<b>21134</b>	11.6	○	-	302373	238712-006-*	3.2	
		4	5	300	300	300	175	8210G007	BR	NBR	120/60,110/50	<b>20095</b>	17.1	□	-	302274	238610-132-D*	3.2	
		4	5	300	300	300	175	EF8210G007	BR	NBR	120/60,110/50	<b>20098</b>	17.1	□	-	302274	238614-132-D*	3.2	
3/4			4.4	0	50	-	-	125	8215G020	AL	NBR	120/60,110/50	<b>20290</b>	10.1	○	●	302350	238610-032-D*	2.8
			4.4	0	50	-	-	125	EF8215G020	AL	NBR	120/60,110/50	<b>20292</b>	10.1	○	●	302350	238614-032-D*	2.8
			4.4	0	50	-	-	104	SC8215G020	AL	NBR	120/60,110/50	<b>21785</b>	10.1	-	-	302350	238612-032-*	2.8
			4.4	0	25	-	-	104	8215G020	AL	NBR	12/DC	<b>20294</b>	11.6	○	●	302430	238710-004-D*	2.8

Refer to inside cover for ordering information.