

ULTRALINE[®] HDPE WATER SERVICE PIPE & TUBING

DRISCOPEX[®] 5100 SERIES ULTRALINE[®] HDPE WATER SERVICE PIPE & TUBING



Ultraline[®] HDPE Water Service Pipe and Tubing is available to meet your needs in compliance with ASTM D2239, ASTM D2737 or ASTM D3035 product standard.

Produced from only the highest rated HDPE pipe materials, Driscopex[®] 5100 Series Ultraline[®] HDPE Pipe and Tubing are manufactured of PE4710 resin listed in PPI-TR4.

Ultraline[®] HDPE Water Service Pipe and Tubing from Performance Pipe meets the requirements of:

- AWWA C 901-08
- NSF/ANSI 61
- NSF /ANSI 14
- ASTM D3350 cell class 445574

When Performance Matters Rely on
Performance Pipe

ULTRALINE® HDPE WATER SERVICE PIPE & TUBING

Performance Pipe Ultraline® Water Service Pipe and Tubing Pressure Class is based on applications at temperatures up to and including 80°F. Contact Performance Pipe for guidance on operating at higher temperatures. See the PPI **Field Service Manual for Municipal Water** for installation guidance. The manual is available as a free download at www.performancepipe.com in the Water/Wastewater section.

ASTM D2239 Inside Diameter Controlled HDPE Pipe (IPS/SDR)

SIZE	SDR	NOMINAL OD / ID	COIL LENGTH / PALLET QTY	COIL LENGTH / PALLET QTY	WEIGHT LB/100FT	PRESSURE CLASS
3 / 4 "	7	1.074"/0.824"	100'/1800'	400'/4000'	16	250 psi
1"	7	1.367"/1.049"	100'/1800'	300'/2400'	25	250 psi
1 – 1 / 4 "	7	1.798"/1.380"	100'/1500'	300'/2100'	43	250 psi
1 – 1 / 2 "	7	2.098"/1.610"	100'/1400'	300'/1800'	59	250 psi
2 "	7	2.692"/2.067"	100'/1000'	300'/2100'	97	250 psi

ASTM D2737 Outside Diameter Controlled HDPE Tubing (CTS)

SIZE	SDR	NOMINAL OD / ID	COIL LENGTH / PALLET QTY	COIL LENGTH / PALLET QTY	WEIGHT LB/100FT	PRESSURE CLASS
3 / 4 "	9	0.875"/0.669"	100' / 1800'	500' / 7500'	10	250 psi
1"	9	1.125"/0.860"	100' / 1600'	300' / 4200'	17	250 psi
1 – 1 / 4 "	9	1.375"/1.051"	100' / 1400'	300' / 2400'	26	250 psi
1 – 1 / 2 "	9	1.625"/1.241"	100' / 1300'	300' / 2400'	36	250 psi
2 "	9	2.125"/1.625"	100' / 1300'	300' / 2700'	61	250 psi

ASTM D3035 Outside Diameter Controlled HDPE Pipe (IPS/SDR)

SIZE	SDR	NOMINAL OD / ID	COIL LENGTH / PALLET QTY	COIL LENGTH / PALLET QTY	WEIGHT LB/100FT	PRESSURE CLASS
3/4 "	11	1.050"/0.849"	150'/1800'	500'/3500'	13	200 psi
1"	11	1.315"/1.061"	150'/1800'	500'/3000'	20	200 psi
1-1/4"	11	1.660"/1.358"	150'/1500'	500'/6000'	31	200 psi
1-1/2"	11	1.900"/1.554"	250'/2500'	500'/4000'	41	200 psi
2"	13.5	2.375"/2.002"	150'/1800'	500'/3500'	53	160 psi
2"	11	2.375"/1.917"	150'/1800'	500'/3500'	64	200 psi
3"	17	3.500"/3.063"	250'/1750'	1000'/2000'	94	125 psi
3"	13.5	3.500"/2.951"	250'/1750'	1000'/2000'	116	160 psi
3"	11	3.500"/2.826"	250'/1750'	1000'/2000'	140	200 psi

Solid black pipe and tubing is standard. Contact your Performance Pipe representative for additional sizes and information.

When Performance Matters Rely on
Performance Pipe