

Campbell

Cast Iron Well Seals



SUB5 5/8X1

SUB6X1

SUB6X1 1/2S

SUB4X2S

SUB5X1

SUB4X1

JET2X1

| part | casing i.d. | drop pipe | vent tapping | cable hole |
|--------|----------------|--------------|-----------------|---------------|
| JET2X1 | 2 | 1 | - | - |

All Submersible Well Seals can be converted to Jet Well Seals by plugging conduit tap with a Malleable Square Head Plug (page C5).

JET WELL SEAL



| | | | | |
|--------------|---|-------|-----|-----|
| SUB2X1 1/4GS | 2 | 1-1/4 | 1/8 | - |
| SUB4X1S | 4 | 1 | 1/2 | 3/4 |
| SUB4X1 1/4S | 4 | 1-1/4 | 1/2 | 3/4 |
| SUB4X1 1/2S | 4 | 1-1/2 | 1/2 | 3/4 |
| SUB4X2S | 4 | 2 | 1/2 | 3/4 |
| SUB6X1S | 6 | 1 | 1/2 | 3/4 |
| SUB6X1 1/4S | 6 | 1-1/4 | 1/2 | 3/4 |
| SUB6X1 1/2S | 6 | 1-1/2 | 1/2 | 3/4 |
| SUB6X2S | 6 | 2 | 1/2 | 3/4 |

Note: SUB2X1 1/4GS is designed to fit outside of well casing.

SOLID WELL SEAL (submersible)



| | | | | |
|-----------------|--------|-------|-----|--------|
| SUB3X3/4 | 3 | 3/4 | 1/8 | 7/16** |
| SUB3X1 | 3 | 1 | 1/8 | 7/16** |
| SUB3X1 1/4 | 3 | 1-1/4 | 1/8 | 7/16** |
| SUB4X3/4 | 4 | 3/4 | 1/2 | 1/2 |
| SUB4X1† | 4 | 1 | 1/2 | 3/4 |
| SUB4X1G* | 4 | 1 | 1/2 | 3/4 |
| SUB4X1 1/4† | 4 | 1-1/4 | 1/2 | 3/4 |
| SUB4X1 1/4G* | 4 | 1-1/4 | 1/2 | 3/4 |
| SUB4X2GS | 4 | 2 | 1/4 | 1/2 |
| SUB4 1/4X3/4 | 4-1/4 | 3/4 | 1/2 | 1/2 |
| SUB4 1/4X1 | 4-1/4 | 1 | 1/2 | 1/2 |
| SUB4 1/4X1 1/4 | 4-1/4 | 1-1/4 | 1/2 | 1/2 |
| SUB4 1/4X1 1/2 | 4-1/4 | 1-1/2 | 1/2 | 1/2 |
| SUB4 1/2X3/4 | 4-1/2 | 3/4 | 1/2 | 1/2 |
| SUB4 1/2X1 | 4-1/2 | 1 | 1/2 | 1/2 |
| SUB4 1/2X1 1/4 | 4-1/2 | 1-1/4 | 1/2 | 1/2 |
| SUB4 1/2X1 1/2 | 4-1/2 | 1-1/2 | 1/2 | 1/2 |
| SUB4 1/2X2 | 4-1/2 | 2 | 1/2 | 1/2 |
| SUB5X3/4 | 5 | 3/4 | 1/2 | 3/4 |
| SUB5X1 | 5 | 1 | 1/2 | 3/4 |
| SUB5X1G* | 5 | 1 | 1/2 | 3/4 |
| SUB5X1 1/4 | 5 | 1-1/4 | 1/2 | 3/4 |
| SUB5X1 1/2 | 5 | 1-1/2 | 1/2 | 3/4 |
| SUB5X2 | 5 | 2 | 1/2 | 3/4 |
| SUB5 3/16X1 | 5-3/16 | 1 | 1/2 | 3/4 |
| SUB5 3/16X1 1/4 | 5-3/16 | 1-1/4 | 1/2 | 3/4 |
| SUB5 3/16X1 1/2 | 5-3/16 | 1-1/2 | 1/2 | 3/4 |
| SUB5 3/16X2 | 5-3/16 | 2 | 1/2 | 3/4 |
| SUB5 5/8X3/4 | 5-5/8 | 3/4 | 1/2 | 3/4 |
| SUB5 5/8X1 | 5-5/8 | 1 | 1/2 | 3/4 |
| SUB5 5/8X1 1/4 | 5-5/8 | 1-1/4 | 1/2 | 3/4 |
| SUB5 5/8X1 1/2 | 5-5/8 | 1-1/2 | 1/2 | 3/4 |
| SUB5 5/8X2 | 5-5/8 | 2 | 1/2 | 3/4 |
| SUB6X3/4 | 6 | 3/4 | 1/2 | 3/4 |
| SUB6X1 | 6 | 1 | 1/2 | 1 |
| SUB6X1G* | 6 | 1 | 1/2 | 1 |
| SUB6X1 1/4 | 6 | 1-1/4 | 1/2 | 1 |
| SUB6X1 1/4G* | 6 | 1-1/4 | 1/2 | 1 |
| SUB6X1 1/2 | 6 | 1-1/2 | 1/2 | 1 |
| SUB6X2 | 6 | 2 | 1/2 | 1 |
| SUB6X2 1/2 | 6 | 2-1/2 | 1/2 | 1 |
| SUB6X3 | 6 | 3 | 1/2 | 3/4 |
| SUB6 1/8X3/4 | 6-1/8 | 3/4 | 1/2 | 3/4 |
| SUB6 1/8X1 | 6-1/8 | 1 | 1/2 | 3/4 |
| SUB6 1/8X1 1/4 | 6-1/8 | 1-1/4 | 1/2 | 3/4 |
| SUB6 1/8X1 1/2 | 6-1/8 | 1-1/2 | 1/2 | 3/4 |

SPLIT WELL SEAL (submersible)



continued on K2

*Imported

**Cable hole is not tapped.

†S-split type (see photo).

All seals individually packaged.

Other sizes and styles available upon request.

Campbell Manufacturing, Inc.
 127 East Spring Street, P.O. Box 207
 Bechtelsville, PA 19505-0207
 800-523-0224, Fax 610-369-3580