



**MIGHTYFLEX  
METAL BALLCOCK  
TOILET CONNECTOR**  
Specification Sheet

PART NO.	DESCRIPTION	LENGTH
SWC-512-PP	7/8" Ballcock x 3/8" Soft Compression	12"
SWC-612-PP	7/8" Ballcock	12"
SWC-616-PP	x 1/2" Soft Compression	16"

**DESIGN FEATURES**

- Chloramine resistant soft cones
- Exclusive POWR-TIGHT 12-point crimp-many times industry standard
- Chloramine resistant tubing
- Withstands dramatic changes in water pressure
- Easy installation, no special tools or soldering required.

**MATERIAL SPECIFICATIONS**

- Working Pressure: 160 psi
- Operating Temperature: 33° F - 140° F
- Tubing: Reinforced PVC, NSF 61 Compliant
- Nuts & End Fittings: Nickel-Plated Brass
- Washers: NSF 61 Compliant

**COMPLIANCES/LISTINGS**

- IAPMO Certified
- NSF Compliant
- ASME A112.18.6



3689 Arrowhead Drive, Carson City, NV 89706  
 Phone (800) 854-3215 Fax (800) 243-1777  
 E-mail sales@lspproducts.com Website www.lspproducts.com

Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained.

AF/S-2012 (04-08) Rev 3

Product Submittal	
Job Name	
Date	
Part Number	Quantity
Architect	
Contractor	