
## DUAL WALL FABRICATED TEES 4" - 30" DIAMETER


PART#	PIPE SIZE	Α	В	JOINT
0460AN	<b>4 in</b> (100 mm)	12.8 in (324 mm)	6.2 in (158 mm)	*
0661AN	6 in (150 mm)	16.5 in (419 mm)	8.1 in (207 mm)	*
0862AN	8 in (200 mm)	21.0 in (533 mm)	10.6 in (268 mm)	*
1063AN	<b>10 in</b> (250 mm)	26.0 in (660 mm)	12.6 in (320 mm)	*
1264AN	<b>12 in</b> (300 mm)	<b>30.7 in</b> (780 mm)	<b>15.4 in</b> (390 mm)	*
1264AN85B	<b>12 in</b> (300 mm)	21.1 in (536 mm)	10.6 in (268 mm)	ST
1264AN65B	12 in (300 mm)	21.1 in (536 mm)	10.6 in (268 mm)	WT
1565AN	<b>15 in</b> (375 mm)	38.9 in (987 mm)	19.4 in (494 mm)	*
1565AN85B	<b>15 in</b> (375 mm)	23.3 in (592 mm)	11.7 in (296 mm)	ST
1565AN65B	<b>15 in</b> (375 mm)	23.3 in (592 mm)	11.7 in (296 mm)	WT
1866AN	<b>18 in</b> (450 mm)	<b>42.9 in</b> (1089 mm)	21.4 in (545 mm)	*
1866AN85B	<b>18 in</b> (450 mm)	26.8 in (681 mm)	13.4 in (340 mm)	ST
1866AN65B	<b>18 in</b> (450 mm)	26.8 in (681 mm)	13.4 in (340 mm)	WT
2467AN	<b>24 in</b> (600 mm)	<b>50.4 in</b> (1280 mm)	25.2 in (640 mm)	*
2467AN85B	<b>24 in</b> (600 mm)	37.8 in (960 mm)	18.9 in (480 mm)	ST
2467AN65B	<b>24 in</b> (600 mm)	<b>37.8 in</b> (960 mm)	18.9 in (480 mm)	WT

<sup>\* =</sup> PLAIN END ST = SOIL TIGHT

WT = WATER TIGHT

NOTE: ALL FITTINGS DIMENSIONS ARE FOR REFERENCE ONLY





ST & WT (INCLUDES 3 GASKETS)



	DRAWING #:	2400	
Г	DRAWN BY:	JCB	05.23.07
	APPROVED BY:	JCB	06.26.07
	REVISIONS:	TJR	2/2/2010
Г			·

<sup>\*\*</sup> LIMITED AVAILABILITY. PLEASE SEE INJECTION MOLDED FITTING SECTION FOR OTHER AVAILABLE FITTINGS