

A KOHLER, COMPANY

TRANQUII ITY®

#### **Features**

- 10-year consumer/3-year commercial limited warranty
- Available in either a high gloss or swirl gloss finish
- 60" (1524 mm) x 43-1/2" (1105 mm) x 18-1/8" (460 mm) rough-in dimensions include flanges
- 60" (1524 mm) x 42" (1067 mm) x 18-1/8" (460 mm) finished dimensions


42" OVAL BATH **61050100** ALSO 61051100, 71050100, 71051100



# **Codes/Standards Applicable**

Specified model meets or exceeds the following:

- ASTM E162
- ASTM E662
- HUD, UM Bulletin 73A
- NAHB Research Foundation, Inc.
- CSA B45.5/IAPMO Z124



#### Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

## **Specified Model**

Model	Description	Colors/Finis	shes
61050000	42" oval bath, with apron, 20 pack, swirl gloss finish	□ 0	☐ Other
61050100	42" oval bath, with apron, swirl gloss finish	□ 0	☐ Other
61051000	42" oval bath, without apron, 20 pack, swirl gloss finish	□ 0	☐ Other
61051100	42" oval bath, without apron, swirl gloss finish	□ 0	☐ Other
61058000	Apron only, 20 pack, swirl gloss finish	□ 0	☐ Other
61058100	Apron only, swirl gloss finish	□ 0	☐ Other
71050000	42" oval bath, with apron, 20 pack, high gloss finish	□ 0	☐ Other
71050100	42" oval bath, with apron, swirl high finish	□ 0	☐ Other
71051000	42" oval bath, without apron, 20 pack, high gloss finish	□ 0	☐ Other
71051100	42" oval bath, without apron, high gloss finish	□ 0	☐ Other
71058000	Apron only, 20 pack, high gloss finish	□ 0	☐ Other
71058100	Apron only, high gloss finish	<b>0</b>	□ Other

## **TRANQUILITY®**

### **Technical Information**

Fixture*:				
Bathing well:				
Basin area, bottom	42" (1067 mm) x 23" (584 mm)			
Basin area, top	51" (1295 mm) x 32-1/2" (826 mm)			
To overflow:				
Water depth	11-1/4" (286 mm)			
Capacity	56 gal (212 L)			
* Approximate measurements for comparison only.				

Door maximum width	*60" (1524 mm)	
Door maximum height	*NA	
* Varies with alternative walls.		

### **Installation Notes**

Install this product according to the installation guide.

Size the drain cutout to fit the drain assembly that will be used.

Double studding is recommended for pivot shower door installations.

Studs should be positioned roughly as shown.

When using the optional apron, use either the nailing-in flange on the apron or the three backing blocks to secure the apron.

