

MJ 100



FIBERGLASS MESH TAPE

TYPICAL APPLICATIONS

- For reinforcing joints, seams and connections when paint-on mastic is used in HVAC applications
- Can also be applied to drywall seams before the application of joint compound

PRODUCT FEATURES

- Self-adhering
- Light adhesive on one side for non-slipping
- Width selection provides ample support for mastic coat
- Fabric count – 8 ends by 8 picks for superior strength

CONSTRUCTION

Overall Grade/Function: Professional
Backing: Fiberglass mesh
Adhesive: Water-based acrylic

STANDARD WIDTH(S)

3 in 48 mm

STANDARD LENGTH(S)

150 ft 300 ft

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	75.5 lbs/in width	132.2 N/10 mm
Adhesion to Stainless Steel	8 oz/in width	0.88 N/10 mm
Thickness	9 mils	0.23 mm
Elongation	3.83%	3.83%

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

