

ProPEX lead-free (LF) copper straight stubs

Submittal information

Date submitted:

Project Information


| | |
|---------------------------------|-----------------|
| Job name : | Location : |
| Engineer : | Date submitted: |
| Contractor : | Submitted by: |
| Manufacturer's representative : | Approved by : |

Technical Data

| | |
|------------------------|--|
| Material | Copper |
| Temp./pressure ratings | 73°F (23°C) at 160 psi (11 bar) 180°F (82°C) at 100 psi (6.9 bar) 200°F (93°C) at 80 psi (5.5 bar) |

Product information and application use

ProPEX® Lead-free (LF) Copper Straight Stub transitions Uponor PEX tubing to copper pipe for use in hot and cold domestic potable water systems and hydronic radiant heating and cooling systems. The transition fitting can be used for direct transition to copper sweat, copper press and roll-groove applications. The transition fitting is safe for direct burial in soil.



| Part name | Part no. | A [inch] | B [inch] | C [inch] | D [inch] | Weight per UOM [lbs/UOM] | End type 1 | End type 2 |
|---|-----------|----------|----------|----------|----------|--------------------------|---------------|--------------|
| ProPEX LF Copper Straight Stub, 1/2" PEX LF Brass x 1/2" Copper (8") | LF2935050 | 8.3 | 0.709 | 7.592 | 0.77 | 0.22 | ProPEX 1/2" | Copper 1/2" |
| ProPEX LF Copper Straight Stub, 1/2" PEX LF Brass x 1/2" Copper (15") | LF2945050 | 14.5 | 0.709 | 13.792 | 0.77 | 0.4 | ProPEX 1/2" | Copper 1/2" |
| ProPEX LF Copper Straight Stub, 2 1/2" PEX LF Brass x 2 1/2" Copper | LF2962525 | 12.11 | 2.83 | 9.28 | 3.36 | 3.7 | ProPEX 2-1/2" | Sweat 2-1/2" |
| ProPEX LF Copper Straight Stub, 3" PEX LF Brass x 3" Copper | LF2963030 | 13.67 | 3.38 | 10.29 | 3.79 | 5.5 | ProPEX 3" | Sweat 3" |

Installation

Use the appropriate Uponor ProPEX Ring for the tubing (sold separately). Do not solder within 18 inches of the ProPEX fitting. Refer to the Uponor AquaPEX® Professional Plumbing Installation Guide or Uponor Hydronic Piping Design Assistance Manual for additional information.

Related applications

PEX-a Plumbing Systems
Hydronic Radiant Heating and Cooling Systems
Snow Melting Systems
Turf Conditioning Systems
Permafrost Prevention Systems

Codes

UPC|IBC|IRC|IPC|NPC of Canada|UMC|NSPC|IMC

Standards

NSF-372|ASTM F877|ASTM F1960|CSA B137.5|NSF-61|NSF-14

Listings

IAPMO-ES|ICC-ES-PMG|cNSFus-pw-G|U.P.Code*

Trademark Information

ProPEX® is a registered trademark of Uponor Inc. ProPEX™ is a trademark of Uponor Ltd.
* Some SKUs in this family have additional codes, standards, or listings. Please see uponor.com for complete information.

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.636.9517