



Location:



SYMMONS® Dia®



SLS-3512-1.5



SLS-3510-1.5




SLS-3512-1.5, SLS-3510-1.5
Single Handle Lavatory Faucet
Specification Submittal

Model Numbers	Feature Highlights
☐ SLS-3512-1.5 <i>Single Handle Lavatory Faucet with lift rod and metal drain assembly</i>	• Single hole mount configuration • Quarter turn ceramic cartridge • 23 inch braided hose water supply connections • 7-1/8" height • Lift rod and metal drain assembly (SLS-3512-1.5) • Standard 1.5 gpm (5.7 L/min) flow rate • Faucet shall be metal construction, plated in standard polished chrome finish
☐ SLS-3510-1.5 <i>Single Handle Lavatory Faucet, lift rod and drain not included</i>	
Finish Options/Modifications	Compliance
☐ -0.5 <i>0.5 gpm (1.9 L/min) flow restrictor</i>	-ASME A112.18.1/CSA B125.1 -NSF/ANSI 61.9; NSF/ANSI 372 -WaterSense 1.0 gpm, 1.5 gpm  
☐ -1.0 <i>1.0 gpm (3.8 L/min) flow restrictor</i>	
☐ -DP4 <i>4" deck plate</i>	
☐ -G <i>Grid drain</i>	
☐ -BBZ <i>Brushed Bronze finish</i>	
☐ -MB <i>Matte Black finish</i>	
☐ -STN <i>Satin Nickel finish</i>	
Note: Append appropriate -suffix to model number.	Warranty
	Limited Lifetime - to the original end purchaser in consumer/residential installations. 10 Years - for commercial/industrial installations. Refer to www.symmons.com/warranty for complete warranty information. 

Dimensions


Notes:

- (1) Dimensions subject to change without notice
- (2) Lift rod included with model SLS-3512-1.5 only






SYMMONS® Dia®



SLS-3512-1.5



SLS-3510-1.5



SLS-3512-1.5, SLS-3510-1.5

Grifo para lavabo con una sola manija

Presentación de especificaciones

Números de modelo	Características destacadas
☐ SLS-3512-1.5 <i>Grifo para lavabo con una sola manija con varilla de levantamiento y conjunto de desagüe metálico</i>	• Configuración de montura en un solo orificio • Cartucho de cerámica con un cuarto de vuelta • Manguera trenzada de 23 pulgadas con conexiones para suministro de agua • 7-1/8" de altura • Varilla de levantamiento y conjunto de desagüe metálico (SLS-3512-1.5) • Caudal estándar de 1.5 gal/min (5.7 L/min) • El grifo será de materiales metálicos, revestidos con un acabado cromado pulido estándar.
Opciones / Modificaciones de acabado	Cumplimiento
☐ -0.5  <i>Reductor de caudal de 0.5 gal/min (1.9 L/min)</i> ☐ -1.0  <i>Reductor de caudal de 1.0 gal/min (3.8 L/min)</i> ☐ -DP4 <i>Placa de cubierta de 4"</i> ☐ -G <i>Desagüe en rejilla</i> ☐ -BBZ <i>Acabado en bronce cepillado</i> ☐ -MB <i>Acabado en negro mate</i>	-ASME A112.18.1/CSA B125.1 -NSF/ANSI 61.9; NSF/ANSI 372 -WaterSense 1.0 gal/min, 1.5 gal/min  Garantía Limitada de por vida - para el comprador original del producto en establecimientos del consumidor/residenciales. 10años - para instalaciones industriales y comerciales. Consulte www.symmons.com/warranty para ob-
Nota: Anexar el -sufijo apropiado al número de	

(1) Las dimensiones pueden cambiar sin previo aviso
(2) La varilla de levantamiento solamente se incluye con el modelo SLS-3512-1.5

