# PEERLESS PTT188762A PTT188762A, PTT188782A, PTT188782A-LHD PTT188792A, PTT188792-ALHD

# PTT188792▲. PTT188792-▲LHD







▲ Designate Proper Finish Suffix

PSP-B-PTT188782 Rev. E



### **TUB AND SHOWER FAUCET**

- Precept<sup>™</sup> Collection
- Valve Only (PTT188762▲)
- Shower Only (PTT188782▲ & PTT188782▲-LHD)
- Tub/Shower (PTT188792▲ & PTT188792▲-LHD)

# **STANDARD SPECIFICATIONS:**

- Maintains a balanced pressure of hot and cold water even when a valve is turned on or off elsewhere in the system.
- For use with MultiChoice<sup>®</sup> Universal rough valve body. (R10000 Series)
- Tub/Shower. Requires 2 3/4" wall cavity.
- Back-to-back installation capability.
- Cartridge utilizes integral check valves to prevent the cross flow of water within the valve.
- Field adjustable means to limit handle rotation into hot water zone.
- Red/blue markings on escutcheon for hot/cold identification.
- Temperature only controlled with handle rotating a maximum of 120° from full cold to the full hot.
- · Easy turn dial to change shower head spray settings, pause is a non-positive shut-off
- Shower head with 6 spray settings Full body spray, massage spray, full spray with massage spay, focus spray, full spray with focus spray & pause.
- "-LHD" models indicate less shower head.
- Shower head maximum flow rate is 1.5 gpm @ 80 psi, 5.7 L/min @ 550 kPa.

## WARRANTY:

2 3/16"

(55 mm)

 Parts and Finish - Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.



### **COMPLIES WITH**

