

**M12™ Cable Stripper Kit**

2435CU-21, 2435AL-21, 2435X-21 (2435-20 Tool-Only)

**Specifications:**

Variable Speed Trigger	Yes
Tool Free Depth Gauge	Yes
Compatible Bushing Types	Industry Standard Quick-Change
Dimensions (L x W x H)	8.6" x 2.8" x 11.5"
Weight	3.6 lbs



**Includes:** 2435CU-21 1/0 AWG – 750 MCM Cu THHN / XHHW Bushings; 2435AL-21 1/0 AWG – 750 MCM Al THHN / XHHW Bushings; 2435X-21 1/0 AWG – 500 MCM Cu RHW / RHH / USE Bushings;  
**All Kits Include:** (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Multi-Voltage Charger, Carrying Case

**Reference Available Bushings on Pg. 62**



**M12™ 600 MCM Cable Cutter Kit**

2472-21XC (2472-20 Tool-Only)

**Specifications:**

Cut Capacity	600 MCM Copper, 750 MCM Aluminum, 1-3/16" Communication Cable
Jaw Opening	1-7/16"
Two-Speed	Yes
Length / Weight	10.5" / 6.7 lbs



**Includes:** (1) M12™ REDLITHIUM™ XC3.0 Battery Pack, Multi-Voltage Charger, Carrying Case

**Related Accessory:** 48-44-0410 M12™ 600 MCM Cable Cutter Blade

**M12™ Plastic Pipe Shear Kit**

2470-21 (2470-20 Tool-Only)

**Specifications:**

Cut Capacity	Up to 2" Schedule 80 PVC
Torque	1,900 in-lbs
Blade	3 mm Reinforced Stainless Steel
Length / Weight	14.4" / 4.4 lbs



**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Charger, Carrying Case

**Related Accessory:** 48-44-0405 M12™ Plastic Pipe Shear Blade

**M12™ Copper Tubing Cutter Kit**

2471-22, 2471-21 (2471-20 Tool-Only)

**Specifications:**

Cut Capacity	3/8" – 1" (1/2" – 1-1/8" O.D.)
Tubing Type	M, L and K Copper
RPM	500
Length / Weight	14.0" / 3.2 lbs



**Includes:** 2471-22 (2) M12™ REDLITHIUM™ CP1.5 Battery Packs; 2471-21 (1) M12™ REDLITHIUM™ CP1.5 Battery Pack;  
**All Kits Include:** Charger, Carrying Case

**Related Accessory:** 48-38-0010 Copper Cutter Wheel (2-Pack)

**M12™ Drain Snake Kit**

2571-21 (2571-20 Tool-Only)

**Specifications:**

Max Drain Line Capacity	1-1/4" – 2-1/2", Up to 25'
Drum Capacity	1/4" x 25', Best for 1-1/4" – 2" drain lines; 5/16" x 25', Best for 1-1/4" – 2-1/2" drain lines
Variable Speed Spin	0 – 500 RPM
LED Light	Yes
Weight (without cable)	6.5 lbs



**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, 5/16" x 25' Inner Core Bulb Head Cable with Inner Drum, Charger, 5 Gallon Storage Bucket

**Related Accessories:**

- 48-53-2561 5/16" x 25' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating;
- 48-53-2562 5/16" x 25' Inner Core Drop Head Cable w/ RUST GUARD™ Plating;
- 48-53-2563 1/4" x 25' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating;
- 48-53-2564 1/4" x 25' Inner Core Drop Head Cable w/ RUST GUARD™ Plating

**M12™ TRAPSSNAKE™ 6' Toilet Auger Kit**

2576-21 (2576-20 Tool-Only)

**Specifications:**

RPM	0 – 500
Cable Lock	Yes
Cable Size	6' x 1/2"
Cable Head	Retriever Bulb
Replacement Cables	Available
Weight	9.0 lbs



**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Cable, Charger

**Related Accessories:**

- 48-53-2576 TRAPSSNAKE™ 6' Toilet Auger Replacement Cable;
- 48-22-2576 TRAPSSNAKE™ Toilet Auger Case;
- 2575-21 M12™ TRAPSSNAKE™ Driver Upgrade Kit



**M12™ TRAPSSNAKE™ 4' Urinal Auger Kit**

2574-21 (2574-20 Tool-Only)

**Specifications:**

RPM	0 – 500
Cable Lock	Yes
Cable Size	4' x 3/8"
Cable Head	Bulb
Replacement Cables	Available
Weight	6.4 lbs



**Includes:** (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Cable, Charger

**Related Accessories:**

- 48-53-2577 TRAPSSNAKE™ 4' Urinal Auger Replacement Cable;
- 48-22-2577 TRAPSSNAKE™ Urinal Auger Case;
- 2575-21 M12™ TRAPSSNAKE™ Driver Upgrade Kit

**M12™ AIRSNAKE™ Drain Cleaning Air Gun Kit**

2572B-21, (2572B-20 Tool-Only)

**Specifications:**

Max Drain Line Capacity	1" – 4", Up to 35'
Automatic Pressure Loading	Yes
Variable Pressure	0 – 50 PSI
Variable Pressure Dial	Yes
LED Light	Yes
Length / Weight	20.8" / 7.1 lbs



**Includes:** 2572B-21 (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Charger;

**All Kits Include:** 2572B-20: 1" – 2" Drain Plug, 2" – 3" Drain Plug, 3" – 4" Drain Plug, Drain Shroud Attachment, Toilet Seal Attachment, 10" Extension, (3) Straight Connectors, 15° Offset Connector, Carrying Case



**M12™ ProPEX® Expansion Tool Kit**

2432-22XC, 2432-22 (2432-20 Tool-Only)

**Specifications:**

Capacity	3/8" – 1"
Auto-Rotate	Built-In
Head Compatibility	3/8" – 1" M12™ / Uponor
Dimensions (L x W x H)	7.1" x 3.7" x 12.8"
Weight	5.0 lbs



**Includes:** 2432-22XC (2) M12™ REDLITHIUM™ XC3.0 Battery Packs; 2432-22 (2) M12™ REDLITHIUM™ CP1.5 Battery Packs;

**All Kits Include:** (3) ProPEX® Expansion Heads (1/2", 3/4", 1"), Grease, Multi-Voltage Charger, Carrying Case

**Related Accessories:**

- 49-08-2400 ProPEX® Expander Cone Grease;
- 49-16-2403 3/8" ProPEX® Expansion Head;
- 49-16-2404 1/2" ProPEX® Expansion Head;
- 49-16-2405 5/8" ProPEX® Expansion Head;
- 49-16-2406 3/4" ProPEX® Expansion Head;
- 49-16-2408 1" ProPEX® Expansion Head



**M12™ FORCE LOGIC™ Press Tool Kit**

2473-22 (2473-20 No Jaw Kit)

**Specifications:**

Capacity	1/2" – 1-1/4" CU
Calibration Interval	32,000 Cycles (LED Indicator)
Approximate Cycle Time	5 Seconds
Press Force	5,400 lbs
Length / Weight	12.8" / 3.8 lbs



**Includes:** 2473-22 (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, (3) Jaws (1/2", 3/4", 1"), Charger, Carrying Case; 2473-20 (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, Charger, Carrying Case (No Jaws Included)

**Related Accessories:**

- 49-16-2450 1/2" CTS Jaw;
- 49-16-2451 3/4" CTS Jaw;
- 49-16-2452 1" CTS Jaw;
- 49-16-2453 1-1/4" CTS Jaw;
- 49-16-2450B 1/2" IPS Jaw;
- 49-16-2451B 3/4" IPS Jaw;
- 49-16-2451C 1/2" PEX Crimp (F1807 & F2159) Jaw;
- 49-16-2453C 3/4" PEX Crimp (F1807 & F2159) Jaw;
- 49-16-2454C 1" PEX Crimp (F1807 & F2159) Jaw;
- 49-16-2455C 1-1/4" PEX Crimp (F1807) Jaw;
- 49-16-2456C 1-1/2" PEX Crimp (F1807) Jaw



**M12™ No-Hub Driver Kit**

2455-22 (2455-20 Tool-Only)

**Specifications:**

Torque Settings (3-Mode)	60 in-lbs / 80 in-lbs / Drill
RPM	0 – 750
Chuck Type	1/4" Hex
Calibration Interval	25,000 Cycles (LED Indicator)
Weight	2.7 lbs



**Includes:** (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, (3) SHOCKWAVE™ Nut Drivers (1/4", 5/16", 3/8"), Charger, Carrying Case