




# COLLECT<sub>AN</sub>DRAIN<sup>®</sup>

## Model 5400A


100 Quaker Lane, Malvern, PA 19355 • Phone: 610-240-4900 • Fax: 610-240-4906 • www.testandrain.com



The **COLLECT<sub>AN</sub>DRAIN<sup>®</sup>** Family of products are auxiliary “low point” drain and/or condensate collecting assemblies available in several configurations to meet and exceed the sections of NFPA 13 and NFPA 25 addressing drainage in dry and preaction sprinkler systems.

### The Model 5400A **COLLECT<sub>AN</sub>DRAIN<sup>™</sup>**




The Model 5400A is the latest addition to the AGF Manufacturing COLLECT<sub>AN</sub>DRAIN<sup>®</sup> product line. The 5400A goes beyond the prevention features of the Model 5100A and 5200A by providing a temperature controlled environment to prevent costly system failures due to freezing of the condensation collectors along with localized and panel notification of required attention. The easily mounted, lockable steel enclosure is finished in a highly visible red powder coat and includes appropriate signage. Inside the insulated and heated cabinet is mounted a traditionally configured condensation collector (drum drip) with a float switch to monitor condensation accumulation levels. When condensation rises to the level of needing maintenance the Model 5400A COLLECT<sub>AN</sub>DRAIN<sup>®</sup> activates an audible alarm and a red LED warning light and can notify the Fire Control Panel. The 5400A features a heater with an integral thermostat that operates only when needed, reducing energy use while maintaining a temperature safely above freezing. In addition to its operational features the Model 5400A includes a TEST button to confirm alarm functionality and an externally mounted THERMOMETER that monitors internal enclosure temperatures.




**Reliability, Versatility, Code Compatibility**

## The Model 5400A COLLECT<sub>AN</sub>DRAIN<sup>®</sup> Features and Dimensions

- The Model 5400A features a secure locking, red powder coated, insulated cabinet designed to increase visibility, resist corrosion, and provide required signage adhering to NFPA guidelines.
- The Model 5400A is equipped with a temperature sensitive internal heating element to prevent excess condensation in the drum drip from freezing.
- The Model 5400A includes a float switch that activates an audible alarm and visual signal to notify when the auxiliary drain has reached capacity and the drum drip requires draining.
- An integral TEST button allows for system testing and the externally mounted THERMOMETER allows for easy monitoring of temperature conditions inside the cabinet.
- The Model 5400A Cabinet, with four mounting tabs, is sized to be easily attached to structure walls, columns, or I-Beams.
- Each unit is fully assembled and ready to be attached to dry pipe systems using galvanized piping components and 1" brass quarter turn ball valves with chrome plated brass balls.



## Meet the COLLECT<sub>AN</sub>DRAIN<sup>®</sup> Family



5100ALBV

5300A

5300ALBV

5100A

5200A

5400A

Patent Pending



**AGF Manufacturing Inc.**  
100 Quaker Lane, Malvern, PA 19355  
Phone: 610-240-4900  
Fax: 610-240-4906  
www.testandrain.com

Job Name: \_\_\_\_\_

Architect: \_\_\_\_\_

Engineer: \_\_\_\_\_

Contractor: \_\_\_\_\_