

# CONCEALED SPRINKLER COVER PLATES

## RESIDENTIAL CONCEALED COVER PLATES

### THE INCH® One Inch Adjustable Residential Concealed Sprinklers Finish/Part No. 135°F (57°C)

- Chrome: 332891                      • Black: 332892-B
- White: 332892
- **cULus Listed: GL4906** - 155°F (68°C) Sprinkler with 135°F (57°C) plate
- **FOR FULL DESCRIPTION SEE DATA SHEET: GFS-360**



### Domed Adjustable Residential Concealed Sprinklers Finish/Part No. 135°F (57°C)

- Chrome: 326046                      • Black: 326048-B
- White: 326048
- **cULus Listed: GL4147, GL4947** - 155°F (68°C) Sprinkler with 135°F (57°C) plate
- **FOR FULL DESCRIPTION SEE DATA SHEET: GFS-350**



## COMMERCIAL CONCEALED COVER PLATES

### THE INCH® One Inch Adjustable Concealed Sprinklers

#### 2 3/4" Diameter Finish/Part No. 135°F (57°C)

- Chrome: 332724                      • Black: 332726-B
- White: 332726

#### 2 3/4" Diameter Finish/Part No. 155°F (68°C)

- Chrome: 332729                      • Black: 332731-B
- White: 332731

#### 3 5/16" Diameter Finish/Part No. 135°F (57°C)

- Chrome: 332704                      • Black: 332706-B
- White: 332706

#### 3 5/16" Diameter Finish/Part No. 155°F (68°C)

- Chrome: 332709                      • Black: 332711-B
- White: 332711



- **cULus Listed: GL5606, GL5653** - 135°F (57°C) Sprinkler with 135°F (57°C) plate; 155°F (68°C) Sprinkler with 135°F (57°C) plate; 155° (68°C) Sprinkler with 155°F (68°C) plate; 175° (79°C) Sprinkler with 155°F (68°C) plate; 200°F (93°C) Sprinkler with 155°F (68°C) plate

- **FM Approved: GL5606, GL5653** - 155°F (68°C) Sprinkler with 135°F (57°C) plate; 175° (79°C) Sprinkler with 155°F (68°C) plate; 200°F (93°C) Sprinkler with 155°F (68°C) plate

- **FOR FULL DESCRIPTION SEE DATA SHEETS: GFS-150a & GFS-150b**

### THE INCH® One Inch Adjustable Dry Concealed Sprinklers

#### Finish/Part No. 135°F (57°C)

- Chrome: 332891                      • Black: 332892-B
- White: 332892

#### Finish/Part No. 155°F (68°C)

- Chrome: 332897                      • Black: 332898-B
- White: 332898

- **cULus Listed: GL5634, GL5689, GL8134, GL8189** - 135°F (57°C) Sprinkler with 135°F (57°C) plate; 155°F (68°C) Sprinkler with 135°F (57°C) plate; 175° (79°C) Sprinkler with 155°F (68°C) plate; 200°F (93°C) Sprinkler with 155°F (68°C) plate

- **FM Approved: GL5634, GL5689** - 135°F (57°C) Sprinkler with 135°F (57°C) plate; 155°F (68°C) Sprinkler with 135°F (57°C) plate; 175° (79°C) Sprinkler with 155°F (68°C) plate; 200°F (93°C) Sprinkler with 155°F (68°C) plate

- **FOR FULL DESCRIPTION SEE DATA SHEETS: GFS-500a & GFS-500b**



# CONCEALED SPRINKLER COVER PLATES

## COMMERCIAL CONCEALED COVER PLATES

### Flat Plate “3-Step” Concealed Sprinklers

#### Finish/Part No. 135°F (57°C)

- Chrome: 325435 • Black: 325437-B
- White: 325437

#### Finish/Part No. 155°F (68°C)

- Chrome: 325440 • Black: 325442-B
- White: 325442



- **cULus Listed:** *GL2804, GL2854, GL4204, GL4254, GL5604, GL5605, GL5637, GL5638, GL5654, GL5681, GL5682, GL8137, GL8181* - 135°F (57°C) Sprinkler with 135°F (57°C) plate; 155°F (68°C) Sprinkler with 135°F (57°C) plate; 155° (68°C) Sprinkler with 155°F (68°C) plate; 175° (79°C) Sprinkler with 155°F (68°C) plate; 200°F (93°C) Sprinkler with 155°F (68°C) plate; **GL5655** - 135° (57°C) Sprinkler with 135°F (57°C) plate; 155°F (68°C) Sprinkler with 135°F (57°C) plate
- **FM Approved:** *GL5654* - 135°F (57°C) Sprinkler with 135°F (57°C) plate; 155°F (68°C) Sprinkler with 135°F (57°C) plate; 155° (68°C) Sprinkler with 155°F (68°C) plate; 175° (79°C) Sprinkler with 155°F (68°C) plate; 200°F (93°C) Sprinkler with 155°F (68°C) plate; **GL5637, GL5681** - 135° (57°C) Sprinkler with 155°F (68°C) plate; 155°F (68°C) Sprinkler with 200°F (93°C) plate
- **LPCB, CE Approved:** *GL5604, GL5654* - 135°F (57°C) Sprinkler with 135°F (57°C) plate; 155°F (68°C) Sprinkler with 135°F (57°C) plate; 155° (68°C) Sprinkler with 155°F (68°C) plate; 175° (79°C) Sprinkler with 155°F (68°C) plate; 200°F (93°C) Sprinkler with 155°F (68°C) plate
- **FOR FULL DESCRIPTION SEE DATA SHEETS:** **GFS-130a, GFS-720a, GFS-510a, GFS-130b, GFS-720b, GFS-510b**

### Domed Adjustable Concealed Sprinklers

#### Finish/Part No. 135°F (57°C)

- Chrome: 326046 • Black: 326048-B
- White: 326048

#### Finish/Part No. 155°F (68°C)

- Chrome: 326051 • Black: 326053-B
- White: 326053



- **cULus Listed:** *GL2845, GL4245, GL5622, GL5646, GL5649, GL5657, GL8104, GL8145, GL8149* - 135°F (57°C) Sprinkler with 135°F (57°C) plate; 155°F (68°C) Sprinkler with 135°F (57°C) plate; 175° (79°C) Sprinkler with 155°F (68°C) plate; 200°F (93°C) Sprinkler with 155°F (68°C) plate
- **FOR FULL DESCRIPTION SEE DATA SHEETS:** **GFS-140a, GFS-730a, GFS-215, GFS-515a, GFS-730b**
- **cULus Listed:** *GL2856, GL4256, GL5677, GL5678, GL8173, GL8177* - 135°F (57°C) Sprinkler with 135°F (57°C) plate; 155°F (68°C) Sprinkler with 135°F (57°C) plate; 155°F (68°C) Sprinkler with 155°F (68°C) plate; 175° (79°C) Sprinkler with 155°F (68°C) plate; 200°F (93°C) Sprinkler with 155°F (68°C) plate
- **FOR FULL DESCRIPTION SEE DATA SHEETS:** **GFS-140b, GFS-515b**

### E.C. Domed Adjustable Concealed Sprinklers

#### Finish/Part No. 135°F (57°C)

- Chrome: 329489 • Black: 329491-B
- White: 329491

#### Finish/Part No. 155°F (68°C)

- Chrome: 329495 • Black: 329497-B
- White: 329497



- **cULus Listed:** *GL5613, GL8113* - 135°F (57°C) Sprinkler with 135°F (57°C) plate; 155°F (68°C) Sprinkler with 135°F (57°C) plate; 175° (79°C) Sprinkler with 155°F (68°C) plate
- **FOR FULL DESCRIPTION SEE DATA SHEET:** **GFS-230**
- **cULus Listed:** *GL8114* - 135°F (57°C) Sprinkler with 135°F (57°C) plate
- **FOR FULL DESCRIPTION SEE DATA SHEET:** **GFS-235**

