


SUBMITTAL INFORMATION

Stainless Steel Tapping Sleeve 4"-12" - (FTSS-xxx-x-MJ style)



STAINLESS STEEL TAPPING SLEEVE WITH MECHANICAL JOINT OUTLET

Connecting Gasket is Buna-N per ASTM D2000.

Flange - 18-8 stainless steel. Optional carbon steel flange available.

Bolts, Nuts, & Washers - 18-8 stainless steel. Heavy hex nuts and washers are coated to prevent galling and maximize bolt efficiency.

Outlet Pipe - Schedule 5. 18-8 stainless steel except 4" is Schedule 10

3/4-14 No-Lead Brass Test Plug

Outlet Gasket - Buna-N compounded for water service, per ASTM D2000. Outlet gasket assures complete seal of outlet area.

Full Gasket - Gridded virgin SBR compounded for water service, per ASTM D2000. Full gasket gives 360° pipe coverage.

Armors - Heavy gage 18-8 stainless steel are vulcanized to gasket and recessed to bridge the gap between lugs.

3/16" lug (1/4" lug if using a 3/4" bolt.)

NOM. PIPE SIZE	SLEEVE O.D. RANGE	CATALOG NUMBER	BY	SS.** OUTLET SIZE/CODE	APPROX. WT.	NOMINAL DIMENSIONS - INCHES			SADDLE THICKNESS (GAGE)	STRAP THICKNESS (GAGE)	BOLT SIZE	No. BOLTS	✓ SUBMITTED ITEM(S)
						A	B	C					
4"	4.50-4.80	FTSS-480-	<div></div>	4 -MJ	38	4-1/4	5-3/16	15	.105" (12)	.075" (14)	5/8"x6-1/2"	8	
	4.80-5.00	FTSS-500-											
	5.10-5.30	FTSS-530-											
	5.20-5.40	FTSS-540-											
6"	6.63-7.00	FTSS-700-	<div></div>	4 -MJ	42	4-1/4	5-3/16	15	.105" (12)	.075" (14)	5/8"x6-1/2"	8	
	6.90-7.30	FTSS-730-		6 -MJ	47								
	7.30-7.50	FTSS-750-			47	6-13/32	5-1/2	15			5/8"x6-1/2"	8	
	8"	8.63-9.05		FTSS-905-	<div></div>	4 -MJ	42	4-1/4			5-3/16	15	.105" (12)
9.05-9.30		FTSS-930-	6 -MJ	49		6-13/32	5-1/2		15	5/8"x6-1/2"			
9.30-9.60		FTSS-960-		75				8-13/32			5-5/8	20	
9.45-9.75		FTSS-975-	8 -MJ	75									
10"	10.75-11.10	FTSS-1110-	<div></div>	4 -MJ	47	4-1/4	5-3/16	15	.105" (12)	.075" (14)	5/8"x6-1/2"	8	
	11.10-11.40	FTSS-1140-		6 -MJ	53	6-13/32	5-1/2	15			5/8"x6-1/2"	8	
	11.40-11.70	FTSS-1170-		8 -MJ	79	8-13/32	5-5/8	20			5/8"x6-1/2"	12	
	11.85-12.15	FTSS-1215-		10 -MJ	99	10-31/32	6-1/8	20			3/4"x8-1/2"	12	
12"	12.75-13.20	FTSS-1320-	<div></div>	4 -MJ	50	4-1/4	5-3/16	15	.105" (12)	.075" (14)	5/8"x6-1/2"	8	
	13.20-13.50	FTSS-1350-		6 -MJ	55	6-13/32	5-1/2	15			5/8"x6-1/2"	8	
	13.50-13.80	FTSS-1380-		8 -MJ	86	8-13/32	5-5/8	20			5/8"x6-1/2"	12	
				10 -MJ	104	10-31/32	6-1/8	20			3/4"x8-1/2"	12	
	14.10-14.40	FTSS-1440-		12 -MJ	138	12-27/64	6-1/4	24			3/4"x8-1/2"	14	

** To order: Add Flanged Outlet Size to catalog number. Example: The complete FTSS catalog number for a 6" pipe (6.90 O.D.) with a 4" stainless steel flange is FTSS-730-4-MJ. For a carbon steel flange, add "A" to the catalog number. Example: FTSS-710-4A-MJ

FEATURES

- Body, straps and UNC threaded bolts are made of 18-8 stainless steel. Flange can be either 18-8 stainless steel or ASTM A36 carbon steel.
- All welds are fully passivated for corrosion resistance
- Tapping sleeves rated for 250 psi working pressure on 4"-12"
- Outlet gaskets are Buna-N rubber (ASTM 2000)

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

09/24/14

Submitted By: