

MALLEABLE IRON HEXAGON BUSHINGS CLASS 150

NPS	Width of Head A	Height of Head B	Length of External Threads C (min)	Length of Internal Threads D (min)	Inside or Outside Head
*1/4 x 1/8	0.64	0.14	0.44	0.26	Outside
*3/8 x 1/4	0.68	0.160	0.48	0.40	Outside
*3/8 x 1/8	0.68	0.16	0.48	0.25	Outside
*1/2 x 3/8	0.87	0.19	0.56	0.36	Outside
*1/2 x 1/4	0.87	0.19	0.56	0.32	Outside
*1/2 x 1/8	0.87	0.19	0.56	0.25	Outside
*3/4 x 1/2	1.15	0.22	0.63	0.53	Outside
*3/4 x 3/8	1.15	0.22	0.63	0.36	Outside
*3/4 x 1/4	1.15	0.22	0.63	0.32	Outside
*3/4 x 1/8	1.15	0.22	0.63	0.25	Outside
*1 x 3/4	1.42	0.25	0.75	0.50	Outside
*1 x 1/2	1.42	0.25	0.75	0.43	Outside
*1 x 3/8	1.12	0.30	0.75	0.36	Inside
*1 x 1/4	1.12	0.30	0.75	0.32	Inside
*1 x 1/8	1.12	0.30	0.75 <td 0.25	Inside	
1 1/4 x 1	1.76	0.28	0.80	0.58	Outside
1 1/2 x 1 1/4	2.00	0.31	0.83	0.77	Outside
2 x 1 1/2	2.48	0.34	0.88	0.70	Outside
2 1/2 x 2	2.98	0.37	1.07	0.75	Outside
3 1/2 x 3	4.62	0.43	1.18	0.98	Outside
4 x 3 1/2	5.20	0.50	1.22	1.03	Outside

* Made from Malleable Iron or Steel

