



## General Product Specification

<b>Item No.</b>	GFMF100
-----------------	---------

<b>Date</b>	6/12/2016
-------------	-----------

<b>No. Pages</b>	1
------------------	---

**Product Description:**

<b>Style</b>	Pads
<b>Item Size (each)</b>	15" x 18"
<b>Color</b>	Gray
<b>Composition</b>	100% Polypropylene
<b>Structure</b>	3-ply composition, fine fiber outer layers on a straight meltblown center
<b>Technology</b>	Meltblown
<b>Absorbency</b>	Universal (Hydrophilic)
<b>Bonding</b>	Thermal bonded

<b>Intended Application</b>	Universal (Hydrophilic) absorbent
-----------------------------	-----------------------------------

<b>Absorbency Capacity</b>	25.2 gallons per bale
----------------------------	-----------------------

**Packaging Description:**

<b>Packaging Configuration</b>	bale
<b>Items Per Package</b>	100 Pads/bale
<b>Container Type</b>	box

<b>Package Weight</b>	11.5 lbs
<b>Package Dimensions</b>	16" x 19" x 17"

**Physical Properties:**

Parameter	MBT Test Method	Units	Nominal	(+/-) Tolerance
Basis Weight	MBTTM001	LBS	11.5	2
Absorbency** (med Oil)	MBTTM012	GAL	25.2	7
3" Tensile Strength	MBTTM02	LBS	17	3
Color	N/A			

The above properties are "nominal" values used for process control when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or environment being applied, stored, or shipped.

\*\* The "Absorbency" spec and "MBTTM012" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

<b>Attributes</b>	Product will be free of foreign material contamination, rips, holes and tears.
<b>Labeling</b>	
<b>Certification</b>	Make no changes in basic process or composition without notifying customer.