

Eaton SC-30

Catalog Number: SC-30

Eaton Bussmann series SC fuse, Current-limiting time-delay fuse, Rejection style, 30 A, Class G, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 10 kAIC at 300 Vdc|100 kAIC at 480 Vac, Standard, 480 V, 300 Vdc

General specifications

Product Name	Catalog Number
Eaton Bussmann series SC fuse	SC-30
UPC	Product Length/Depth
051712250306	0.41 in
Product Height	Product Width
1.62 in	0.41 in
Product Weight	Warranty
0.18 lb	Not Applicable
Compliances	
RoHS Compliant	

Electrical rating

Amperage Rating

30 A

Interrupt rating

10 kAIC at 300 Vdc

100 kAIC at 480 Vac

Response time

12 sec at 200%

Voltage rating

480 Vac, 300 Vdc

Physical details

Packaging type

Standard

General information

Class

Class G

Connection

Ferrule end x ferrule end

Fuse indicator

Non-indicating

Special features

Ferrule design, Type P

Resources

Multimedia

[Bussmann series Fuseology](#)

Specifications and datasheets

[Eaton Specification Sheet - SC-30](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)