

SPECIFICATIONS DRLC70 EXHAUST FAN WITH LIGHT



70 CFM/4.0 Sones @ 0.10" SP.

Grill

DRLC701 - Oil Rubbed Bronze Finish: 131/4" diameter.

DRLC702 - Nickel Finish: 131/4" diameter. DRLC703 - White Finish: 131/4" diameter.

Light Lens

Ribbed frosted glass light lens.

Light Housing

Heavy gauge cold rolled steel c/w baked enamel finish; locks in place on the grill via two integral tabs.

Blower Wheel

One piece polymeric wheel, 41/2" diameter, 1" wide, with 10 fins.

Motor

Single coil plug-in, two pole motor, life time lubrication, thermally protected. Rated 120 volts, 60 hz., 1.6 amps.

Fan Housing

23 ga. Galvanized metal housing, dimensions $7^3\!\!\,/\!\!\!s"$ x $7^5\!\!/\!\!\!s"$ x $5^7\!\!/\!\!s"$, double metal thickness mounting tabs.

Duct Collar

Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

Ventilating Area

For bathrooms up to 65 sq. ft. for other rooms up to 85 sq. ft.

Lighting

2 - 26W medium base fluorescent lamps (2-60W type A19 incandescent bulbs can also be used) (lamps not included)

73/8" 77/8" 57/8"

Unit Mounting

Rated Type IC for ceilings insulated to R-40. Designed to mount in ceilings with at least 6" of clearance. The unit will mounts directly to the joist with a rough in opening of 7^5 %" x 7^7 /8". The housing will mount through drywall thickness up to 3/4".

131/4"

• Single Pack Shipping Info

Box Dim: 111/2" x 131/4" x 91/2"

EXPANDED PERFORMANCE											
								Sones	Fan Speed	Maximum	
	Static Pressure (inches of w.g.)								RPM	Fan Watts	Amps
	0	0.05	0.1	0.125	0.15	0.2	0.25				
Air Flow - CFM	77	73	70	69	68	66	64	4.0	1725	44.0	1.6

PROJECT						ARCHITECT				
LOCATION						ENGINEER				
CONTRACTOR						SUBMITT	SUBMITTED BY DATE			
FAN MODE NUMBER NUMBER		IN W.G.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS		





U.S.: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 ● 877-304-3785 Fax: (610) 696-8048 Canada: Brampton, Ontario Tel: 800-250-8767 Fax: (905) 456-1015

Specifications subject to change without notice.