





420 CFM/1.5 Sones @ 0.10" SP. 381 CFM @ 0.25 SP.

Grill

White, metal grill secured in place with 4 screws; easily removed if necessary, dimensions - 23^5 /s" x 14^3 /4".

Blower Wheel

Balanced polymeric dual inlet blower wheel secured in place using a hex nut.

Motor

High efficiency, permanent split capacitor motor (PSC); life time lubrication, suitable for continuous operation. Rated 115/120 volts, 60 Hz.

Fan Housing

22 gauge galvanized steel housing. Overall dimensions: 12³/₄"x 12³/₄"x 21¹/₂". Includes ¹/₂" acoustic insulation.

Duct Collar

41/2" x 181/2" duct connector with 2 aluminum backdraft dampers.

Electrical Connections


 $1\!/\!_2$ " electrical knockouts provided. Easy wiring access via either top or side connection.

Single Pack Shipping Info

Shipping Weight: 34 lbs.

Unit Mounting

24" on center joists, using the 4 supplied housing mounting angles. The housing mounting angles can be adapted for vertical or right angle discharge mounting (hardware not provided).



EXPANDED PERFORMANCE												
								Sones	Fan Speed			
	Static Pressure (inches of w.g.)							@ .1 SP	RPM	Power Watts	Amps	
	0	0.05	0.1	0.2	0.25	0.375	0.5					
Air Flow - CFM	440	430	420	397	381	341	264	1.5	978	118	1.1	

PROJECT							ARCHITECT				
LOCATION							ENGINEER				
CONTRACTOR							SUBMITTED BY DATE				
FAN Number	MODEL Number	CFM	IN W.G.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS		
l .											



Air King: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 ● 877-304-3785 Fax: (610) 696-8048

Specifications subject to change without notice. Updated 2-16