



SPECIFICATIONS
PIN
RANGE HOODS

Professional Series Insert

- **Dimensions**

Overall bottom projection: 18"
Height: 12"
Overall Width: 32"

- **Hood**

All metal Galvanized Steel with stainless steel fascia.

- **Lighting**

2 - PAR16 medium screw base, 45 watt maximum Halogen lamps (not included).

- **Ducting Options**

Vertical or Horizontal ducting through ducting transition (not included) specified for size of motor.

- **Cut Out Opening Size**



Width: 30.5"
Depth: 17.25"

- **Filters**

Grease Baffles: Dishwasher safe, Stainless Steel baffles (included).

- **Available Finishes**

Stainless Steel



MODEL	HVI	CFM/SONES @ 0.1 WG	REQUIRED DUCT SIZE	LIGHTING	FULL LOAD AMPS	BREAKER ³ SIZE
	HIGH	MEDIUM	LOW			
PIN300	300/1.5	N/A ¹	N/A ¹	6" round	2-45W Halogen	1.7 amps
PIN500	500/4.5	N/A ²	300/1.5 ²	6" round	2-45W Halogen	1.9 amps
PIN600	600/5.5	500/4.5	300/1.5	6" round	2-45W Halogen	2.1 amps
PIN900	900/11.0	600/5.5	400/2.0	8" round	2-45W Halogen	6.5 amps
PIN1200	1200/15.0	900/11.0	400/2.0	10" round	2-45W Halogen	8.0 amps

¹ All speed selections of control panel operated at same speed • ² Speed selections II and III of control panel operate at same speed
³ Breaker Size is listed at the recommended minimum size. Installation must be in accordance with all applicable codes and standards.
CFM = cubic feet per minute • Sones = sound level measurement

PROJECT							ARCHITECT				
LOCATION							ENGINEER				
CONTRACTOR							SUBMITTED BY			DATE	
FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS		



U.S.: West Chester, PA 19380
Phone: (877) 304-3785
Fax: (610) 696-8048
Email: sales@airkinglimited.com

Canada: Brampton, Ontario L6T 2J3
Phone: (905) 456-2033
Fax: (905) 456-1015
Email: casales@airkinglimited.com