NEWPORT BRASS

SHOWER VALVE

1-743

Features

1/2" Thermostatic Valve For Shower Installations

- Solid brass construction
- Provides anti-scald protection and temperature regulation
- Integrated transfer valve allowing shared functions on ports 1 & 2
- \bullet High-temperature safety stop ensures water temperature maximum is 100° F (37.7 C)°
- Built in check valves with service stops
- 1/2" NPT female thread (inlet and outlet) valve body
- Mounting tabs located on rough-in for secure installation option
- 3 way diverter configuration
- 7.75 gpm (gallons per minute) flow rate (@ 45 psi)
- Requires Newport Brass BP Valve Trim (many options available, sold-separately)

Codes / Standards Compliance

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1
- IAPMO/Cupc
- IPC
- ASSE 1016
- All applicable US Federal and State material regulations



Colors / Finishes

- 10B: Oil Rubbed Bronze
- 15: Polished Nickel
- 15S: Satin Nickel PVD
- 26: Polished Chrome
- Other: Refer to the Newport Brass catalog for additional color/finish options.

Specified Model


Model	Description	Colors Finishes
1-743	1/2" Thermostat Valve For Shower Installations	□ 10B □ 15 □ 15S □ 26 □ Other

Product Specification Add "Color / Finish" suffix to Model number, below.

The Thermostat Valve for shower installations shall be made of solid brass construction. Valve shall provide anti-scald protection ensuring water temperature maximum is 100° F (37.7 C)° Valve shall have a maximum flow rate of 7.75 gpm (gallons per minute) @ 45 psi. Valve inlets shall include integral stops and incorporate 1/2" NPT female thread for inlets and outlet. Valve shall incorporate mounting tabs along the back surface. Valve shall have a maximum flow rate of 7.75 gpm (gallons per minute) @ 45 psi. Thermostat Valve for shower installations shall be Newport Brass Model 1-743.

1-743

PRODUCT DIMENSIONS (Units are in inches)



Shower Valve 1-743



t: 949.417.5207 | www.newportbrass.com ©2016 Brasstech, Inc.

Page 2 of 2 Spec_1-743