



SPECIFICATION SHEET

280-EV6151

EVOLUTION™ DELUXE 6151 STANDARD BRIM HARD HAT

- Meets ANSI Z89.1-2014 Type I Class E requirements (Class C for Vented)
- High-Density Polyethylene (HDPE) shell designed with five raised channels running across the top for strength, and an extended back area for extra protection
- 6-Point polyester textile suspension system offers unrivaled comfort without compromising performance
- Unique "3D Adjustment" provides a precise fit using harness depth settings unlike any other hard hat on the US market today
- Revolution™ Wheel Ratchet is easy to use and creates a firm comfortable fit
- Chamlon™ sweatband
- Universal accessory slots accepts virtually any competitors' accessories
- Packed ready-to-wear with no installation of the suspension required
- Also meets the ANSI requirements for Reverse Donning and Lower Temperature

APPLICATIONS

- Construction
- Oil & gas
- Mining
- Demolition
- High pressure jetting
- Energy companies
- Certain emergency services (FEMA & USAR)
- High-risk environments where high impact situations are of concern

CARE INSTRUCTIONS

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature.

TECHNICAL DATA

MATERIAL	Shell: High Density Polyethylene, Recyclable Suspension: HDPE strap & clips, polyester straps Sweatband: Egyptian cotton core with PU coating
COLOR	<input type="checkbox"/> White (-10) <input type="checkbox"/> Green (-30) <input type="checkbox"/> Blue (-50) <input type="checkbox"/> Bright Orange(-OR) <input type="checkbox"/> Black (-11) <input type="checkbox"/> Pink (-39) <input type="checkbox"/> Red (-60) <input type="checkbox"/> Lime Yellow (-LY) <input type="checkbox"/> Yellow (-20) <input type="checkbox"/> Gray (-40)
HAT SIZE	6 5/8 - 8 (20 7/8" - 25")
EACH WEIGHT	13.2 oz / 374.2 g
PACKAGING	10 per case
CASE	9.5" x 23" x 18" / 24.1cm x 58.4cm x 45.7cm
CASE WEIGHT	8.4 lbs / 3.8 kg
COO	USA

BARCODES

ITEM	EACH	DOZEN	CASE
<input type="checkbox"/> 280-EV6151-10	5038428136716	---	5038428811934
<input type="checkbox"/> 280-EV6151-11	5038428160223	---	5038428813280
<input type="checkbox"/> 280-EV6151-20	5038428136723	---	5038428811941
<input type="checkbox"/> 280-EV6151-30	5038428136730	---	5038428811958
<input type="checkbox"/> 280-EV6151-39	5038428143646	---	5038428812351




BARCODES CONT.

<input type="checkbox"/> 280-EV6151-40	5038428151146	---	5038428812979
<input type="checkbox"/> 280-EV6151-50	5038428136747	---	5038428811965
<input type="checkbox"/> 280-EV6151-60	5038428136754	---	5038428811972
<input type="checkbox"/> 280-EV6151-LY	5038428136785	---	5038428812009
<input type="checkbox"/> 280-EV6151-OR	5038428136778	---	5038428811996
<input type="checkbox"/> 280-EV6151S-10	5038428136853	---	5038428812078
<input type="checkbox"/> 280-EV6151S-20	5038428136860	---	5038428812085
ITEM	EACH	DOZEN	CASE
VENTED HARD HATS (CLASS C)			
<input type="checkbox"/> 280-EV6151V-10	5038428136815	---	5038428812030
<input type="checkbox"/> 280-EV6151V-20	5038428136822	---	5038428812047
<input type="checkbox"/> 280-EV6151V-40	5038428814171	---	5038428239615
<input type="checkbox"/> 280-EV6151V-50	5038428021449	---	5038428813228
<input type="checkbox"/> 280-EV6151V-LY	5038428192217	---	5038428813785
<input type="checkbox"/> 280-EV6151V-OR	5038428018890	---	5038428813136
<input type="checkbox"/> 280-EV6151SV-10	5038428136877	---	5038428812092
<input type="checkbox"/> 280-EV6151SV-20	5038428136884	---	5038428812108
<input type="checkbox"/> 280-EV6151SV-50	5038428021494	---	5038428813242

DIMENSIONS (in)

	OSFA					
A	11.5 / 29.2					
B	6.375 / 16.2					



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

968 Albany Shaker Road | Latham, NY 12110 | 800-262-5755 | 518-861-0133 | Fax: 518-861-0144 | sales@pipusa.com | www.pipusa.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.