



# TASKI® swingo® XP-R & XP-M

The new generation of TASKI® swingo® XP machines deliver the comfort of stand-on cleaning with unmatched visibility around the machine. The battery operated auto scrubbers perform with unsurpassed agility offering the maneuverability of a much smaller machine and unbeatable cleaning performance.

**swingo XP-R** – Round disc cleaning for customers requiring intensive heavy duty cleaning

**swingo XP-M** – Micro rotational cleaning for customers requiring maximum autonomy

## Features & Benefits

- TASKI swingo XP-R and XP-M are engineered for sustainability through conservative use of water, chemicals and energy use with next generation electronics and software providing a best in class driving experience
- The rugged, ergonomic design maintains a professional image and increases operator satisfaction
- The intuitive machine design features total 360-degree visibility around machine allowing excellent cleaning and drying results for safe floors
- Larger solution tank capacity increases productivity up to 10% reducing water and energy consumption compared to standard scrubbers
- The operator can easily mount and dismount the machine with an automatic shut-off feature engaging upon dismount, keeping the operator and the environment safe
- Compatible with TASKI Intellitrail Intelligent GPS Fleet Tracking System for increased visibility to an entire machine fleet

## Applications

- Versatile machine can be used in a number of facilities seeking increased sustainability
- Ideal for dining facilities, hospitals, grocery stores and schools
- Can be used to utilize reduced water and energy consumption resulting in lower operational costs





# TASKI® swingo® XP-R & XP-M

| Technical data           | XP-M                   | XP-R                   | Technical data                           | XP-M                                 | XP-R                                 |
|--------------------------|------------------------|------------------------|--|--------------------------------------|--------------------------------------|
| Theoretical performance  | 4500 m <sup>2</sup> /h | 4500 m <sup>2</sup> /h | Machine weight ready to use (w/o driver) | 966 lb. (438 kg)                     | 996 lb. (452 kg)                     |
| Working width            | 29.5 in. (75 cm)       | 29.5 in. (75 cm)       | Dimensions (L x W x H)                   | 52 x 37 x 51 in. (131 x 95 x 130 cm) | 52 x 37 x 51 in. (131 x 95 x 130 cm) |
| Squeegee width           | 37 in. (95 cm)         | 37 in. (95 cm)         | Door pass through width (w/o squeegee)   | 31.5 in. (80 cm)                     | 31.5 in. (80 cm)                     |
| Solution tank-bag system | 30 gal. (113 L)        | 30 gal. (113 L)        | Brush system                             | 18 x 6 in. (45 x 15 cm)              | 1 x 15 in. (2 x 38 cm)               |
| Recovery tank            | 37 gal. (140 L)        | 37 gal. (140 L)        | Speed of brushes                         | 550 rpm                              | 165 rpm                              |
| Rated voltage            | 24 V                   | 24 V                   | Brush pressure min-max                   | 0.25 - 0.5 N/cm <sup>2</sup>         | 0.13 - 0.25 N/cm <sup>2</sup>        |
| Nominal consumption      | 1093 W                 | 1152 W                 | Cleaning speed                           | 4 mph (6 km/h)                       | 4 mph (6 km/h)                       |
| Battery capacity (max)   | 180 Ah/C5              | 180 Ah/C5              | Sound level                              | 69 dB(A)                             | 69 dB(A)                             |
| Battery run time         | 3 h 30 min.            | 3 h 15 min.            |  |                                      |                                      |
| Machine weight net       | 432 lb. (196 kg)       | 456 lb. (207 kg)       |  |                                      |                                      |

| Product                              | Product code |  |
|--------------------------------------|--------------|--|
| TASKI swingo XP-R (machine only)     | D7523097     |  |
| TASKI swingo XP-R Kit                | D6132987     |  |
| TASKI swingo XP-R + IntelliDose Kit  | D6133103     |  |
| TASKI swingo XP-R + IntelliTrail Kit | D1222171     |  |
| TASKI swingo XP-M (machine only)     | D7523098     |  |
| TASKI swingo XP-M Kit                | D6133218     |  |
| TASKI swingo XP-M + IntelliDose Kit  | D6133251     |  |
| TASKI swingo XP-M + IntelliTrail Kit | D1222173     |  |

| Accessories                           | Product code |  |
|---------------------------------------|--------------|--|
| TASKI IntelliDose kit for XP          | D7516242     |  |
| Filling hose with universal coupling  | D8502830     |  |
| Pad drive harpoon grip 450 mm         | D7514648     |  |
| Scrubbing brush Nylon 450 mm          | D7514650     |  |
| Scrubbing brush Nylon hard 450 mm     | D7515725     |  |
| Scrubbing brush abressive 450 mm      | D7515726     |  |
| TASKI IntelliPad S-Pad                | D6093826     |  |
| Contact pad 450 mm                    | D7514732     |  |
| Diamond pad 450 mm                    | D7515372     |  |
| Pad drive harpoon grip 38 cm          | D7522220     |  |
| Scrubbing brush standard 38 cm        | D7522221     |  |
| Scrubbing brush washed concrete 38 cm | D7522222     |  |
| Scrubbing brush abrasive 38 cm        | D7522223     |  |
| Scrubbing brush water saving 38 cm    | D7523342     |  |
| TASKI IntelliPad 15"                  | D6093762     |  |
| TASKI 4G IntelliTrail Hardware*       | D7524424     |  |

\*Does not include Data Plan