



PRODUCT FEATURES:

Power Options:

- **PWRX™ Long-Life Battery System:** Battery Life - 480,000 cycles (10 years @ 4,000 cycles per month). Advanced battery & electronics reduce the downtime and maintenance costs associated with changing batteries.
 Safety Circuitry prevents overheating in case of short circuit and protects the electronics from damage.
- **DC (Battery):** Includes CR-P2 lithium battery. Battery Life - 192,000 cycles (4 years @ 4,000 cycles per month).
- **Plug-In AC:** Includes Class 2 UL certified universal Plug-In AC transformer with 6' long power cord.
- **Hard-Wired AC:** Includes Class 2 UL certified universal Hard-Wired AC transformer (electrical box by others).
- **Multi-AC:** One AC transformer can power up to 15 faucets and/or flush valves in a daisy chain configuration.
POWER SUPPLY NOT INCLUDED.

Flexible Selectronic® Platform with programmable, multi-function sensor.

Easy & Flexible Installation: Single post mounting with optional 4" & 8" deck plate. Water resistant solenoid enclosure mounts to wall.

Durable Vandal-Resistant Brass Body: Ideal for high-use commercial applications.

Self-Cleaning Solenoid Valve: Wiper spring prevents clogging

Universal Voltage: AC power supplies and transformers have input voltage range of 100 - 240 VAC, 50/60 Hz.

Easy to Service Integrated Strainer: Patented integrated strainer protects solenoid from debris. Strainer is enclosed in removable debris cup for easy service.

Optional Purge Feature: Faucet can be programmed to open at a pre-determined time after last use to purge the faucet and water lines.

Safety Timer: Helps prevent vandalism by turning off the faucet if the sensor is covered for 55 seconds or more.

Low Lead: Faucet contains ≤ 0.25% total lead content by weighted average.



MODEL NUMBER:

- **PWRX™ LONG-LIFE BATTERY POWERED**
 - 6053.165** 0.5 GPM pressure compensating, vandal-resistant multi-laminar spray.
 - 6053.163** 1.5 GPM pressure compensating, vandal-resistant laminar flow outlet.
- **DC (BATTERY) POWERED**
 - 6055.165** 0.5 GPM pressure compensating, vandal-resistant multi-laminar spray.
 - 6055.163** 1.5 GPM pressure compensating, vandal-resistant laminar flow outlet.
- **PLUG-IN AC POWERED**
 - 6056.165** 0.5 GPM pressure compensating, vandal-resistant multi-laminar spray.
 - 6056.163** 1.5 GPM pressure compensating, vandal-resistant laminar flow outlet.
- **MULTI-AC POWERED**
 - 6057.165** 0.5 GPM pressure compensating, vandal-resistant multi-laminar spray.
 - 6057.163** 1.5 GPM pressure compensating, vandal-resistant laminar flow outlet.
- **HARD-WIRED AC POWERED**
 - 6059.165** 0.5 GPM pressure compensating, vandal-resistant multi-laminar spray.
 - 6059.163** 1.5 GPM pressure compensating, vandal-resistant laminar flow outlet.
- **OPTIONAL 4" or 8" Deck plates**
 - 605P.400** 4" brass deck plate with 1/4" fixation studs and quick spin nuts. (6-1/8" x 2-1/8" x 1/2")
 - 605P.800** 8" brass deck plate with 1/4" fixation studs and quick spin nuts. (10-1/8" x 2-3/8" x 1/2")
- **OPTIONAL Mixing Valve**
 - 605XTMV1070** Thermostatic mixing valve. 20" flexible stainless steel inlet hoses with 3/8" compression fittings. ASSE 1070 certified down to 0.35 gpm.

GENERAL DESCRIPTION:

Electronic faucet with proximity operation. Vandal-resistant brass construction with single post mounting. Water pressure range from 20 to 125 psi. Single inlet. Field-convertible rigid/swivel gooseneck spout. 18" flexible stainless steel hose with 3/8" compression fitting for connection to control box.

RECOMMENDED SPECIFICATION

Electronic, sensor-operated lavatory faucet shall feature a programmable, multi-function sensor and an electronically operated self-cleaning solenoid valve. Shall also feature a vandal resistant solid brass construction with single inlet and in-line strainer. Field-convertible rigid/swivel gooseneck spout. Shall meet ANSI A112.18.1 and ANSI 117.1 codes. Fitting shall be American Standard Model # 605_.16_.

CODES AND STANDARDS

These products meet or exceed the following codes and standards:

- ANSI A117.1
- ASME A112.18.1
- CSA B 125
- NSF 372

 MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES-CHECK LOCAL CODES

Other Aerators Available:

| Part Suffix | Description |
|-------------|---|
| V035 | 0.35 gpm (1.3 Lpm) PCA Vandal-Resistant Multi-Laminar Spray |
| L10 | 1.0 gpm (3.8 Lpm) PCA Vandal-Resistant Laminar Flow Outlet |
| L22 | 2.2 gpm (8.3 Lpm) PCA Vandal-Resistant Laminar Flow Outlet |

*PCA - Pressure Compensating

