

54V XR FLEXVOLT 190MM CIRCULAR SAW

DCS575T2

Blade Diameter	190 x 30mm
No Load Speed	5800rpm
Max. Depth of Cut (90°)	67mm
Max. Depth of Cut (45°)	49mm
Bevel Capacity	57°
Hand/Arm Vibration	2.5m/s ²



DCS575N - BARE UNIT

54V XR FLEXVOLT 190MM TRACKED CIRCULAR SAW

DCS576T2

Blade Diameter	190 x 30mm
No Load Speed	5800rpm
Max. Depth of Cut (90°)	61mm
Max. Depth of Cut (90°) with Rail	57mm
Max. Depth of Cut (45°)	43mm
Max. Depth of Cut (45°) with Rail	39mm
Bevel Capacity	57°
Hand/Arm Vibration	2.5m/s ²
Track Compatible	Yes



DCS576N - BARE UNIT

54V XR FLEXVOLT 190MM HIGH TORQUE CIRCULAR SAW

DCS577T2

Blade Diameter	190 x Diamond Bore
No Load Speed	5800rpm
Max. Depth of Cut (90°)	65mm
Max. Depth of Cut (45°)	50mm
Bevel Capacity	53°
Hand/Arm Vibration	2.5m/s ²



DCS577N - BARE UNIT

300MM DUAL PORT RIPPING FENCE FOR DCS577 HIGH TORQUE CIRCULAR SAW

DWS5100-XJ

Rip Capacity Left Side	300mm
Rip Capacity Right Side	360mm
Folds Down To	485mm x 76mm



DCS520NT - BARE UNIT IN TSTAK

54V XR FLEXVOLT PLUNGE SAW

DCS520T2

Blade Diameter	165 x 20mm
No Load Speed	2500 - 4200rpm
Max. Depth of Cut (90°)	59mm
Max. Depth of Cut (90°) with Rail	55mm
Max. Depth of Cut (45°)	44mm
Max. Depth of Cut (45°) with Rail	40mm
Bevel Capacity	47°



DCS520NT - BARE UNIT IN TSTAK

54V XR FLEXVOLT RECIPROCATING SAW

DCS388T2

No Load Stroke Rate	0 - 3000spm
Stroke Length	28.6mm
Max. Cutting Capacity Timber	300mm
Hand/Arm Vibration - Cutting Boards	12.5m/s ²



DCS388N - BARE UNIT