

3018WC • 18" Wine Captain® Model • Modular 3000 Series

FEATURES & BENEFITS

PERFORMANCE

INTERIOR/EXTERIOR

INTEGRATION



STAINLESS FRAME



INTEGRATED FRAME



STAINLESS FRAME (LOCK)



INTEGRATED SOLID



STAINLESS FRAME (HANDLELESS PANEL)*



STAINLESS SOLID (HANDLELESS PANEL)*

- Volume of 3.6 cu ft holds up to 31 wine bottles (750 ml)
- Temperature range: 38°F 65°F
- Convection cooling system rapidly and efficiently takes items to the set temperature
- U-Select® Control offers three distinct modes: Sparkling Wine: 38°F - 50°F, White Wine: 45°F - 55°F, Red Wine: 55°F - 65°F
- U-Select® Control with digital OLED display
- Rubber mounted compressor virtually eliminates vibration

Black interior is illuminated with LED theater lighting that automatically turns off when the door is closed, or can be set to stay on for 3, 6, or 24 hours Robust full-extension black vinyl coated wine racks allow for

- Robust full-extension black vinyl coated wine racks allow for easy access and prevent bottles from shifting
- Wine racks accommodate a variety of bottle shapes and sizes; the fourth and fifth racks allow for larger diameter wine and champagne bottles
- LowE coated, argon gas filled triple thermopane glass door provides protection from harmful UV light
- Standard commercial stainless steel handle is interchangeable with professional handle accessory
- The door swing on non-lock models is field reversible, and is shipped right-hand hinged
- Lock models must be ordered right-hand or left-hand hinged
- Robust, concealed and covered hinges with built-in door stop and closer
- Adjustable grille can be shifted front-to-back and up-and down
- Integrated model requires 3/4" custom panel of your choice, or can accept U-Line Euro Style Handleless Stainless Panel Accessory (must be ordered separately)
- Grille can accept an integrated toe-kick
- Four independently adjustable leveling legs; rear legs are adjustable from the front for ease of installation

MODEL DETAILS

Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
U-3018WCS-00B	115 / 60	Field Reversible	Stainless Frame	134 lb
U-3018WCS-13B	115 / 60	Right-Hand Hinged	Stainless Frame (Lock)	134 lb
U-3018WCS-15B	115 / 60	Left-Hand Hinged	Stainless Frame (Lock)	134 lb
U-3018WCINT-00B	115 / 60	Field Reversible	Integrated Frame	139 lb
U-3018WCINT-60B	115 / 60	Field Reversible	Integrated Solid	133 lb

ACCESSORIES

Model	Description	Finish	Shipping Weight
23074	Professional Door Handle, 1 1/4" Diameter	Stainless	2 lb
23073	Commercial Door Handle, 7/8" Diameter	Stainless	2 lb
U-ESPF45S*	Euro Style Handleless Panel, 18" Frame	Stainless	6 lb
U-ESP45S*	Euro Style Handleless Panel, 18" Solid	Stainless	9 lb


^{*}Installs on integrated models.




Modular 3000 Series • 18" Wine Captain® Model • 3018WC

DIMENSIONS

Dimensions shown apply to all finishes, including Integrated (INT) models with 3/4" integrated panel/frame installed.



CABINET CUT-OUT



SPECIFICATIONS

Model	3018WC	
Amps: Running	1.2	
Capacity: Volume (cu ft)	3.6	
Capacity: Wine Bottle (750 ml)	31	
Control Type	U-Select®	
Dimensions: Product Depth	23 7/16" / 590 mm	
Dimensions: Product Height	33 ¹¹ / ₁₆ " / 856 mm	
Dimensions: Product Width	17 ³ / ₄ " / 450 mm	
ENERGY STAR	N/A	
Panel Height	30" / 762 mm	
Panel Thickness	³ / ₄ " / 20 mm	
Panel Type	2 ³ / ₄ " / 70 mm Frame Panel or Solid Panel (-60 suffix)	
Panel Width	17 5/8" / 445 mm	
Product Weight: Max	125 lb	
Refrigerant Type	R600a	
Sabbath (Star K Certified)	Yes	
Temperature Range	38°F - 65°F	

INSTALLATION NOTES

When installing adjacent to wall, ensure 2 $\frac{1}{2}$ " clearance on hinged side for 90° door opening, allowing ample room for door handle.

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille air flow.

COOLING SYSTEM





ELECTRICAL REQUIREMENTS

This unit requires a grounded, polarized 115 VAC, $60\,Hz$, $15\,A$ power supply (normal household current).





Please visit U-Line.com to view this model's User Guide. All specifications are subject to change without notice.